

Aqua Mix® KnockDown®

1 Product Name

Aqua Mix® KnockDown®

2 Manufacturer

Custom Building Products
 Technical Services
 10400 Pioneer Boulevard, Unit 3
 Santa Fe Springs, CA 90670
 Customer Support: 800-272-8786
 Technical Services: 800-282-8786
 Fax: 800- 200-7765
 Email: contactus@cbpmail.net
custombuildingproducts.com

3 Product Description

A non-acidic honing powder that removes light surface scratches, moderate acid etching and wear patterns to produce a flat, even and honed finish. It is excellent for safely honing polished marble, limestone or travertine to a smooth honed surface when a honed, unpolished finish is desired.

Key Features

- Removes scratches, acid etching and traffic wear patterns
- Produces an even, flat, honed finish
- Safe, acid-free formula

Suitable Tile Types

Limestone, marble and travertine.

Limitations to the Product

- Do not allow product to come in contact with any non-recommended surface.
- Not intended for use as a pre-polish powder

4 Technical Data

Technical Chart

Property	Result
pH	7-9

Environmental Consideration

Complies with all Federal EPA and SCAQMD standards for VOC.

5 Instructions

General Surface Prep

Test a small area according to application instructions to determine desired results.

Equipment

- 175 to 300 RPM floor machine or 600 to 900 RPM hand polish machine
- Natural hair or synthetic fiber tan floor pads
- KnockDown™
- Protective plastic or blue painter's tape
- Spray bottle of water
- Wet vacuum
- Mop and bucket
- Squeegee



Application of Product

USE CHEMICAL-RESISTANT GLOVES, such as nitrile, when handling product.

Read entire label before using. Test in a small inconspicuous area to determine desired results. Sweep or vacuum surface. Protect baseboards, carpet, etc. with protective plastic and/or blue painters tape. Surface must be free of existing sealers or coatings. **Liberal apply KnockDown® to the stone surface. Add water to form a slurry.** Refinish using a weighted floor machine fitted with a natural hair or synthetic fiber tan floor pad or use a hand polishing machine. If lippage is present, use two pads, double stacked. Keep slurry wet while **buffing. Add KnockDown® as needed. Harder stones will require a thicker slurry.** Buff area until the desired level of hone has been achieved squeegee slurry from a small area to check for desired results prior to removing slurry. Rinse well and use a wet vacuum to remove all excess compound.

Cleaning of equipment

Clean tools with water before material dries.

Health Precautions

MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear skin and eye protection. Contains nonreactive mineral powders. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting, seek medical attention. **KEEP OUT OF REACH OF CHILDREN.**

6 Availability & Cost

Location	Item Code	Size	Package
USA	100287	2 lb (.9 kg)	Bottle



CUSTOM®

Aqua Mix® KnockDown®

7 Product Warranty

Custom® Building Products warrants to the original consumer purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom's® sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom's® printed instructions. Custom® makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country/territory to another. This warranty is not transferrable.

8 Product Maintenance

Properly applied product requires no special maintenance.

9 Technical Services Information

For technical assistance, contact Custom technical services at 800-282-8786 or visit custombuildingproducts.com.

10 Filing System

Additional product information is available from the manufacturer upon request.

VOC Content

No VOCs

Handling & Storage

- Close container tightly after each use
- Store in original container only
- Store in and use in temperatures between 45° F to 85° F (7° C to 29° C)
- Store in areas inaccessible to small children
- Do not reuse empty container, wrap and discard in trash or recycle

Related Products

Aqua Mix® Reviver®

Aqua Mix® Renue®



Aqua Mix® KnockDown®

Coverage

Coverage depends on the hardness of the stone and method of application.

SIZE	Min Coverage	Max Coverage
1 lb (.45 kg)	100 ft ² (10 M ²)	200 ft ² (19 M ²)



CUSTOM®