

WonderBoard® Backerboard

1 Product Name

WonderBoard® Backerboard

2 Manufacturer

Custom Building Products
13001 Seal Beach Blvd.
Seal Beach, CA 90740-2757
Customer Support: 800-272-8786
Technical Services: 800-282-8786
Fax: 800- 200-7765
Email: contactus@cbpmail.net
custombuildingproducts.com

3 Product Description

A fiberglass mesh reinforced cement backerboard for residential and commercial tile, stone, slate and thin brick applications. High-flexural strength, along with moisture resistance, makes WonderBoard® ideal for both interior and exterior substrate applications. Uses for WonderBoard® include walls and ceilings.

Composition of Product

WonderBoard® panels are composed of stable Portland cement, aggregates and reinforcement.

Benefits of Product in the Installation

- Patented open mesh edges allow tapeless installation and provides outstanding edge bond strength.
- Aligns to 1/2" (13 mm) drywall without use of shims or spacers on wall studs.
- WonderBoard® includes a pre-printed grid pattern on the panel surface and is easy to score, snap, cut and fasten, simplifying installation.
- Remains stable when exposed to moisture, reducing risk of moisture damage.

Limitations to the Product

- Do not use WonderBoard® for exterior surfaces where imposed wind loads exceed 30 lb/ft(146 kg/M).
- Do not use WonderBoard® as a structural load bearing member.
- WonderBoard® is not a waterproof barrier. If the area behind the backerboard must be kept dry, use RedGard® Waterproofing and Crack Prevention Membrane or Custom® 9240 Waterproofing and Anti-Fracture Membrane.
- Do not use drywall fiberglass tape for this product.
- Do not use wallboard joint compound for this product.

Packaging

- 36" 60" 1/2" (914 1524 13 mm) for floors, walls and countertops
- 36" x 60" x 1/4" (914 x 1524 x 6 mm) for floors and countertops

4 Technical Data

Applicable Standards

American National Standards Institute (ANSI) ANSI A108.11, A118.9, A108.5 and A118.4 American National Standards for the Installation of Ceramic Tile ASTM International (ASTM)

- ASTM C473 Standard Test Methods for Physical Testing of Gypsum Panel Products
- ASTM C947 Standard Test Method for Flexural Properties of Thin-Section Glass-Fiber-Reinforced Concrete (Using Simple Beam With Third-Point Loading)
- ASTM D1037 Standard Test Methods for Evaluating Properties of Wood-Base Fiber and Particle Panel Materials
- ASTM D2394 Standard Methods for Simulated Service Testing of Wood and Wood-Base Finish Flooring
- ASTM E84 Standard Test Method for Surface Burning Characteristics of Building Materials
- ASTM E330 Standard Test Method for Structural Performance of Exterior Windows, Doors, Skylights and Curtain Walls by Uniform Static Air Pressure Difference National Fire Protection Association (NFPA) NFPA 255 Standard Method of Test of Surface Burning Characteristics of Building Materials

Tile Council of North America (TCNA) TCNA Handbook for Ceramic Tile Installation, TCNA Method EJ171

Underwriters Laboratories, Inc. (UL) ANSI/UL 263 Fire Tests of Building Construction and Materials

Underwriters Laboratories of Canada (ULC) CAN/ULC S101 Standard Method of Fire Endurance Tests of Building Construction and Materials

Environmental Consideration

Custom® Building Products is committed to environmental responsibility in both products produced and in manufacturing practices. Use of this product can contribute to LEED® certification.



CUSTOM®

WonderBoard® Backerboard

5 Instructions

Application of Product

For wall framing, edges parallel to framing should be continuously supported (typical sleeper studs should be used). For ceiling framing, the complete ceiling assembly allowable deflection, due to dead load, should not exceed 1/360 of the span. Framing members in the ceiling should not exceed 16" (40 cm) o.c. The weight applied to the ceiling frame, including insulation, backerboard, bonding material and facing material, should not exceed 15 lb/ft (73 kg/M). Backerboard edges parallel to the framing should be continuously supported. Provide additional blocking, when necessary, to permit proper backerboard attachment and reduce deflection between the joists. Leaving a 1/8" - 3/16" (3 - 5 mm) space at all joints and corners, install the **WonderBoard®** panels. **Stagger board joints with those of adjacent rows.** Fasten the backerboard every 6" (15 cm) along the joist or rafter. It is recommended that blocking be installed between the joints to support the ends of the backerboard. On all joints and corners, pre-fill the gap with bonding material, and then embed 2" (5 cm) mesh tape and smooth the material over the joint and corner. A moisture barrier must be installed to protect the wall cavity for wet area installations. Nail or staple 15 lb roofing felt or 4 mil polyethylene sheeting to the studs. **Precut WonderBoard® panels and make any necessary cutouts. Install WonderBoard®, leaving a 1/8" - 3/16" (3 - 5 mm) space at all joints and corners. Stagger board joints with those of adjacent rows.** Fasten backerboards every 8" (20.3 cm) o.c. along studs. At all joints and corners, pre-fill gaps with polymer-modified mortar, then embed 2" (5 cm) alkali-resistant fiberglass mesh tape and smooth material over joint and corner. Any shelf, ledge or horizontal surface subjected to water exposure must have a slight downward slope for water runoff. These areas also require proper **waterproofing. Apply TVIS™ Veneer Waterproofing Membrane** according to directions. For installation of tile, natural stone or a similar material, comply with ANSI A108 standard specifications. Install according to installation instructions for the corresponding mortar technical data sheets.

Health Precautions

This product, when cut, drilled or abraded, produces dust containing free silica, which may cause cancer or delayed lung injury (silicosis) if inhaled. Work outdoors, in a well-ventilated area, or use mechanical ventilation. Wear safety glasses and a dust mask; in very dusty areas or where airborne dust exceeds PEL, wear a NIOSH/MSHA approved respirator. This product contains one or more chemicals known to the State of California to cause cancer.

Conformance to Building Codes

Installation must comply with the requirements of all applicable local, state and federal code jurisdictions.

6 Availability & Cost

Product Name	Item Code	Size
WonderBoard® Backerboard	GCB60	36" x 60" x 1/2" (91 cm x 153 cm x 13 mm)
	GCB60	36" x 96" x 1/2" (91 cm x 244 cm x 13 mm)
	GCB60	36" x 48" x 1/4" (91 cm x 122 cm x 6 mm)
	GCB60	36" x 60" x 1/4" (91 cm x 153 cm x 6 mm)

7 Product Warranty

This product is eligible for Custom® Building Products Lifetime Backerboard Warranty. Custom® Building Products warrants to the original consumer purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Customs® sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Customs® printed instructions. Custom® makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country/territory to another. For details and complete warranty information, contact Custom® Building Products or visit customTVIS.com.

8 Product Maintenance

Properly installed product requires no special maintenance.

9 Technical Services Information

For technical assistance, contact Custom® Building Products.

10 Filing System

Additional product information is available from the manufacturer upon request.



CUSTOM®