

Commercial 100% Silicone Caulk

1 Product Name

Commercial 100% Silicone Caulk

2 Manufacturer

Custom Building Products
13001 Seal Beach Blvd.
Seal Beach, CA 90740-2757
Customer Support: 800-272-8786
Technical Services: 800-282-8786
Fax: 800- 200-7765
Email: contactus@cbpmail.net
custombuildingproducts.com

3 Product Description

Designed for use in coves, corners, changes in plane and expansion joints associated with exterior and interior applications of tile and stone. Can be used in pools and other wet area applications. Conforms to ASTM C-920, Type S, Grade NS, Class 25, Use T, I, M and G and ASTM C-794 properties.

- Interior/Exterior use
- Use with stone, ceramic or porcelain tile
- Suitable for expansion joints, dry, wet and submerged areas
- Permanently flexible
- Conforms to TCNA Handbook EJ 171

Suitable Substrates

- Exterior and interior use
- Around tubs, showers and sinks
- Joints for ceramic tile and stone applications
- Expansion joints in residential and commercial applications including those in traffic areas

Limitations to the Product

- Joint depth should not exceed 1/2" (13 mm)
- Joint width should not exceed 1" (2.5 cm)
- Material will stain some stones. Test small area before installation

4 Technical Data

Applicable Standards

Meets the requirements of ASTM C-920 and TCNA EJ 171

5 Instructions

Application of Product

Sealant should be installed after TVIS™ Premium Veneer Pointing Mortar has cured. Joints and surfaces should be clean, dry and free of all contamination including old caulk or other sealants. Backup strips shall be flexible and compressible type of closed-cell foam polyethylene, butyl rubber, or urethane. Backup strip should fit tightly in the joint and to a depth that allows the caulk depth to be 1/2 the thickness of the tile. Cut tip off nozzle on a slant to desired opening size. Completely fill joints with caulk. Smooth or clean off excess caulk with mineral spirits or paint thinner before caulk cures. After cure, remove excess with a razor blade. Do not apply when temperatures fall below 40°F (4°C).

IMPORTANT: Commercial 100% Silicone Caulk is not a paintable surface. Painting should be done prior to installation.



Drying Time

Protect finished work from traffic and exposure to water until fully cured, generally 24 hours at 70° F (21° C). Caulk should cure a full 7 days before being exposed to continuous submersion in water.

Cleaning of equipment

Clean all tools with paint thinner or mineral spirits before material dries.

Storage

Replace cap after each use. Store away from extreme heat or cold. Keep from freezing.

Health Precautions

KEEP OUT OF REACH OF CHILDREN. Provide adequate ventilation during installation. DO NOT TAKE INTERNALLY. AVOID EYE CONTACT.

WARNING: This product contains one or more chemicals known to the State of California to cause cancer.

Conformance to Building Codes

Installation must comply with the requirements of all applicable local, state and federal code jurisdiction.



CUSTOM®

Commercial 100% Silicone Caulk

6 Availability & Cost

Product Name		Color	Item Code	Size	Package
Commercial 100% Silicone Caulk	#000	Clear	CCSC000	10.1 oz. (300 ml)	Cartridge
	#09	Natural Gray	CCSC09	10.1 oz. (300 ml)	Cartridge
	#10	Antique White	CCSC10	10.1 oz. (300 ml)	Cartridge
	#19	Pewter	CCSC19	10.1 oz. (300 ml)	Cartridge
	#35	Chaparral	CCSC35	10.1 oz. (300 ml)	Cartridge
	#45	Summer Wheat	CCSC45	10.1 oz. (300 ml)	Cartridge
	#52	Tobacco Brown	CCSC52	10.1 oz. (300 ml)	Cartridge
	#59	Saddle Brown	CCSC59	10.1 oz. (300 ml)	Cartridge
	#60	Charcoal	CCSC60	10.1 oz. (300 ml)	Cartridge
	#92	Admiral Blue	CCSC92	10.1 oz. (300 ml)	Cartridge
	#96	Quarry Red Clay	CCSC96	10.1 oz. (300 ml)	Cartridge
	#101	Quartz	CCSC101	10.1 oz. (300 ml)	Cartridge
	#105	Earth	CCSC105	10.1 oz. (300 ml)	Cartridge
	#122	Onyx	CCSC122	10.1 oz. (300 ml)	Cartridge
	#127	Antique	CCSC127	10.1 oz. (300 ml)	Cartridge

7 Product Warranty

Custom® Building Products warrants to the original purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom's® sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom's® printed instructions. Custom® makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country or territory to another. For details and complete warranty information, contact Custom® Building Products or visit CustomTVIS.com.

8 Product Maintenance

Properly installed product requires no special maintenance.

9 Technical Services Information

For technical assistance, contact Custom® Building Products.

10 Filing System

Additional product information is available from the manufacturer upon request.

Related Products

TVIS™ Premium Veneer Pointing Mortar

Related Articles

TB41



CUSTOM®

		Linen		oz. (300 ml)	
	#135	Mushroom	CCSC135	10.1 oz. (300 ml)	Cartridge
	#145	Light Smoke	CCSC145	10.1 oz. (300 ml)	Cartridge
	#156	Fawn	CCSC156	10.1 oz. (300 ml)	Cartridge
	#165	Delorean Gray	CCSC165	10.1 oz. (300 ml)	Cartridge
	#180	Sandstone	CCSC180	10.1 oz. (300 ml)	Cartridge
	#183	Chateau	CCSC183	10.1 oz. (300 ml)	Cartridge
	#185	New Taupe	CCSC185	10.1 oz. (300 ml)	Cartridge
	#312	Bonsai	CCSC312	10.1 oz. (300 ml)	Cartridge
	#333	Alabaster	CCSC333	10.1 oz. (300 ml)	Cartridge
	#380	Haystack	CCSC380	10.1 oz. (300 ml)	Cartridge
	#381	Bright White	CCSC381	10.1 oz. (300 ml)	Cartridge
	#382	Bone	CCSC382	10.1 oz. (300 ml)	Cartridge
	#386	Oyster Gray	CCSC386	10.1 oz. (300 ml)	Cartridge