



MATERIAL SAFETY DATA SHEET

Silicone Caulk

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Silicone Caulk
Product Use: Sealant.
Manufacturer/Supplier: Custom Building Products
13001 Seal Beach Blvd
Seal Beach, CA 90740
Phone Number: (562) 598-8808
Emergency Phone: INFOTRAC 1-800-535-5053 (US and Canada)
INTERNATIONAL + 1-352-323-3500
Date of Preparation: June 10, 2010 **Revision Date:** January 18, 2012

Section 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING

MAY CAUSE EYE IRRITATION. MAY CAUSE SKIN IRRITATION.

Potential Health Effects: See Section 11 for more information.

Likely Routes of Exposure: Skin contact, skin absorption, eye contact, inhalation, and ingestion.

Eye: May cause eye irritation.

Skin: May cause skin irritation. May cause sensitisation by skin contact.

Ingestion: May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

Inhalation: May cause respiratory tract irritation.

Chronic Effects: Prolonged or repeated contact may dry skin and cause irritation.

Signs and Symptoms: Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling. Symptoms may include redness, edema, drying, defatting and cracking of the skin. Vapours may cause drowsiness and dizziness.

Medical Conditions Aggravated By Exposure: Because of its irritating properties, product may aggravate preexisting skin, eye, and respiratory conditions.

Target Organs: Eyes, skin, respiratory system.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Potential Environmental Effects: May cause long-term adverse effects in the aquatic environment. See Section 12 for more information.

Section 3: COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	CAS #	Wt. %
Titanium dioxide	13463-67-7	1 - 5
Butan-2-one O,O',O''-(methylsilyldiyl)trioxime	22984-54-9	1 - 5
N-(3-(trimethoxysilyl)propyl)ethylenediamine	1760-24-3	1 - 5
Silica, amorphous, fumed	7631-86-9	5 - 10
Calcium carbonate	1317-65-3	15 - 40



MATERIAL SAFETY DATA SHEET

Silicone Caulk

Section 4: FIRST AID MEASURES

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.

Skin Contact: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

Ingestion: If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.

General Advice: In case of accident or if you feel unwell, seek medical advice immediately (show the label or MSDS where possible).

Note to Physicians: Symptoms may not appear immediately.

Section 5: FIRE FIGHTING MEASURES

Flammability: Not flammable by WHMIS/OSHA criteria.

Means of Extinction:

Suitable Extinguishing Media: Powder, water spray, foam, carbon dioxide.

Unsuitable Extinguishing Media: Not available.

Products of Combustion: May include, and are not limited to: oxides of carbon, silicon dioxide, formaldehyde, and traces of incompletely burned carbon compounds.

Explosion Data:

Sensitivity to Mechanical Impact: Not available.

Sensitivity to Static Discharge: Not available.

Protection of Firefighters: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

Section 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental Precautions: Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

Methods for Containment: Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for Clean-Up: Scoop up material and place in a disposal container.

Other Information: Not available.



MATERIAL SAFETY DATA SHEET

Silicone Caulk

Section 7: HANDLING AND STORAGE

Handling:

Avoid contact with skin and eyes. Do not swallow. Do not breathe gas/fumes/vapor/spray. Use only in well-ventilated areas. Handle and open container with care. Wear appropriate NIOSH approved filtering facepiece when permissible exposure limits may be exceeded. When using do not eat or drink. Wash hands before eating, drinking, or smoking.

Storage:

Keep out of the reach of children. Keep container tightly closed and in a well-ventilated place. Do not store at temperatures above 49 °C / 120 °F.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Ingredient	Exposure Limits	
	OSHA-PEL	ACGIH-TLV
Titanium dioxide	15 mg/m ³ (total dust)	10 mg/m ³
Butan-2-one O,O',O''-(methylsilyldiyl)trioxime	Not available.	Not available.
N-(3-(trimethoxysilyl)propyl)ethylenediamine	Not available.	Not available.
Silica, amorphous, fumed	80 mg/m ³ /%SiO ₂	10 mg/m ³
Calcium carbonate	15 mg/m ³ (total); 5 mg/m ³ (resp)	10 mg/m ³

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

Personal Protective Equipment:

Eye/Face Protection: Wear eye/face protection.

Hand Protection: Wear suitable gloves.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory equipment.

General Hygiene Considerations: Handle according to established industrial hygiene and safety practices.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Viscous paste.
Color:	Clear/White.
Odour:	Somewhat pungent.
Odour Threshold:	Not available.
Physical State:	Paste-like compound.
pH:	Not available.
Viscosity:	Not available.
Freezing Point:	Not available.
Boiling Point:	Not available.
Flash Point:	Not available.
Evaporation Rate:	Not available.



MATERIAL SAFETY DATA SHEET

Silicone Caulk

Lower Flammability Limit:	Not available.
Upper Flammability Limit:	Not available.
Vapor Pressure:	0.1 kPa @ 25°C (77°F)
Vapor Density:	Not available.
Specific Gravity:	1.30 g/cm ³ @ 25°C (77°F)
Solubility in Water:	Insoluble.
Coefficient of Water/Oil Distribution:	Not available.
Auto-ignition Temperature:	Not available.
Percent Volatile, wt. %:	Not available.
VOC content, wt. %:	Not available.

Section 10: STABILITY AND REACTIVITY

Stability: Stable under normal storage conditions.

Conditions of Reactivity: Extreme heat. Incompatible materials.

Incompatible Materials: Moisture/Water. Oxidizers.

Hazardous Decomposition Products: May include, and are not limited to: oxides of carbon, silicon dioxide, formaldehyde, and traces of incompletely burned carbon compounds.

Possibility of Hazardous Reactions: No dangerous reaction known under conditions of normal use. Product evolves methyl ethyl ketoxime (MEKO) when exposed to water or humid air.

Section 11: TOXICOLOGY INFORMATION

EFFECTS OF ACUTE EXPOSURE

Component Analysis

Ingredient	LD ₅₀ (oral)	LC ₅₀
Titanium dioxide	>10000 mg/kg, rat	Not available.
Butan-2-one O,O',O''-(methylsilyldiyl)trioxime	Not available.	Not available.
N-(3-(trimethoxysilyl)propyl)ethylenediamine	7460 µL/kg, rat	Not available.
Silica, amorphous, fumed	5000 mg/kg, rat	> 200000 mg/m ³ 1hr, rat
Calcium carbonate	6450 mg/kg, rat	Not available.

Eye: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

Skin: May cause skin irritation. May cause sensitisation by skin contact. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Ingestion: May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

Inhalation: May cause respiratory tract irritation. Vapours may cause drowsiness and dizziness.

EFFECTS OF CHRONIC EXPOSURE

Target Organs: Not available.

Chronic Effects: Hazardous by WHMIS/OSHA criteria.

Carcinogenicity: Hazardous by WHMIS/OSHA criteria.



MATERIAL SAFETY DATA SHEET

Silicone Caulk

Ingredient

Titanium dioxide
Butan-2-one O,O',O''-(methylsilylidyne)trioxime
N-(3-(trimethoxysilyl)propyl)ethylenediamine
Silica, amorphous, fumed
Calcium carbonate

Chemical Listed as Carcinogen or Potential Carcinogen *

G-A4, I-2B, CP65
Not listed.
Not listed.
I-3
Not listed.

* See Section 15 for more information.

Mutagenicity: Not hazardous by WHMIS/OSHA criteria.

Reproductive Effects: Not hazardous by WHMIS/OSHA criteria.

Developmental Effects:

Teratogenicity: Not hazardous by WHMIS/OSHA criteria.

Embryotoxicity: Not hazardous by WHMIS/OSHA criteria.

Respiratory Sensitization: Not hazardous by WHMIS/OSHA criteria.

Skin Sensitization: Not hazardous by WHMIS/OSHA criteria.

Toxicologically Synergistic Materials: Not available.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: May cause long-term adverse effects in the aquatic environment.

Persistence / Degradability: Not available.

Bioaccumulation / Accumulation: Not available.

Mobility in Environment: Not available.

Section 13: DISPOSAL CONSIDERATIONS

Disposal Instructions:

This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

Section 14: TRANSPORTATION INFORMATION

DOT Ground Classification

Not regulated

TDG Ground Classification

Not regulated

IATA Classification

Not regulated

IMDG Classification

Not regulated

Section 15: REGULATORY INFORMATION

Federal Regulations

Canadian: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

US: MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200).



MATERIAL SAFETY DATA SHEET

Silicone Caulk

SARA Title III

Ingredient	Section 302 (EHS) TPQ (lbs.)	Section 304 EHS RQ (lbs.)	CERCLA RQ (lbs.)	Section 313
Titanium dioxide	Not listed.	Not listed.	Not listed.	Not listed.
Butan-2-one O,O',O''-(methylsilyldiyl)trioxime	Not listed.	Not listed.	Not listed.	Not listed.
N-(3-(trimethoxysilyl)propyl)ethylenediamine	Not listed.	Not listed.	Not listed.	Not listed.
Silica, amorphous, fumed	Not listed.	Not listed.	Not listed.	Not listed.
Calcium carbonate	Not listed.	Not listed.	Not listed.	Not listed.

State Regulations

New Jersey Right-To-Know: Calcium carbonate, Amorphous silica, Titanium dioxide.

Pennsylvania Right-To-Know: Limestone, Silica, amorphous, Titanium oxide.

Massachusetts Right-To-Know: Calcium carbonate, Amorphous silica, Titanium dioxide.

California Proposition 65:

This product contains a chemical known to the state of California to cause cancer.

Global Inventories

Ingredient	Canada DSL/NDSL	USA TSCA
Titanium dioxide	DSL	Yes.
Butan-2-one O,O',O''-(methylsilyldiyl)trioxime	DSL	Yes.
N-(3-(trimethoxysilyl)propyl)ethylenediamine	DSL	Yes.
Silica, amorphous, fumed	DSL	Yes.
Calcium carbonate	NDSL	Yes.

HMIS - Hazardous Materials Identification System

Health - 2* Flammability - 1 Physical Hazard - 0 PPE - B

NFPA - National Fire Protection Association:

Health - 2 Fire - 1 Reactivity - 0

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

WHMIS Classification(s):

- Class D2A - Carcinogenicity
- Class D2A - Chronic Toxic Effects
- Class D2B - Skin Sensitization
- Class D2B - Skin/Eye Irritant

WHMIS Hazard Symbols:



SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

- OSHA (O)** Occupational Safety and Health Administration.
- ACGIH (G)** American Conference of Governmental Industrial Hygienists.
 - A1 - Confirmed human carcinogen.
 - A2 - Suspected human carcinogen.
 - A3 - Animal carcinogen.
 - A4 - Not classifiable as a human carcinogen.
 - A5 - Not suspected as a human carcinogen.



MATERIAL SAFETY DATA SHEET

Silicone Caulk

- IARC (I)** International Agency for Research on Cancer.
1 - The agent (mixture) is carcinogenic to humans.
2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.
2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.
3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.
4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.
- NTP (N)** National Toxicology Program.
1 - Known to be carcinogens.
2 - Reasonably anticipated to be carcinogens.

Section 16: OTHER INFORMATION

Disclaimer:

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Expiry Date: June 10, 2013

Version #: 2.2

Prepared by: Nexreg Compliance Inc.
Phone: (519) 488-5126
www.nexreg.com