

StoneSpecific® Tumbled/Honed Marble, Travertine Limestone & Slate Sealer

1 Product Name

StoneSpecific® Tumbled/Honed Marble, Travertine Limestone & Slate Sealer

2 Manufacturer

Custom Building Products
 Technical Services
 10400 Pioneer Boulevard, Unit 3
 Santa Fe Springs, CA 90670
 Customer Support: 800-272-8786
 Technical Services: 800-282-8786
 Fax: 800- 200-7765
 Email: contactus@cbpmail.net
custombuildingproducts.com

3 Product Description

Available in Canada only.

A specially-formulated stone sealer designed to penetrate and protect the surface of a unpolished, low to medium-density porous, and roughly textured natural stone. These types of stone are highly susceptible to staining and Tumbled/Honed Marble, Travertine, Limestone & Slate Sealer is designed to provide optimum protection against grease, dirt, oil and water-based stains allowing for easy clean-up. A premium water-based formula that is non-combustible. Low odor, pH neutral it can be used indoors or out, in commercial or residential applications. Allows moisture vapor transmission. Protects sanded or non-sanded grouts.

StoneSpecific® Low VOC (Volatile Organic Compound) formulas help provide better indoor and outdoor air quality compared to similar traditional products. Complies with EPA and CARB VOC Requirements.

Suitable Tile Types

Provides optimum protection for all types of tumbled or honed stone such as marble, travertine, limestone and slate. Specifically formulated to protect unpolished, low to medium-density porous and roughly textured natural stone.

Benefits of Product in the Installation

When optimum protection is required for tumbled and honed natural stone.

Packaging

1 quart (946 ml) bottle

4 Technical Data

Technical Properties Chart

- Excellent stain resistance to most household contaminants (CTI-072)
- No darkening of stone

5 Instructions

General Surface Prep

Surface should be dry, clean and free of waxes, sealers or finishes. TileLab® Heavy-Duty Cleaner & Stripper will clean the surface or strip wax and acrylic finishes. New Installations: Allow grout to cure 48 hours before applying sealer.

Application of Product

USE CHEMICAL-RESISTANT GLOVES, such as nitrile, when handling product.

Published Date: 3/30/2018



Test product in obscure area to ensure desirable results. Apply liberally using a new mop, lambswool applicator or sponge. Maintain a thin, even coat to cover surface, working-in sealer for 5 – 10 minutes. Surface must stay wet letting sealer soak for additional 10 minutes, for maximum penetration. Immediately after, wipe off any sealer completely before it dries. If initial coat has been absorbed, apply additional coat 15 minutes after first application. To prevent grout from staining porous stone, apply two coats after stone has been bonded for 24 hours or apply to face of stone before installation.

Pre-Grout Sealer/Grout Release

Porous tile, such as clay and Saltillo pavers, can be stained by grout during installation. Sealing the tile before grouting will make grout removal much easier. Apply two coats of sealer according to directions after tile has been bonded for a minimum of 24 hours, or apply to front face of tile before installation.

Drying Time

Drying time 2 – 3 hours. Do not clean for 24 hours.

Cleaning of equipment

Clean tools and hands with soap and water immediately after use.

Health Precautions

MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear skin and eye protection. Contains Diethylene glycol monobutylether and fluorophosphate esters. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting. Seek medical attention. KEEP OUT OF REACH OF CHILDREN.

6 Availability & Cost

Item Code	Size	Location	Package
SSTHMSQT-3	1 quart (946 ml)	USA	Bottle
CSSTHMSQT-3	1 quart (946 ml)	Canada	Bottle

7 Product Warranty

Obtain the applicable **LIMITED PRODUCT WARRANTY** at www.custombuildingproducts.com/product-warranty or send a written request to Custom Building Products, Inc., Five Concourse Parkway, Atlanta, GA 30328, USA. Manufactured under the authority of Custom Building Products, Inc. © 2017 Quikrete International, Inc.



StoneSpecific® Tumbled/Honed Marble, Travertine Limestone & Slate Sealer

8 Product Maintenance

Do not use cleaners containing ammonia, acids or bleach. Use an appropriate TileLab® or Aqua Mix® neutral cleaner. Tile industry experts recommend periodic testing of sealed surfaces. Apply a few drops of water on the surface. If it soaks in, a coat of TileLab® or Aqua Mix® sealer will be necessary to keep sealer at peak performance.

9 Technical Services Information

For technical assistance, contact Custom® Building Products.

10 Filing System

Additional product information is available from the manufacturer upon request.

Expected Wear

Lasts up to 20 years under normal conditions depending on hardness and texture of surface. Use factors, cleaning routines, harsh cleaning methods, sun exposure and weather conditions will affect wear.

Related Products

StoneSpecific® Marble, Travertine Limestone & Slate Cleaner/Resealer



CUSTOM®

StoneSpecific® Tumbled/Honed Marble, Travertine Limestone & Slate Sealer

Coverage

Size	Min Coverage	Max Coverage
Quart (946ml)	200 sq. ft. (18.6 M ²)	300 sq. ft. (27.9 M ²)



CUSTOM®