

# StoneSpecific® Stone Enhancer & Sealer

## 1 Product Name

StoneSpecific® Stone Enhancer & Sealer

## 2 Manufacturer

Custom Building Products  
 Technical Services  
 10400 Pioneer Boulevard, Unit 3  
 Santa Fe Springs, CA 90670  
 Customer Support: 800-272-8786  
 Technical Services: 800-282-8786  
 Fax: 800- 200-7765  
 Email: [contactus@cbpmail.net](mailto:contactus@cbpmail.net)  
[custombuildingproducts.com](http://custombuildingproducts.com)

## 3 Product Description

### Available in Canada only.

Color enhancer and penetrating sealer for all types of porous natural stone and grout. Rejuvenates the color and appearance of worn, faded stone, tumbled marble and other rustic-look stones. Can also be used to darken the color of grout. Provides long-lasting protection against oil, grease and stains. Its water-based, low odor formula can be used indoors or outdoors.

StoneSpecific® Low VOC (Volatile Organic Compound) formulas help provide better indoor and outdoor air quality compared to similar traditional products. Complies with EPA and CARB VOC Requirements.

For interior and exterior use.

### Suitable Tile Types

As a sealer and color enhancer for all stone surfaces, clay pavers and grout. Excellent for tumbled marble and other rustic look stones. This product may not be totally effective as a color enhancer on some polished stones.

## 4 Technical Data

### Technical Properties Chart

- Excellent stain resistance to most household contaminants (CTI-072)
- Darkens most stone to a "wet look"

## 5 Instructions

### General Surface Prep

Surface should be dry, clean and free of waxes, sealers or finishes. TileLab® Heavy-Duty Cleaner & Stripper will clean the surface or strip wax and acrylic finishes. New installations need to be cured 48 hours before application.

### Application of Product

**USE CHEMICAL-RESISTANT GLOVES, such as nitrile, when handling product.**



Once the enhancer has been applied to the surface of stone, grout or tile it cannot be reversed. Always test product in hidden area to ensure desired results. Apply liberally using a new mop, lambswool applicator or sponge. Allow to penetrate for up to 5 minutes. Immediately wipe off any sealer completely before it dries. Immediately apply a second coat. Ensure no residue is left to dry on the surface. Do not use outside if inclement weather is expected within 24 hours. Clean off any residue **left on the surface with an appropriate StoneSpecific® or TileLab® cleaner.** Note: The more porous the stone the deeper the color enhancement.

### Drying Time

4 - 6 hours. Do not clean for 24 hours.

### Cleaning of equipment

Clean tools and hands with soap and water immediately after use.

### Storage

- Close container tightly after each use
- Store in original container only
- Store and use between temperatures of 45°F - 85°F (7°C - 29°C)
- Dispose of residue or any unused leftover product in accordance with applicable federal, state, and local requirements

### Health Precautions

MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear skin and eye protection. Contains Ethylene Glycol, Dibutyl phthalate, Dipropylene glycol methyl ether and acrylic polymer. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting. Seek medical attention. KEEP OUT OF REACH OF CHILDREN.

## 6 Availability & Cost

Item Code	Size	Location	Package
SSSESQT-3	1 quart (946 ml)	USA	Bottle
CSSESQT-3	1 quart (946 ml)	Canada	Bottle



# CUSTOM®

# StoneSpecific® Stone Enhancer & Sealer

---

## 7 Product Warranty

Obtain the applicable **LIMITED PRODUCT WARRANTY** at [www.custombuildingproducts.com/product-warranty](http://www.custombuildingproducts.com/product-warranty) or send a written request to Custom Building Products, Inc., Five Concourse Parkway, Atlanta, GA 30328, USA. Manufactured under the authority of Custom Building Products, Inc. © 2017 Quikrete International, Inc.

## 8 Product Maintenance

Use an appropriate TileLab® or Aqua Mix® neutral cleaner for routine cleaning.

## 9 Technical Services Information

For technical assistance, contact Custom® Building Products.

## 10 Filing System

Additional product information is available from the manufacturer upon request.

---

### VOC Content

No VOCs



# StoneSpecific® Stone Enhancer & Sealer

---

## Coverage

Size	Min Coverage	Max Coverage
Porous Surfaces: Quart (946 ml)	45 sq. ft. (4,2 M <sup>2</sup> )	85 sq. ft. (8.3 M <sup>2</sup> )
Polished or Dense Surfaces: Quart (946 ml)	170 sq. ft. (16.6 M <sup>2</sup> )	255 sq. ft. (25 M <sup>2</sup> )