

Aqua Mix® Ex-Treme®

1 Product Name

Aqua Mix® Ex-Treme®

2 Manufacturer

Custom Building Products
 Technical Services
 10400 Pioneer Boulevard, Unit 3
 Santa Fe Springs, CA 90670
 Customer Support: 800-272-8786
 Technical Services: 800-282-8786
 Fax: 800- 200-7765
 Email: contactus@cbpmail.net
custombuildingproducts.com

3 Product Description

A nonflammable, heavy-viscosity acidic cleaner designed to remove years of accumulated discoloration from air pollution or carbon buildup, stains from smoke, soot, red soil and rust. It is a safer alternative to traditional harsh acids.

Key Features

- Removes mineral deposits, rust stains and red dirt stains
- Safer alternative to traditional harsh acids
- Removes hydrocarbon, smoke and soot stains

Uses

Unpolished natural stone, concrete pavers, masonry surfaces, ceramic, porcelain, grout, quarry, saltillo, terra-cotta, and other acid resistant tile and stone.

Limitations to the Product

- Do not use on polished, acid-sensitive stone (such as marble and limestone)
- Do not allow product to come in contact with any non-recommended surface
- Do not mix with ammoniated cleaners, such as bleach, as harmful fumes will result
- Acids of all kinds may etch, lighten, or change the color of cementitious material, metallic glazes and some natural stones such as marble and limestone

4 Technical Data

Technical Properties Chart

- pH 2-3
- Complies with all Federal EPA and SCAQMD standards for VOC

Environmental Consideration

Environmental Consideration

Custom® Building Products is committed to environmental responsibility in both products produced and in manufacturing practices. Use of this product may contribute towards LEED® certification:

- Up to 2 points towards MR Credit 5, Regional Materials
- Complies with all Federal, SCAQMD, and CARB standards for VOC's



5 Instructions

General Surface Prep

Test a small area according to application instructions to determine desired results.

Application of Product

USE CHEMICAL-RESISTANT GLOVES, such as nitrile, when handling product.

Read entire label before using. Remove loose debris. Pre-wet the surface with water and remove excess before applying solution. Mix Ex-Treme® as follows:

LIGHT BUILDUP: Mix 1 part cleaner to 4 parts water.

MODERATE BUILDUP: Mix 1 part cleaner to 2 parts water.

HEAVY BUILDUP: Use undiluted.

Liberal apply solution with paint roller, brush or sponge. Allow to dwell up to 30 minutes. DO NOT ALLOW SOLUTION TO DRY ON SURFACE. Apply additional solution if drying occurs. Agitate with scrub brush thoroughly rinse with clean water. For vertical surfaces a garden hose or high-pressure washer may be used to rinse area. Mop or wet vacuum dirty solution. Heavy buildup may require additional applications and a longer dwell time.

Cleaning of equipment

Clean tools with water before material dries.

Storage

Protect from freezing. Store in a cool, dry area.

Health Precautions

MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear skin and eye protection. Contains glycol ether PNB, oxalic acid, and glycolic acid. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting, seek medical attention. KEEP OUT OF REACH OF CHILDREN.



CUSTOM®

Aqua Mix® Ex-Treme®

6 Availability & Cost

Location	Item Code	Size	Package
USA	100991*	1 gal (3.8 L)	Bottle
Canada	C100991*	1 gal (3.8 L)	Bottle

* Indicates a special order item

7 Product Warranty

Obtain the applicable **LIMITED PRODUCT WARRANTY** at www.custombuildingproducts.com/product-warranty or send a written request to Custom Building Products, Inc., Five Concourse Parkway, Atlanta, GA 30328, USA. Manufactured under the authority of Custom Building Products, Inc. © 2017 Quikrete International, Inc.

8 Product Maintenance

Properly applied product requires no special maintenance.

9 Technical Services Information

For technical assistance, contact Custom technical services at 800-282-8786 or visit custombuildingproducts.com.

10 Filing System

Additional product information is available from the manufacturer upon request.

VOC Content

No VOCs

Handling & Storage

- Close container tightly after each use
- Store in original container only
- Store in and use in temperatures between 45° F to 85° F (7.2° C to 29.4° C)
- Store in areas inaccessible to small children
- Do not reuse empty container, wrap and discard in trash or recycle

Related Products

Aqua Mix® Sealer's Choice® Gold



Aqua Mix® Ex-Treme®

Coverage

SIZE	Min Coverage	Max Coverage	
1 Gal (3.78 L)	200 sq. ft. (19 M ²)	1,000 sq. ft. (93 M ²)	Depending on dilution.