

# Ceramic Tile Caulk

## 1 Product Name

Ceramic Tile Caulk

## 2 Manufacturer

Custom Building Products  
 Technical Services  
 10400 Pioneer Boulevard, Unit 3  
 Santa Fe Springs, CA 90670  
 Customer Support: 800-272-8786  
 Technical Services: 800-282-8786  
 Fax: 800- 200-7765  
 Email: [contactus@cbpmail.net](mailto:contactus@cbpmail.net)  
[custombuildingproducts.com](http://custombuildingproducts.com)

## 3 Product Description

Our ceramic tile caulk is for caulking around sinks, tubs, showers and where tile meets tile or another surface. Also adheres bath fixtures and loose tile. Do not use to install grab bars. Maximum joint width and depth should not exceed 1/4" (6 mm). Do not use in areas with constant water exposure. For interior use only.

### Key Features

- Use around tubs and sinks
- Use where horizontal and vertical surfaces meet
- Siliconized for ease of use

### Suitable Tile Types

- Around tubs, showers and sinks
- Bonds bath fixtures and loose tiles

### Composition of Product

Siliconized acrylic latex resins with fine fillers and colored pigments

### Benefits of Product in the Installation

- For caulking around sinks, tubs and showers
- Adheres bath fixtures and loose tile.
- For joint up to 1/4" (6mm) wide and deep
- For interior use.
- Available in sanded and non-sanded versions to match grout texture.
- Mold and mildew resistant

### Limitations to the Product

- Do not use to install grab bars.
- Maximum joint width and depth should not exceed 1/4" (6 mm).
- Do not use in areas with constant water exposure

### Packaging

10.5 oz (310 ml) cartridge



## 4 Technical Data

### Technical Chart

Tack-Free Time (ASTM C-679)	30 Minutes
Paintable	>Yes
Slump	< 0.15 mm
Shrinkage	< 30%
Stain Resistance	Excellent
Crack Resistance	Excellent
pH	7-9

### Environmental Consideration

Custom® Building Products is committed to environmental responsibility in both products produced and in manufacturing practices. Use of this product may contribute towards LEED® certification:

- Up to 2 points towards MR Credit 5, Regional Materials
- Complies with all Federal, SCAQMD, and CARB standards for VOC's

## 5 Instructions

### General Surface Prep

**Always wear proper protective equipment when handling the product, including IMPERVIOUS GLOVES, such as nitrile, safety glasses, and a NIOSH N95 respirator (mask).**

### Application of Product

Surfaces should be clean, dry and free of all contamination. Place cartridge in standard caulking gun. Cut tip off nozzle on a slant to desired opening size and completely fill joints with caulk. Smooth with wet finger. Clean off excess caulk with soap and water before it cures. Do not apply when temperature falls below 50°F (10°C).

### Curing of Product

Minimum 24 hours before exposing to water. Cure time may be extended, depending on caulking thickness and ambient conditions.

### Cleaning of equipment

Clean tools with water before material dries.



# CUSTOM®

# Ceramic Tile Caulk


---

## Storage

Protect from freezing. Store in a cool, dry area.

## Health Precautions

**WARNING: MAY IRRITATE SKIN AND EYES. DUST FROM SANDING MAY CAUSE IRRITATION TO RESPIRATORY TRACT. PROLONGED OR REPEATED INHALATION OF DUST MAY CAUSE LUNG DAMAGE OR CANCER.** A NIOSH N95 respirator (mask) is recommended if sanding the product. May be harmful if swallowed. Do not mix with other chemical products. Avoid contact with eyes and prolonged contact with skin. Do not breathe in vapors. Do not take internally. Immediately wash contaminated body and clothing thoroughly. Use in well-ventilated areas. If in eyes: rinse cautiously with water for several minutes; remove contact lenses if easy to do; continue rinsing. If inhaled: remove person to fresh air and keep comfortable for breathing. If swallowed: rinse mouth; do NOT induce vomiting. Immediately seek medical attention if any symptoms are significant or persist. In Emergency: 1-800-535-5053. **Contains: Silica sand, styrene-acrylic polymer, titanium dioxide, and ethylene glycol.** Before handling read Safety Data Sheet at [www.custombuildingproducts.com](http://www.custombuildingproducts.com). KEEP OUT OF REACH OF CHILDREN.

 **WARNING:** This product can expose you to chemicals including crystalline silica, which is known to the State of California to cause cancer, and ethylene glycol, which are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

# Ceramic Tile Caulk

## 6 Availability & Cost

Sanded					
Location	Color #	Color	Item Code	Size	Package
USA	#9	Natural Gray	PC0910S-6	10.5 oz. (310 ml)	Cartridge
USA	#11	Snow White	PC1110S-6	10.5 oz. (310 ml)	Cartridge
USA	#19	Pewter	PC1910S-6	10.5 oz. (310 ml)	Cartridge
USA	#60	Charcoal	PC6010S-6	10.5 oz. (310 ml)	Cartridge
USA	#115	Platinum	PC11510S-6	10.5 oz. (310 ml)	Cartridge
USA	#122	Linen	PC12210S-6	10.5 oz. (310 ml)	Cartridge
USA	#165	Delorean Gray	PC16510S-6	10.5 oz. (310 ml)	Cartridge
USA	#380	Haystack	PC38010S-6	10.5 oz. (310 ml)	Cartridge
USA	#381	Bright White	PC38110S-6	10.5 oz. (310 ml)	Cartridge
USA	#382	Bone	PC38210S-6	10.5 oz. (310 ml)	Cartridge
USA	#386	Oyster Gray	PC38610S-6	10.5 oz. (310 ml)	Cartridge
USA	#544	Rolling Fog	PC54410S-6	10.5 oz. (310 ml)	Cartridge
USA	#640	Arctic White	PC64010S-6	10.5 oz. (310 ml)	Cartridge
USA	#646	Coffee Bean	PC64610S-6	10.5 oz. (310 ml)	Cartridge
USA	#647	Brown Velvet	PC64710S-6	10.5 oz. (310 ml)	Cartridge
Canada	#9	Natural Gray	CPC0910S-6	10.5 oz. (310 ml)	Cartridge
Canada	#10	Antique White	CPC1010S-6	10.5 oz. (310 ml)	Cartridge
Canada	#11	Snow White	CPC1110S-6	10.5 oz. (310 ml)	Cartridge
Canada	#19	Pewter	CPC1910S-6	10.5 oz. (310 ml)	Cartridge
Canada	#52	Tobacco Brown	CPC5210S-6	10.5 oz. (310 ml)	Cartridge
Canada	#60	Charcoal	CPC6010S-6	10.5 oz. (310 ml)	Cartridge
Canada	#105	Earth	CPC10510S-6	10.5 oz. (310 ml)	Cartridge
Canada	#122	Linen	CPC12210S-6	10.5 oz. (310 ml)	Cartridge
Canada	#145	Light Smoke	CPC14510S-6	10.5 oz. (310 ml)	Cartridge
Canada	#165	Delorean Gray	CPC16510S-6	10.5 oz. (310 ml)	Cartridge
Canada	#380	Haystack	CPC38010S-6	10.5 oz. (310 ml)	Cartridge
Canada	#381	Bright White	CPC38110S-6	10.5 oz. (310 ml)	Cartridge
Canada	#382	Bone	CPC38210S-6	10.5 oz. (310 ml)	Cartridge

Non-Sanded					
Location	Color #	Color	Item Code	Size	Package
USA	#10	Antique White	PC1010N-6	10.5 oz. (310 ml)	Cartridge
USA	#11	Snow White	PC1110N-6	10.5 oz. (310 ml)	Cartridge
USA	#122	Linen	PC12210N-6	10.5 oz. (310 ml)	Cartridge
USA	#165	Delorean Gray	PC16510N-6	10.5 oz. (310 ml)	Cartridge
USA	#381	Bright White	PC38110N-6	10.5 oz. (310 ml)	Cartridge
Canada	#10	Antique White	CPC1010N-6	10.5 oz. (310 ml)	Cartridge
Canada	#11	Snow White	CPC1110N-6	10.5 oz. (310 ml)	Cartridge
Canada	#122	Linen	CPC12210N-6	10.5 oz. (310 ml)	Cartridge
Canada	#165	Delorean Gray	CPC16510N-6	10.5 oz. (310 ml)	Cartridge
Canada	#381	Bright White	CPC38110N-6	10.5 oz. (310 ml)	Cartridge

Additional colors may be available in select markets.

See our color card for truest color representation when selecting or specifying a grout color. Final installed show may vary with tile color and porosity as well as jobsite conditions and finishing techniques. For best results, perform a test of grout, conspicuously, or leave a sample of grout prior to installation.



# CUSTOM

# Ceramic Tile Caulk

---

## 7 Product Warranty

Obtain the applicable **LIMITED PRODUCT WARRANTY** at [www.custombuildingproducts.com/product-warranty](http://www.custombuildingproducts.com/product-warranty) or send a written request to Custom Building Products, Inc., Five Concourse Parkway, Atlanta, GA 30328, USA. Manufactured under the authority of Custom Building Products, Inc. © 2017 Quikrete International, Inc.

## 8 Product Maintenance

Clean with a neutral cleaner such as Aquamix AquaKleen or Tilelab Grout & Tile Cleaner

## 9 Technical Services Information

For technical assistance, contact Custom technical services at 800-282-8786 or visit [custombuildingproducts.com](http://custombuildingproducts.com).

## 10 Filing System

Additional product information is available from the manufacturer upon request.

---

### VOC Content

Sanded: Less than 45 g/L (<0.30% CARB VOC)

Non-Sanded: Less than 50 g/L (<0.40% CARB VOC)

### Related Products

Polyblend® Sanded Grout

Prism® Ultimate Performance Grout

# Ceramic Tile Caulk

---

**Coverage**

Size	Coverage
10.1 oz. (300 mL)	24 lineal feet (7.3 M) of 1/4" x 1/4" (6 x 6 mm) joint

