

Aqua Mix® Sealer Application Kit

1 Product Name

Aqua Mix® Sealer Application Kit

2 Manufacturer

Custom Building Products
 Technical Services
 10400 Pioneer Boulevard, Unit 3
 Santa Fe Springs, CA 90670
 Customer Support: 800-272-8786
 Technical Services: 800-282-8786
 Fax: 800- 200-7765
 Email: contactus@cbpmail.net
custombuildingproducts.com

3 Product Description

Specially designed for stone and tile sealer application and cleanup. The kit contains one 4" x 4" sponge application pad for easy sealer application with less waste and two 18" x 18" microfiber towels for quick cleanup after sealing. Application pad distributes sealer evenly and efficiently for better, more even application. Microfiber towels lift, trap, and absorb better than other fibers and trap residue, dirt and particles that other towels may leave behind. Will not scratch stone surfaces and is reusable, absorbent and long-lasting.

Key Features

Designed for stone and tile sealer application and cleanup

Suitable Tile Types

- All natural stone and tile surfaces
- Also excellent for everyday cleaning and polishing with Aqua Mix® cleaning products

4 Instructions

General Surface Prep

Surface should be dry, clean and free of waxes, sealers or finishes. **TileLab® Heavy-Duty Stripper & Cleaner** or **Aqua Mix® Heavy-Duty Tile & Grout Cleaner** will clean the surface or strip wax and acrylic finishes. **New installations need to be cured 48 – 72 hours before application.** Protect painted surfaces. Test product in obscure area to ensure desirable results. Sealer can be applied 48 hours after grout has been installed.

Exterior applications must meet moisture conditions - [read CUSTOM Technical Bulletin 49](#) for details.

Application of Product

Follow surface preparation and usage instructions of sealer to be used. Apply sealer to applicator pad and spread evenly over application area. Per sealer instructions, clean up any leftover sealer residue with microfiber towels. Wash applicator pad and towels per washing instructions.

Pre-Grout Sealer/Grout Release

Porous tile, such as clay and Saltillo pavers, can be stained by grout during installation. Sealing the tile before grouting will make grout removal much easier. Apply two coats of sealer according to directions after tile has been bonded for a minimum of 24 hours, or apply to front face of tile before installation.



Drying Time

- Allow 30 minutes drying time between coats.
- Ready for surface traffic in 2 hours.
- Keep dry for 12 hours.
- Achieves a full cure in 24 hours.

5 Availability & Cost

Location	Item Code	Size	Package
USA	200812-4	1 Application Kit	Bag

6 Product Warranty

Obtain the applicable **LIMITED PRODUCT WARRANTY** at www.custombuildingproducts.com/product-warranty or send a written request to Custom Building Products, Inc., Five Concourse Parkway, Atlanta, GA 30328, USA. Manufactured under the authority of Custom Building Products, Inc. © 2017 Quikrete International, Inc.

7 Product Maintenance

Do not use cleaners containing ammonia, acids or bleach. Use an appropriate **TileLab®** or **Aqua Mix® neutral cleaner**. Tile industry experts recommend periodic testing of sealed surfaces. Apply a few drops of water on the surface. If it soaks in, an additional application of sealer will be necessary to keep sealer at peak performance.

8 Technical Services Information

For technical assistance, contact Custom technical services at 800-282-8786 or visit custombuildingproducts.com.

9 Filing System

Additional product information is available from the manufacturer upon request.

10 Handling & Storage

Wash and allow to dry per instructions and store in resealable pouch provided.

