

Aqua Mix® 1 & 2 Deep Clean

1 Product Name

Aqua Mix® 1 & 2 Deep Clean

2 Manufacturer

Custom Building Products
 Technical Services
 10400 Pioneer Boulevard, Unit 3
 Santa Fe Springs, CA 90670
 Customer Support: 800-272-8786
 Technical Services: 800-282-8786
 Fax: 800- 200-7765
 Email: contactus@cbpmail.net
custombuildingproducts.com

3 Product Description

An effective, highly-concentrated, high-alkaline, two part (1 part powder, 1 part liquid) industrial strength cleaner and degreaser. Removes ground-in dirt, grease and soap scum. Cost effective product for use in large commercial areas such as restaurants, malls, and hotels. Also effective for quick and easy removal of all types of waxes and synthetic floor finishes.

Key Features

- Highly concentrated cost effective
- For heavily soiled and neglected areas
- Removes ground-in dirt, grease, wax and floor finishes

Suitable Tile Types

Natural stone (such as granite, limestone, marble, slate, and travertine), ceramic, porcelain, grout, concrete, quarry, masonry surfaces and other stone and tile.

Limitations to the Product

- Do not allow product to come in contact with any non-recommended surface
- Not recommended for use on vinyl or linoleum surfaces
- Do not mix with other cleaners or strippers

4 Technical Data

Technical Chart

Property	Results
pH	12-13 (alkaline)

Environmental Consideration

Complies with all Federal EPA and SCAQMD standards for VOC.

5 Instructions

Mixing Procedures

- Mix powder and liquid in plastic container only
- Do not use metal or aluminum containers
- Once mixed, cleaner will remain in solution for several months
- Store unused, mixed solution in a well marked, tightly capped plastic container



Application of Product

USE CHEMICAL-RESISTANT GLOVES, such as nitrile, when handling product.

Read entire label before using. Sweep, vacuum or wipe surface to remove loose debris. Mix 1 & 2 Deep Clean as follows in a plastic container or bucket:

CLEANING AND STRIPPING: Mix 1/4 cup (30 g) powder to 2 1/2 gallons (9.5 L) of water and mix well. Then add 1/4 cup (59 mL) of liquid and mix thoroughly.

HEAVY-DUTY CLEANING AND STRIPPING: Mix 1/2 cup (60 g) of powder to 2 1/2 gallons (9.5 L) of water and mix well. Then add 1/2 cup (118 mL) of liquid and mix thoroughly.

Note: Mixing solution with hot water is preferable, however, cold water may be used. Liberally apply cleaning solution with mop or sponge. Allow to dwell for 15 to 20 minutes. Agitate with a scrub brush or scrub machine. Do not allow solution to dry on surface. Apply additional solution if necessary. Mop up dirty solution or remove with a wet/dry vacuum. Rinse with clean water.

Cleaning of equipment

Clean tools with water before material dries.

Storage

- Close container tightly after each use
- Store in original container only
- Store in and use in temperatures between 45° F to 85° F (7° C to 29° C)
- Store in areas inaccessible to small children
- Do not reuse empty container, wrap and discard in trash or recycle

Health Precautions

CORROSIVE. CAUSES BURNS. HARMFUL IF SWALLOWED. Wear skin and eye protection. Do not breathe vapor or spray. Contains silicic acid. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If respiratory tract is irritated, move to fresh air. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting. Seek medical attention.



CUSTOM®

Aqua Mix® 1 & 2 Deep Clean

6 Availability & Cost

Location	Item Code	Size	Package
USA	010120 (set)*	8 lbs. (3.6 kg)	Powder/Liquid Drums

* Indicates a special order item

7 Product Warranty

Obtain the applicable **LIMITED PRODUCT WARRANTY** at www.custombuildingproducts.com/product-warranty or send a written request to Custom Building Products, Inc., Five Concourse Parkway, Atlanta, GA 30328, USA. Manufactured under the authority of Custom Building Products, Inc. © 2017 Quikrete International, Inc.

8 Product Maintenance

Properly applied product requires no special maintenance.

9 Technical Services Information

For technical assistance, contact Custom technical services at 800-282-8786 or visit custombuildingproducts.com.

10 Filing System

Additional product information is available from the manufacturer upon request.

VOC Content

Maximum VOCs: 14 grams per liter

Related Products

Aqua Mix® Sealer's Choice® Gold



Aqua Mix® 1 & 2 Deep Clean

Coverage

Coverage will vary depending on dilution.

Size	Min Coverage	Max Coverage
1 Unit (3.78 L)	8,000 ft ² (743 M ²)	32,000 ft ² (2,973 M ²)

