## **Aqua Mix® Cement Grout Haze Remover**

#### 1 Product Name

Agua Mix® Cement Grout Haze Remover

#### 2 Manufacturer

Custom Building Products Technical Services

10400 Pioneer Boulevard, Unit 3 Santa Fe Springs, CA 90670 Customer Support: 800-272-8786 Technical Services: 800-282-8786

Fax: 800- 200-7765

Email: contactus@cbpmail.net custombuildingproducts.com

## 3 Product Description

An acidic treatment designed to remove cementitious grout haze. Also effective for the removal of most hard water stains, rust stains, efflorescence and lime deposits. Contains no phosphates.

#### **Key Features**

- · Removes cured grout haze and mortar smears
- · Cleans hard water stains and rust
- Dissolves efflorescence
- · Contains no phosphates
- · Easy-to-use acidic treatment

#### Uses

Acid resistant natural stone (such as granite and slate), ceramic, porcelain, quarry, Saltillo, terra-cotta, and other acid-resistant tile

#### Limitations to the Product

- Do not allow product to come in contact with any non-recommended surface
- Do not mix with other cleaners
- Acids of all kinds may etch, lighten, or change the color of cementitious material, metallic glazes and some natural stones such as marble, limestone, travertine and some basalts
- Do not use to remove epoxy or premixed grout haze from tile

#### 4 Technical Data

## **Environmental Consideration**

Complies with all Federal EPA and SCAQMD standards for VOC.

## 5 Instructions

## **Application of Product**

USE CHEMICAL-RESISTANT GLOVES, such as nitrile, when handling product.

Read entire label before using. Concrete and grout installations should be cured a minimum of 10 days. Sweep, vacuum, or wipe surface. Pre-wet surface with water. Mix Aqua Mix® Cement Grout Haze Remover as follows:

LIGHT CEMENT HAZE: Mix 1 part cleaner to 3 parts water.

HEAVY CEMENT HAZE: Use product up to full strength as needed.



Apply solution to wet surface and scrub with a white nylon bristle brush. Work in small areas. Flush with water immediately after brushing.

#### Cleaning of equipment

Clean tools with water before material dries.

#### **Health Precautions**

MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear skin and eye protection. Contains urea monohydrochloride. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting, seek medical attention.

#### 6 Availability & Cost

Location	Item Code	Size	Package
USA	050162-4	1 Qt. (946 ml)	Bottle

<sup>\*</sup> Indicates a special order item

#### 7 Product Warranty

Obtain the applicable **LIMITED PRODUCT WARRANTY** at <a href="https://www.custombuildingproducts.com/product-warranty">www.custombuildingproducts.com/product-warranty</a> or send a written request to Custom Building Products, Inc., Five Concourse Parkway, Atlanta, GA 30328, USA. Manufactured under the authority of Custom Building Products, Inc. © 2017 Quikrete International, Inc.

#### 8 Product Maintenance

Properly applied product requires no special maintenance.

#### 9 Technical Services Information

For technical assistance, contact Custom technical services at 800-282-8786 or visit <u>custombuildingproducts.com</u>.

#### 10 Filing System

Additional product information is available from the manufacturer upon request.

#### **VOC Content**

Maximum VOCs: Less than 5 grams per liter



Published Date: 4/3/2018

# **Aqua Mix® Cement Grout Haze Remover**

## Handling & Storage

- Close container tightly after each use
- Store in original container only
- Store in and use in temperatures between 45° F to 85° F (7.2° C to 29.4° C)
- Store in areas inaccessible to small children
- Do not reuse empty container, wrap and discard in trash or recycle

#### **Related Products**

Aqua Mix® Grout Sealer

Aqua Mix® Non-Cement Grout Haze Remover

