

Waterproofing Reinforcing Tape

1 Product Name

Waterproofing Reinforcing Tape

2 Manufacturer

Custom Building Products
 Technical Services
 10400 Pioneer Boulevard, Unit 3
 Santa Fe Springs, CA 90670
 Customer Support: 800-272-8786
 Technical Services: 800-282-8786
 Fax: 800- 200-7765
 Email: contactus@cbpmail.net
custombuildingproducts.com

3 Product Description

An alkali resistant fiberglass tape used to reinforce RedGard® Liquid Waterproofing and Crack Prevention Membrane and RedGard® SpeedCoat™ Waterproofing Membrane around drains in shower pans, corners and wherever there is a change of plane in the installation for additional reinforcement.

Key Features

- Helps prevent breaks in waterproofing

Suitable Substrates

- Concrete, cement mortar, masonry
- Cement Backerboard
- Exterior Plywood and OSB (interior, dry areas only)
- Exterior Decks – Contact Technical Services
- Existing ceramic tile

Composition of Product

Fiberglass mesh and integrated polymer veil with an alkali-resistant coating.

Benefits of Product in the Installation

Helps prevent breaks in the waterproofing with higher degree of movement such as changes of plane.

4 Technical Data

Applicable Standards

No industry standards are available for tape alone.

Approvals

None applicable.

Technical Properties Chart

- Fiberglass mesh and integrated veil design
- Alkali-resistant coating

Environmental Consideration

Custom® Building Products is committed to environmental responsibility in both products produced and in manufacturing practices. Use of this product may contribute to LEED® certification.



5 Instructions

General Surface Prep

Exterior and wet areas must have proper sloping to drains. All surfaces must be structurally sound, clean, dry and free from contaminants that would prevent a good bond. Newly prepared concrete must be troweled smooth and textured to a fine broom finish and cured for 28 days. Existing surfaces must be scarified and leveled, and all defects must be repaired.

Application of Product

Follow installation instructions provided with RedGard® Waterproofing and Anti-Fracture Membrane or RedGard® SpeedCoat™ Waterproofing Membrane.

Protection

If tile or stone will not be set immediately after curing, protect the application from heavy traffic damage. Protect from rain and inclement weather for 72 hours after application. If delays longer than 72 hours are expected, cover the area with felt paper. Care should be taken to prevent the application from becoming soiled or punctured during and after application.

Health Precautions

Wear impervious gloves and eye protection while using this product. Avoid contact with eyes or prolonged contact with skin. Wash thoroughly after handling. If eye contact occurs, rinse cautiously with water for several minutes, remove contact lenses if easy to do: continue rinsing. Immediately seek medical advice if symptoms are significant or persist. Do not take internally. KEEP OUT OF REACH OF CHILDREN.

Conformance to Building Codes

Installation must comply with the requirements of all applicable local, state and federal code jurisdictions.

6 Availability & Cost

Item Code	Size	Package
TNSM2	2" x 50 yd	Roll



CUSTOM®

Waterproofing Reinforcing Tape

7 Product Warranty

Obtain the applicable **LIMITED PRODUCT WARRANTY** at www.custombuildingproducts.com/product-warranty or send a written request to Custom Building Products, Inc., Five Concourse Parkway, Atlanta, GA 30328, USA. Manufactured under the authority of Custom Building Products, Inc. © 2017 Quikrete International, Inc.

8 Product Maintenance

Properly installed product requires no special maintenance. Do not use as a wear surface.

9 Technical Services Information

For technical assistance, contact Custom technical services at 800-272-8786 or visit custombuildingproducts.com.

10 Filing System

Additional product information is available from the manufacturer upon request.

Related Products

RedGard® Waterproofing and Crack Prevention Membrane

RedGard® SpeedCoat® Waterproofing Membrane

