

Grout Colors for Tile and Stone. CUSTOM offers you the best color choices!

#381 Bright White

#11 Snow White

#10 Antique White

#333 Alabaster

#382 Bone

#122 Linen

#101 Quartz

#172 Urban Putty

#380 Haystack

#180 Sandstone

#135 Mushroom

Custom Building Products is North America's leader in flooring preparation products and tile and stone installation systems for residential and commercial projects. When it comes to choosing a quality grout for your next project, trust the company with the right product, performance and color selection. We know grout. Count on CUSTOM.



- Stain proof and color perfect*
- Unsurpassed stain resistance
- Never needs sealing
- Easy to spread and clean
- Ultimate color consistency



- Formulated for use in harsh environments
- High chemical, stain and temperature resistance
- Water cleanable
- Contains recycled materials which may contribute to LEED® points
- Exceeds ANSI A118.3



- Chemical and stain resistant
- Lightweight formula packs tightly into joints
- Easy to work with — Uniform in color
- Contains recycled LEED® contributing materials
- Exceeds ANSI A118.3



- Color consistent
- No efflorescence
- Cures quickly, develops high early strengths
- Lightweight, excellent handling characteristics
- Exceeds ANSI A118.7



- Polymer fortified for hard, durable, professional results
- Available in Sanded and Non-Sanded
- Resistant to shrinking, cracking and wear
- Exceeds ANSI A118.6



- Suitable for expansion joints, wet and submerged areas
- Interior/Exterior
- Use with stone and tile
- Remains permanently flexible
- ASTM C920/C794 Compliant

CUSTOM may make product modifications at any time without notice. Product specifications are subject to change. Visit custombuildingproducts.com for updated technical data sheets and MSDS information.

800-272-8786 custombuildingproducts.com

©2014 Custom Building Products.

CC6 11/14



CUSTOM®

TILE INSTALLATION SYSTEMS

CEG-IG™ Industrial Grade 100% Solids Epoxy Grout

Square Feet / M² per Unit of Grout (2 Part A + 1 Part B)

CEG-IG™

TILE SIZE

JOINT WIDTH

	1/16" (1.6 mm)	1/8" (3 mm)	1/4" (6 mm)	3/8" (9.5 mm)	1/2" (13 mm)
1" x 1" x 1/4"	96	52	31	23	19
25 x 25 x 6 mm	8.8	4.8	2.8	2.2	1.8
2" x 2" x 1/4"	182	96	52	38	31
50 x 50 x 6 mm	16.8	8.8	4.8	3.6	2.8
4-1/4" x 4-1/4" x 1/4"	379	193	101	71	55
108 x 108 x 6 mm	35.2	18.0	9.4	6.6	5.2
6" x 6" x 1/4"	530	270	140	96	73
150 x 150 x 6 mm	49.2	25	13	8.8	6.8
12" x 12" x 3/8"	702	354	180	123	92
300 x 300 x 9.5 mm	65.2	32.8	16.8	11.4	8.6
16" x 16" x 3/8"	935	470	237	161	122
400 x 400 x 9.5 mm	86.8	43.8	22	15	11.4
24" x 24" x 1/2"	1050	526	266	178	134
600 x 600 x 13 mm	97.6	48.8	24.6	16.6	12.4

Prism® Color Consistent Grout

Square Feet / M² per Unit of Grout (1 Package)

Can be used with 1/16" to 1/2" joints.

See website for details.



Polyblend® Sanded Grout

Square Feet per 25 lb. / M² per 11.34 kg



TILE SIZE

JOINT WIDTH

	1/8" (3 mm)	3/16" (4.8 mm)	1/4" (6 mm)	3/8" (9.5 mm)	1/2" (13 mm)
1" x 1" x 1/4"	63	40	25	23	20
25 x 25 x 6 mm	5.9	3.7	2.3	2.1	1.9
2" x 2" x 1/4"	88	73	50	40	33
50 x 50 x 6 mm	8.2	6.8	4.6	3.7	3.1
4-1/4" x 4-1/4" x 1/4"	210	143	110	75	60
108 x 108 x 6 mm	19.5	13.3	10.2	7	5.6
6" x 6" x 1/4"	263	178	136	93	70
150 x 150 x 6 mm	24.4	16.5	12.6	8.6	6.5
12" x 12" x 3/8"	345	230	175	118	90
300 x 300 x 9.5 mm	32.1	21.4	16.3	11.1	8.4
18" x 18" x 3/8"	512	343	253	167	118
450 x 450 x 9.5 mm	47.5	31.9	23.5	15.5	11.0
24" x 24" x 3/8"	685	458	325	225	150
600 x 600 x 9.5 mm	63.6	42.5	30.2	20.9	13.9

Polyblend® Non-Sanded Grout

Square Feet per 10 lb. / M² per 4.5 kg



TILE SIZE

JOINT WIDTH

	1/16" (1.6 mm)	1/8" (3 mm)
1" x 1" x 1/4"	44	20
25 x 25 x 6 mm	4.1	1.9
2" x 2" x 1/4"	85	40
50 x 50 x 6 mm	7.9	3.7
4-1/4" x 4-1/4" x 1/4"	149	78
108 x 108 x 6 mm	13.8	7.2
6" x 6" x 1/4"	250	120
150 x 150 x 6 mm	23.2	11.1
12" x 12" x 3/8"	331	171
300 x 300 x 9.5 mm	30.1	15.9
16" x 16" x 3/8"	370	185
400 x 400 x 9.5 mm	34.4	17.2
20" x 20" x 3/8"	453	227
500 x 500 x 9.5 mm	42.1	21.1

Coverages are approximate and may be reduced by 10 - 20% based on waste, spillage and project conditions.

STAIN PROOF*
AND
COLOR PERFECT*

Fusion Pro® Single Component® Grout

*Fusion Pro will not effloresce, mottle, fade or color shade within the grout joint when installed per manufacturer's directions. Cured Fusion Pro will not stain when exposed to most common, non-corrosive household goods and cleaning agents. All spills should be immediately cleaned from the grout. See website for details.

Coverage

Fusion Pro® Single Component® Grout

Square Feet per 1 Gallon Unit / M² per 3.78 L



TILE SIZE	JOINT WIDTH					
	1/16" (1.6 mm)	1/8" (3 mm)	3/16" (4.8 mm)	1/4" (6 mm)	3/8" (9.5 mm)	1/2" (13 mm)
1" x 1" x 1/4"	56	31	24	18	14	12
25 x 25 x 6 mm	5.2	2.9	2.2	1.7	1.3	1.1
2" x 2" x 1/4"	107	56	41	30	22	19
50 x 50 x 6 mm	9.9	5.2	3.8	2.8	2.0	1.8
6" x 6" x 1/4"	313	159	115	82	56	46
150 x 150 x 6 mm	29.1	14.8	10.7	7.6	5.2	4.3
12" x 12" x 3/8"	414	208	141	106	71	53
300 x 300 x 9.5 mm	38.5	19.3	13.1	9.8	6.6	4.9
18" x 18" x 3/8"	619	311	209	157	106	78
450 x 450 x 9.5 mm	57.5	28.9	19.4	14.6	9.8	7.2

CEG-Lite™ Commercial 100% Solids Epoxy Grout

Square Feet / M² per Combined 1 Part A + 1 Part B (9.5 lb./4.3 kg)

Coverage for larger size CEG-Lite (19 lb./8.6 kg) is double the values below. See our website for chart and details.

CEG-Lite™

TILE SIZE	JOINT WIDTH				
	1/16" (1.6 mm)	1/8" (3 mm)	1/4" (6 mm)	3/8" (9.5 mm)	1/2" (13 mm)
1" x 1" x 1/4"	50	27	16	12	10
25 x 25 x 6 mm	4.6	2.5	1.5	1.1	0.9
2" x 2" x 1/4"	95	50	27	20	16
50 x 50 x 6 mm	8.8	4.6	2.5	1.9	1.5
4-1/4" x 4-1/4" x 1/4"	198	101	53	37	29
108 x 108 x 6 mm	18.4	9.4	4.9	3.4	2.7
6" x 6" x 1/4"	277	141	73	50	38
150 x 150 x 6 mm	25.7	13.1	6.8	4.6	3.5
12" x 12" x 3/8"	367	185	94	64	48
300 x 300 x 9.5 mm	34.1	17.2	8.7	5.9	4.5
16" x 16" x 3/8"	489	246	124	84	64
400 x 400 x 9.5 mm	45.4	22.9	11.5	7.8	5.9
24" x 24" x 1/2"	549	275	139	93	70
600 x 600 x 13 mm	51.0	25.5	12.9	8.6	6.5