



SAFETY DATA SHEET

Section 1: IDENTIFICATION

1.1 PRODUCT IDENTIFIER

Product Name: Prism® SureColor® Stain Resistant Grout

Product Code: Not Available

1.2 RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE

Product Use: Grout

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEETS

Name/Address:	Custom Building Products 13001 Seal Beach Blvd. Seal Beach, CA 90740
Telephone Number:	(562)-598-8808

1.4 EMERGENCY TELEPHONE NUMBER

Emergency Telephone Number:	INFOTRAC 1-800-535-5053 (US and Canada) INTERNATIONAL + 1-352-323-3500
------------------------------------	---

Section 2: HAZARD(S) IDENTIFICATION

2.1 CLASSIFICATION OF THE CHEMICAL IN ACCORDANCE WITH PARAGRAPH (d) OF 29 CFR

1910.1200 (OSHA HAZCOM2012)

Skin Irritation	Category 2
Eye Irritation	Category 2A
STOT-SE	Category 3
STOT-RE	Category 1
Carcinogenicity	Category 1A
Reproductive Toxicity	Category 1B
Respiratory Sensitization	Category 1 ¹
Skin Sensitization	Category 1 ¹

¹ Prism SureColor Grout – Only the following colors contain cobalt compounds which is a known respiratory and skin sensitizer.

- #190 Bayleaf
- #387 Captains Blue
- #415 Concorde Grape
- #389 N Sea Green



SAFETY DATA SHEET

2.2 LABEL ELEMENTS ACCORDING TO OSHA HAZCOM2012

2.2a SIGNAL WORD:
DANGER!

2.2b HAZARD STATEMENTS
Causes skin irritation
Causes serious eye irritation
May cause respiratory irritation
Causes damage to organs through prolonged or repeated exposure
May cause cancer
May damage fertility or the unborn child
May cause allergy or asthma symptoms or breathing difficulties if inhaled¹
May cause an allergic skin reaction¹

¹ See Footnote on page 1 under Section 2.1

2.2c HAZARD PICTOGRAMS



2.2d PRECAUTIONARY STATEMENTS

i. PREVENTION	Wash hands thoroughly after handling. Do not breathe dust/fume/gas/mist/ vapors/spray. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Contaminated work clothing must not be allowed out of the workplace.
ii. RESPONSE	If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a poison center/doctor. If exposed or concerned: Get medical advice/attention.
iii. STORAGE	Store in a well-ventilated place. Keep container tightly closed. Store locked up.
iv. DISPOSAL	Dispose of contents/containers in accordance with all local, state, provincial, and federal regulations.



SAFETY DATA SHEET

2.3 ADDITIONAL INFORMATION

2.3a HNOC – HAZARDS NOT OTHERWISE CLASSIFIED

Not applicable

2.3b UNKNOWN ACUTE TOXICITY

54% of the mixture consists of ingredient(s) of unknown acute toxicity.

2.3c WHMIS CLASSIFICATION

Class D2B – Skin/Eye Irritant

Class D2A – Chronic Toxic Effects

Class D2A - Carcinogenicity

2.3d LABEL ELEMENTS ACCORDING TO WHMIS

i. WHMIS HAZARD SYMBOLS



ii. WHMIS SIGNAL WORD

WARNING!

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 MIXTURES

Chemical Name	CAS Number	Weight %
Cement, Alumina, Chemicals	65997-16-2	30 – 60%
Crystalline Silica, Quartz	14808-60-7	15 – 40%
Glass, oxide	65997-17-3	10 – 30%
Gypsum	10101-41-4	3 – 7%
Coal Ash	68131-74-8	1 – 5%
Portland cement	65997-15-1	1 – 5%
Lithium carbonate	554-13-2	0.5 – 1.5%
Carbon Black ²	1333-86-4	1 – 5%
Iron Oxide Red	1309-37-1	1 – 5%
Cobalt Compounds ¹	7440-48-4	0.1 – 1.0%

The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

¹ Prism SureColor Grout – Only the following colors contain cobalt compounds which is a known respiratory and skin sensitizer.

- #190 Bayleaf
- #387 Captains Blue
- #415 Concorde Grape
- #389 N Sea Green



SAFETY DATA SHEET

² Prism SureColor Grout – Only #60 Charcoal contains carbon black.

Section 4: FIRST-AID MEASURES

4.1 DESCRIPTION OF THE FIRST-AID MEASURES

ROUTES OF EXPOSURE	DESCRIPTION
Eye Contact:	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.
Skin Contact:	In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
Inhalation:	If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
Ingestion:	If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2 MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED

ROUTES OF EXPOSURE	DESCRIPTION
Eye Contact:	Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Skin Contact:	Causes skin irritation. Handling can cause dry skin, discomfort, irritation, and dermatitis. May cause an allergic skin reaction ¹ .
Inhalation:	May cause allergy or asthma symptoms or breathing difficulties if inhaled ¹ . May cause respiratory tract irritation. Causes damage to organs through prolonged or repeated exposure. This product contains crystalline silica. Prolonged or repeated inhalation of respirable crystalline silica from this product can cause silicosis, a serious disabling and fatal lung disease. Please see section 4.3 for further information.
Ingestion:	May be harmful if swallowed. Ingestion may cause discomfort and/or distress, nausea or vomiting.

¹ See Footnote on page 1 under Section 2.1



SAFETY DATA SHEET

4.3 INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

Note to Physicians:

The three types of silicosis include:

- Simple chronic silicosis – which results from long-term exposure (more than 20 years) to low amounts of respirable crystalline silica. Nodules of chronic inflammation and scarring provoked by the respirable crystalline silica form in the lungs and chest lymph nodes. This disease may feature breathlessness and may resemble chronic obstructive pulmonary disease (COPD).
- Accelerated silicosis – occurs after exposure to larger amounts of respirable crystalline silica over a shorter period of time (5-15 years). Inflammation, scarring, and symptoms progress faster in accelerated silicosis than in simple silicosis.
- Acute silicosis – results from short-term exposure to very large amounts of respirable crystalline silica. The lungs become very inflamed and may fill with fluid, causing severe shortness of breath and low blood oxygen levels.

Progressive massive fibrosis may occur in simple or accelerated silicosis, but is more common in the accelerated form. Progressive massive fibrosis results from severe scarring and leads to the destruction of normal lung structures.

Special Treatments:

In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

Section 5: FIRE-FIGHTING MEASURES

5.1 FLAMMABILITY

Flammability:

Not Flammable by WHMIS/OSHA HAZCOM2012 Criteria

5.2 EXTINGUISHING MEDIA

5.2a. Suitable Extinguishing Media:
Treat for surrounding material.

5.2b. Unsuitable Extinguishing Media:
Not available.

5.3 SPECIFIC HAZARDS ARISING FROM THE CHEMICAL

5.3a. Products of Combustion:

May include, and are not limited to: oxides of carbon, cobalt, and Iron



SAFETY DATA SHEET

5.3b. Explosion Data

- i. **Sensitivity to Mechanical Impact:**
Not available.
- ii. **Sensitivity to Static Discharge:**
Not available.

5.4 SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS

Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

Section 6: ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.2 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP

Methods for Containment: Recover all usable material. Pick up large pieces, then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for Cleaning-Up: Vacuum or sweep material and place in a disposal container. Dispose of unwanted material properly in accordance with all local, regional, national and international regulations.

Section 7: HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING

Handling: Use in well-ventilated areas. Wear chemical resistant gloves and eye protection. Do not mix with other chemical products. Do not get in eyes. Do not get on skin or clothing. Do not breathe fumes. Do not take internally. Good housekeeping is important to prevent accumulation of dust.

To prevent burial or suffocation, do not enter a confined space, such as a silo, bin, bulk truck, or other storage container or vessel that stores or contains this product.

General Hygiene Advice: Use good industrial hygiene practices and wear recommended personal protection. Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Storage: Keep out of the reach of children. Keep container tightly closed.



SAFETY DATA SHEET

Store at room temperature and keep containers closed when not in use. Avoid any dust buildup by frequent cleaning and suitable construction of the storage area. Keep dry until use.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETERS

Exposure Guidelines

Occupational Exposure Limits		
Chemical Name	OSHA-PEL	ACGIH-TLV
Cement, Alumina, Chemicals	Not available	Not available
Crystalline Silica, Quartz	0.1 mg/m ³	0.025 mg/m ³
Glass, oxide	15 mg/m ³ (total)	10 mg/m ³ (Total)
Gypsum	5 mg/m ³ (Resp.) 15 mg/m ³ (Total)	0.025 mg/m ³
Coal Ash	Not available	Not available
Portland cement	5 mg/m ³ (Resp.) 15 mg/m ³ (Total)	10 mg/m ³ (Resp.)
Lithium carbonate	Not available	Not available
Carbon Black	3.5 mg/m ³	3 mg/m ³
Iron Oxide Red	5 mg/m ³ (Fume)	5 mg/m ³ (Fume)
Cobalt Compounds	Not available	Not available

8.2 EXPOSURE CONTROLS

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

8.3 INDIVIDUAL PROTECTION MEASURES

8.3a. Personal Protective Equipment:

- i. **Eye/Face Protection:** Wear approved eye [properly fitted dust- or splash-proof chemical safety goggles/face (face shield)] protection
- ii. **Skin Protection:**
 1. **Hand Protection:** Wear chemical resistant gloves.
 2. **Body Protection:** Wear suitable protective clothing
- iii. **Respiratory Protection:** A NIOSH approved dust mask or filtering facepiece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).



SAFETY DATA SHEET

- iv. **General Health and Safety Measures:** Handle according to established industrial hygiene and safety practices.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance (physical state, color, etc.):	Solid Powder (Various Colors)
Odor:	Not available
Odor Threshold:	Not available
pH:	~11 – 11.5
Melting point/Freezing point:	Not available
Initial boiling point and boiling range:	Not available
Flash point:	> 212°F
Evaporation rate (Water=1):	Not available
Flammability:	Not flammable
Upper Flammability/Explosive Limit:	Not available
Lower Flammability/Explosive Limit:	Not available
Vapor Pressure	Not available
Vapor Density:	Not available
Relative Density:	1.56 – 1.62 (Wet Density)
Solubility in Water:	Slightly Soluble
Partition coefficient: n-octanol/water:	Not available
Auto-ignition temperature:	Not available
Decomposition Temperature:	Not available
Viscosity (cps):	Not available
VOC Content:	0 g/L (0%)

Section 10: STABILITY AND REACTIVITY

10.1. REACTIVITY

No dangerous reaction known under conditions of normal use.

10.2. CHEMICAL STABILITY

Stable under normal storage conditions. Keep dry in storage.

10.3. POSSIBILITY OF HAZARDOUS REACTION

Reacts with water to form alkaline solution (condition of normal use)

10.4. CONDITIONS TO AVOID

Heat. Incompatible materials.

10.5. INCOMPATIBLE MATERIALS

Acids, Aluminum, Ammonium salts, Alkali and alkaline earth metals.

10.6. HAZARDOUS DECOMPOSITION PRODUCTS

Upon decomposition, this product may yield oxides of carbon, cobalt, and iron



SAFETY DATA SHEET

Section 11: TOXICOLOGICAL INFORMATION

11.1. LIKELY ROUTES OF EXPOSURE:

Skin contact, skin absorption, eye contact, inhalation, and ingestion.

11.2. SYMPTOMS RELATED TO PHYSICAL/CHEMICAL/TOXICOLOGICAL CHARACTERISTICS:

Eye Contact: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Skin Contact: Causes skin irritation. Handling can cause dry skin, discomfort, irritation, and dermatitis. May cause an allergic skin reaction¹.

Inhalation: May cause allergy or asthma symptoms or breathing difficulties if inhaled¹. May cause respiratory tract irritation. Causes damage to organs through prolonged or repeated exposure. This product contains crystalline silica. Prolonged or repeated inhalation of respirable crystalline silica from this product can cause silicosis, a serious disabling and fatal lung disease. Please see section 4.3 for further information.

Ingestion: May be harmful if swallowed. Ingestion may cause discomfort and/or distress, nausea or vomiting.

¹ See Footnote on page 1 under Section 2.1

Acute Toxicity		
Chemical Name	LC50	LD50
Cement, Alumina, Chemicals	Not available	Oral: >2,000 mg/kg (Practically non-toxic)
Crystalline Silica, Quartz	Not available	Not available
Glass, oxide	Not available	Not available
Gypsum	Not available	Not available
Coal Ash	Not available	Not available
Portland cement	Not available	Not available
Lithium carbonate	>2 mg/L/4hrs	Dermal: >2,000 mg/kg Oral: 640 mg/kg
Carbon Black	Not available	Dermal: >3,000 mg/kg Oral: >8,000 mg/kg
Iron Oxide Red	Not available	Oral: >5,000 mg/kg
Cobalt compounds	<0.05 mg/L	Dermal: >2,000 mg/kg Oral: 550 mg/kg

Chemical Name	Chemical Listed as Carcinogens or Potential Carcinogen (NTP, IARC, OSHA, ACGIH, CP65)
Cement, Alumina, Chemicals	Not Listed
Crystalline Silica, Quartz	N-A2, I-1, O-1, CP65



SAFETY DATA SHEET

Glass, oxide	N-2, I-2B, CP65
Gypsum	Not Listed
Coal Ash	Not Listed
Portland cement	Not Listed
Lithium carbonate	CP65
Carbon Black	I-2B, O, CP65, ACGIH-A3
Iron Oxide Red	I-3, ACGIH-A4
Cobalt compounds	I-2A/2B, CP65, ACGIH-A3,O

11.3. DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT AND LONG-TERM EXPOSURE

SHORT-TERM	
Skin Corrosion/Irritation:	Causes skin irritation
Serious Eye Damage/Irritation:	Causes serious eye irritation
Respiratory Sensitization:	May cause allergy or asthma symptoms or breathing difficulties if inhaled ¹
Skin Sensitization:	May cause an allergic skin reaction ¹
STOT-Single Exposure:	May cause respiratory irritation
Aspiration Hazard:	Not available
LONG-TERM	
Carcinogenicity:	May cause cancer
Germ Cell Mutagenicity:	Not available
Reproductive Toxicity:	May damage fertility or the unborn child
STOT-Repeated Exposure:	Causes damage to organs through prolonged or repeated exposure
Synergistic/Antagonistic Effects:	Not available

¹ See Footnote on page 1 under Section 2.1

Section 12: ECOLOGICAL INFORMATION

12.1. ECOTOXICITY

May cause long-term adverse effects to the aquatic environment. Keep from entry into sewers and waterways.

Ecotoxicity		
Chemical Name	EC50/NOEC-48 Hours	LC50/NOEC-96 Hours
Cement, Alumina, Chemicals	Not available	Not available
Crystalline Silica, Quartz	Not available	Not available
Glass, oxide	Not available	>1,000 mg/L Zebra fish
Gypsum	Not available	Not available
Coal Ash	LC50 > 100 mg/L Daphnia Magna	LC50: > 100 mg/L
Portland cement	Not available	Not available
Lithium carbonate	EC50 - 33.2 mg/L Daphnia Magna (No mortality)	LC50 - 30.3 mg/L NOEC - 19.1 mg/L
Carbon Black	EC50 - Daphnia magna (Water flea) - > 5,600 mg/l - 24 h	LC50 - > 1,000 mg/l - Zebra fish



SAFETY DATA SHEET

Iron Oxide Red	Not available	Not available
Cobalt compounds	Not available	Not available

12.2. PERSISTENCE AND DEGRADABILITY

Not available

12.3. BIOACCUMULATIVE POTENTIAL

Not available

12.4. MOBILITY IN SOIL

Not available

12.5. OTHER ADVERSE EFFECTS

Not available

Section 13: DISPOSAL CONSIDERATIONS

13.1. DISPOSAL METHOD

Dispose of contents/containers in accordance with all local, state, provincial, and federal regulations

13.2. OTHER DISPOSAL CONSIDERATIONS

Not available

Section 14: TRANSPORT INFORMATION

DOT (U.S.)	TDG (CANADA)
UN NUMBER: Not regulated	UN NUMBER: Not regulated
UN PROPER SHIPPING NAME: Not regulated	UN PROPER SHIPPING NAME: Not regulated
TRANSPORT HAZARD CLASS (ES): Not regulated	TRANSPORT HAZARD CLASS (ES): Not regulated
PACKING GROUP (if applicable): Not regulated	PACKING GROUP (if applicable): Not regulated

SUMMARY: Product is not regulated under DOT/TDG and other transportation regulations.

14.1. ENVIRONMENTAL HAZARDS

Not available

14.2. TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE

Not available

14.3. SPECIAL PRECAUTIONS FOR USER

Do not handle until all safety precautions have been read and understood.



SAFETY DATA SHEET

Section 15: REGULATORY INFORMATION

15.1. SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATIONS SPECIFIC FOR THE CHEMICAL

Canada: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

US: MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

15.2. US FEDERAL INFORMATION:

SARA TITLE III: Section 302, Extremely Hazardous Substances, 40 CFR 355:

SARA TITLE III: Section 311 and 312, MSDS Requirements, 40 CFR 370 Hazard Classes: Fire Hazard; Immediate (Acute) Health Hazard; Chronic Health Hazard; Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds for the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

SARA TITLE III: Section 313, Toxic Chemicals Notification, 40 CFR 372: This product may be subject to SARA notification requirements if it contains Toxic Chemical Constituents above their de minimus concentrations.

Clean Air Act – Not available

SARA TITLE III				
CHEMICAL NAME	SECTION 302 (EHS) TPQ (LBS)	SECTION 304 EHS RQ (LBS)	CERCLA RQ (LBS)	SECTION 313 (TRI)
Cement, Alumina, Chemicals	Not Listed	Not Listed	Not Listed	Not Listed
Crystalline Silica, Quartz	Not Listed	Not Listed	Not Listed	Not Listed
Glass, oxide	Not Listed	Not Listed	Not Listed	Not Listed
Gypsum	Not Listed	Not Listed	Not Listed	Not Listed
Coal Ash	Not Listed	Not Listed	Not Listed	Not Listed
Portland cement	Not Listed	Not Listed	Not Listed	Not Listed
Lithium carbonate	Not Listed	Not Listed	Not Listed	Listed
Carbon Black	Not Listed	Not Listed	Not Listed	Not Listed
Iron Oxide Red	Not Listed	Not Listed	Not Listed	Not Listed
Cobalt compounds	Not Listed	Not Listed	&	Listed

"&" - Indicates that no RQ is assigned to this generic or broad class, although the class is a CERCLA hazardous substance. See 50 Federal Register 13456 (April 4, 1985).

15.3. US STATE RIGHT TO KNOW LAWS:

California Proposition 65:	WARNING! This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm (Crystalline Silica, Lithium Carbonate)
-----------------------------------	---



SAFETY DATA SHEET

Other U.S. States "Right to Know" Lists:	
New Jersey:	CEMENT, ALUMINA, CHEMICALS: CAS#65997-16-2 SILICA, QUARTZ: CAS#14808-60-7 GLASS, OXIDE: CAS#65997-17-3 GYPSUM (CALCIUM SULFATE): CAS#10101-41-4 COAL ASH: CAS#68131-74-8
Pennsylvania:	CEMENT, ALUMINA, CHEMICALS: CAS#65997-16-2 SILICA, QUARTZ: CAS#14808-60-7 GLASS, OXIDE: CAS#65997-17-3 GYPSUM (CALCIUM SULFATE): CAS#10101-41-4 COAL ASH: CAS#68131-74-8
Massachusetts:	QUARTZ: CAS#14808-60-7 PORTLAND CEMENT: CAS#65997-15-1 GYPSUM (CALCIUM SULFATE): CAS#10101-41-4 CARBON BLACK: CAS#1333-86-4 LITHIUM CARBONATE: CAS#554-13-2
Minnesota:	SILICA, QUARTZ: CAS#14808-60-7 PORTLAND CEMENT: CAS#65997-15-1 GYPSUM (CALCIUM SULFATE): CAS#7778-18-9 CARBON BLACK: CAS#1333-86-4
Florida:	Not Available
Michigan:	Not Available

15.4. GLOBAL INVENTORIES

Chemical Name	USA TSCA	Canada DSL/NDL
Cement, Alumina, Chemicals	Yes	DSL
Crystalline Silica, Quartz	Yes	DSL
Glass, oxide	Yes	DSL
Gypsum	Yes	DSL
Coal Ash	Yes	DSL
Portland cement	Yes	DSL
Lithium carbonate	Yes	DSL
Carbon Black	Yes	DSL
Iron Oxide Red	Yes	DSL
Cobalt compounds	Yes	DSL



SAFETY DATA SHEET

15.5. NFPA AND HMIS RATINGS:

<p style="text-align: center; margin: 0;">HEALTH HAZARD</p> <p>4 EXTREME - Highly toxic - May be fatal on short-term exposure.</p> <p>3 SERIOUS - Toxic - Full protective suit and breathing apparatus should be worn.</p> <p>2 MODERATE - Breathing apparatus and face mask must be worn.</p> <p>1 SLIGHT - Breathing apparatus may be worn.</p> <p>0 MINIMAL - No precautions necessary.</p>	<p style="text-align: center; margin: 0;">FLAMMABILITY HAZARD</p> <p>4 EXTREME - Extremely flammable gas or liquid. Flash Point below 73°F.</p> <p>3 SERIOUS - Flammable. Flash Point 73°F to 100°F.</p> <p>2 MODERATE - Combustible. Requires moderate heating to ignite. Flash Point below 200°F.</p> <p>1 SLIGHT - Slightly combustible. Requires strong heating to ignite.</p> <p>0 MINIMAL - Will not burn under normal conditions.</p>
<p style="text-align: center; margin: 0;">SPECIFIC HAZARD</p> <p>OXIDIZER OXY</p> <p>ACID ACID</p> <p>ALKALI ALK</p> <p>CORROSIVE COR</p> <p>Use NO WATER W</p> <p>RADIATION ☼</p>	<p style="text-align: center; margin: 0;">INSTABILITY HAZARD</p> <p>4 EXTREME - Explosive at room temperature.</p> <p>3 SERIOUS - May detonate if shocked or heated under confinement or mixed with water.</p> <p>2 MODERATE - Unstable. May react with water.</p> <p>1 SLIGHT - May react if heated or mixed with water.</p> <p>0 MINIMAL - Normally stable. Does not react with water.</p>

NFPA

HMIS

2 HEALTH	PROTECTIVE EQUIPMENT INDEX	
0 FLAMMABILITY	A	G
0 REACTIVITY	B	H
0 PERSONAL PROTECTION	C	I
G	D	J
	E	K
	F	X Ask your supervisor for special handling instructions.

*Chronic Hazard Indicator

15.6. SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

CP65	California Proposition 65
OSHA (O)	Occupational Safety and Health Administration
ACGIH (G)	American Conference of Governmental Industrial Hygienists <ul style="list-style-type: none"> A1 – Confirmed human carcinogen A2 – Suspected human carcinogen A3 – Animal carcinogen A4 – Not classifiable as a human carcinogen A5 – Not suspected a human carcinogen
IARC (I)	International Agency for Research on Cancer <ul style="list-style-type: none"> 1 – The agent (mixture) is carcinogenic to humans 2A – The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals. 2B – The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of



SAFETY DATA SHEET

	<p>sufficient evidence of carcinogenicity in experimental animals.</p> <ul style="list-style-type: none"> • 3 – The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans. • 4 – The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.
NTP (N)	<p>National Toxicology Program</p> <ul style="list-style-type: none"> • 1 – Known to be carcinogens • 2 – Reasonably anticipated to be carcinogens

Section 16: OTHER INFORMATION

Date of Preparation: April 28, 2014

Version: 1.0

Revision Date: N/A

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Prepared by: Custom Building Products
Phone: (562)-968-2980
www.custombuildingproducts.com

End of Safety Data Sheet