



SAFETY DATA SHEET

Section 1: IDENTIFICATION

1.1 PRODUCT IDENTIFIER

Product Name: SimpleFix Ceramic Tile & Fixture Caulk
Product Code: Not available.

1.2 RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE

Use: Sealant.

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Name/Address: Custom Building Products
3490 Piedmont Rd Suite 1300
Atlanta, GA 30329

Telephone Number: (562) 598-8808

1.4 EMERGENCY TELEPHONE NUMBER

Emergency Telephone Number: INFOTRAC 1-800-535-5053 (US and Canada)
INTERNATIONAL + 1-352-323-3500

Section 2: HAZARD(S) IDENTIFICATION

2.1 CLASSIFICATION OF THE CHEMICAL ACCORDING TO OSHA HAZCOM 2012

Hazard class

Carcinogenicity 1A
Specific target organ toxicity - Repeated Exposure 1

2.2 LABEL ELEMENTS ACCORDING TO OSHA HAZCOM 2012

Hazard Pictogram:



Signal Word: Danger

Hazard Statement: May cause cancer. Causes damage to lungs through prolonged or repeated exposure.

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe fumes/vapors. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product.

Response: If exposed or concerned: Get medical advice/attention.

Storage: Store locked up.

Disposal: Dispose of contents and container in accordance with all local, regional, national and international regulations.



SAFETY DATA SHEET

2.3 ADDITIONAL INFORMATION

Hazards not otherwise classified: Not applicable.

30% of the mixture consists of ingredient(s) of unknown acute toxicity.

WHMIS Classification(s):

Class D2A - Carcinogenicity

Class D2A - Chronic Toxic Effects

WHMIS Hazard Symbols:



WHMIS Signal Word: CAUTION

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 MIXTURES

Ingredient	CAS No	Wt. %
Calcium carbonate	1317-65-3	40 - 70
Silica, crystalline, quartz	14808-60-7	15 - 40
1,2-Propylene glycol	57-55-6	1 - 5
Titanium dioxide	13463-67-7	0.5 - 1.5
Hydrotreated heavy naphtha (petroleum)	64742-48-9	0.1 - 1
Carbon black	1333-86-4	0.1 - 1

The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

Section 4: FIRST-AID MEASURES

4.1 DESCRIPTION OF THE FIRST AID MEASURE

- Eye:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.
- Skin:** In case of contact, immediately flush skin with plenty of soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
- Inhalation:** If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
- Ingestion:** If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

- Eye:** May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.



SAFETY DATA SHEET

Skin:	May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
Inhalation:	May cause respiratory tract irritation. Causes damage to lungs through prolonged or repeated exposure.
Ingestion:	May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENTS NEEDED

Note to Physicians:	Symptoms may not appear immediately.
Specific Treatments:	In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

Section 5: FIRE-FIGHTING MEASURES

5.1 FLAMMABILITY

Flammability:	Not flammable by WHMIS/OSHA criteria.
----------------------	---------------------------------------

5.2 EXTINGUISHING MEDIA

Suitable Extinguishing Media:	Powder, water spray, foam, carbon dioxide.
Unsuitable Extinguishing Media:	Not available.

5.3 SPECIAL HAZARDS ARISING FROM THE CHEMICAL

Products of Combustion:	May include, and are not limited to: oxides of carbon, oxides of nitrogen.
Explosion Data:	
Sensitivity to Mechanical Impact:	Not available.
Sensitivity to Static Discharge:	Not available.

5.4 SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE FIGHTERS

Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

Section 6: ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.2 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING - UP

Methods for Containment:	Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
Methods for Cleaning-Up:	Scoop up material and place in a disposal container. Provide ventilation.



SAFETY DATA SHEET

Section 7: HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING

- Handling:** Avoid contact with skin and eyes. Do not swallow. Do not breathe fumes/vapors. Handle and open container with care. When using do not eat, drink or smoke. (See section 8)
- General Hygiene Advice:** Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

- Storage:** Keep out of the reach of children. Keep container tightly closed. Store in a well-ventilated place. Do not store at temperatures above 49 °C / 120 °F. Keep from freezing. (See section 10)

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETERS

Exposure Guidelines

Occupational Exposure Limits		
Ingredient	OSHA-PEL	ACGIH-TLV
Calcium carbonate	15 mg/m ³ (total); 5 mg/m ³ (resp)	10 mg/m ³
Silica, crystalline, quartz	((10 mg/m ³)/(%SiO ₂ +2) TWA (resp)) ((30 mg/m ³)/(%SiO ₂ +2) TWA (total)) ((250)/(%SiO ₂ +5) mppcf TWA (resp))	0.025 mg/m ³
1,2-Propylene glycol	Not available.	Not available.
Titanium dioxide	15 mg/m ³ (total dust)	10 mg/m ³
Hydrotreated heavy naphtha (petroleum)	Not available.	Not available.
Carbon black	3.5 mg/m ³	3 mg/m ³

8.2 EXPOSURE CONTROLS

- Engineering Controls:** Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

8.3 INDIVIDUAL PROTECTIVE MEASURES

Personal Protective Equipment:

Eye/Face Protection: Safety glasses or goggles are recommended when using product.

Skin Protection:

Hand Protection: Wear chemical-resistant gloves.

Body Protection: Wear suitable protective clothing.

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

General Health and Safety Measures: Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Wash contaminated clothing before reusing.



SAFETY DATA SHEET

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Smooth paste.
Color:	Various colours.
Odor:	Mild acrylic.
Odor Threshold:	Not available.
Physical State:	Liquid.
pH:	7.0 – 9.0
Melting Point/Freezing Point:	Not available.
Initial Boiling Point and Boiling Range:	Not available.
Flash Point:	> 93.3 °C (> 200 °F) (closed cup)
Evaporation Rate:	Not available.
Flammability:	Not flammable.
Lower Flammability/Explosive Limit:	Not available.
Upper Flammability/Explosive Limit:	Not available.
Vapor Pressure:	Not available.
Vapor Density:	> 1 (Air = 1)
Relative Density/Specific Gravity:	1.50 – 1.70
Solubility:	Not available.
Partition coefficient: n-octanol/water:	Not available.
Auto-ignition Temperature:	Not available.
Decomposition Temperature:	Not available.
Viscosity:	Not available.
Oxidizing Properties:	Not available.
Explosive Properties:	Not available.
VOC content, g/L:	15 g/L (1.5%)

Section 10: STABILITY AND REACTIVITY

10.1 REACTIVITY

No dangerous reaction known under conditions of normal use.

10.2 CHEMICAL STABILITY

Stable under normal storage conditions.

10.3 POSSIBILITY OF HAZARDOUS REACTIONS

No dangerous reaction known under conditions of normal use.



SAFETY DATA SHEET

10.4 CONDITIONS TO AVOID

Heat. Incompatible materials.

10.5 INCOMPATIBLE MATERIALS

Strong bases. Oxidizers.

10.6 HAZARDOUS DECOMPOSITION PRODUCTS

May include, and are not limited to: oxides of carbon, oxides of nitrogen.

Section 11: TOXICOLOGICAL INFORMATION

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS

Likely Routes of Exposure: Skin contact, eye contact, inhalation, and ingestion.

Symptoms related to physical/chemical/toxicological characteristics:

Eye: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

Skin: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.

Ingestion: May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

Inhalation: May cause respiratory tract irritation. Causes damage to lungs through prolonged or repeated exposure.

Acute Toxicity:

Ingredient	LC50	LD50
Calcium carbonate	Not available.	Oral 6450 mg/kg, rat
Silica, crystalline, quartz	Not available.	Oral TD ₀₁ 120 g/kg, rat
1,2-Propylene glycol	Not available.	Oral 20000 mg/kg, rat Dermal 20800 mg/kg, rabbit
Titanium dioxide	Not available.	Oral >10000 mg/kg, rat Dermal >10000mg/kg, rabbit
Hydrotreated heavy naphtha (petroleum)	Not available.	Oral >5000 mg/kg, rat Dermal >3160 mg/kg, rabbit
Carbon black	Not available.	Oral >15400 mg/kg, rat Dermal >3 g/kg, rabbit

Calculated overall Chemical Acute Toxicity Values

LC50 (inhalation)	LD50 (oral)	LD50 (dermal)
Not available.	>2000 mg/kg, rat	>2000 mg/kg, rabbit

Ingredient	Chemical Listed as Carcinogen or Potential Carcinogen (NTP, IARC, OSHA, ACGIH, CP65)*
Calcium carbonate	Not listed.
Silica, crystalline, quartz	G-A2, I-1, N-1, O, CP65
1,2-Propylene glycol	Not listed.
Titanium dioxide	G-A4, I-2B, O, CP65
Hydrotreated heavy naphtha (petroleum)	Not listed.
Carbon black	G-A3, I-2B, O, CP65



SAFETY DATA SHEET

* See Section 15 for more information.

11.2 DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT- AND LONG-TERM EXPOSURE

Skin Corrosion/Irritation:	Based on available data, the classification criteria are not met.
Serious Eye Damage/Irritation:	Based on available data, the classification criteria are not met.
Respiratory Sensitization:	Based on available data, the classification criteria are not met.
Skin Sensitization:	Based on available data, the classification criteria are not met.
STOT-Single Exposure:	Based on available data, the classification criteria are not met.
Chronic Health Effects:	
Carcinogenicity:	May cause cancer.
Germ Cell Mutagenicity:	Based on available data, the classification criteria are not met.
Reproductive Toxicity:	
Developmental:	Based on available data, the classification criteria are not met.
Teratogenicity:	Based on available data, the classification criteria are not met.
Embryotoxicity:	Based on available data, the classification criteria are not met.
Fertility:	Based on available data, the classification criteria are not met.
STOT-Repeated Exposure:	Causes damage to lungs through prolonged or repeated exposure.
Aspiration Hazard:	Based on available data, the classification criteria are not met.
Toxicologically Synergistic Materials:	Not available.
Other Information:	Not available.

Section 12: ECOLOGICAL INFORMATION

12.1 ECOTOXICITY

Acute/Chronic Toxicity: May cause long-term adverse effects in the aquatic environment.

12.2 PERSISTENCE AND DEGRADABILITY

Not available.

12.3 BIOACCUMULATIVE POTENTIAL

Bioaccumulation: Not available.

12.4 MOBILITY IN SOIL

Not available.

12.5 OTHER ADVERSE EFFECTS

Not available.

Section 13: DISPOSAL CONSIDERATIONS

13.1 WASTE TREATMENT METHODS

Disposal Method: This material must be disposed of in accordance with all local, state, provincial, and federal regulations.



SAFETY DATA SHEET

Other disposal recommendations: Not available.

Section 14: TRANSPORT INFORMATION

14.1 UN NUMBER

DOT

Not regulated.

TDG

Not regulated.

14.2 UN PROPER SHIPPING NAME

DOT

Not applicable.

TDG

Not applicable.

14.3 TRANSPORT HAZARD CLASS (ES)

DOT

Not applicable.

TDG

Not applicable.

14.4 PACKING GROUP

DOT

Not applicable.

TDG

Not applicable.

14.5 ENVIRONMENTAL HAZARDS

Not available.

14.6 TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE

Not available.

14.7 SPECIAL PRECAUTIONS FOR USER

Do not handle until all safety precautions have been read and understood.

Section 15: REGULATORY INFORMATION

15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/ LEGISLATIONS SPECIFIC FOR THE CHEMICAL

Canada: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

US: MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

SARA Title III				
Ingredient	Section 302 (EHS) TPQ (lbs.)	Section 304 EHS RQ (lbs.)	CERCLA RQ (lbs.)	Section 313
Calcium carbonate	Not listed.	Not listed.	Not listed.	Not listed.
Silica, crystalline, quartz	Not listed.	Not listed.	Not listed.	Not listed.
1,2-Propylene glycol	Not listed.	Not listed.	Not listed.	Not listed.
Titanium dioxide	Not listed.	Not listed.	Not listed.	Not listed.
Hydrotreated heavy naphtha (petroleum)	Not listed.	Not listed.	Not listed.	Not listed.
Carbon black	Not listed.	Not listed.	Not listed.	Not listed.



SAFETY DATA SHEET

State Regulations

California Proposition 65:

This product contains chemicals known to the State of California to cause cancer. (Silica, crystalline; Titanium dioxide; Carbon black)

Global Inventories:

Ingredient	Canada DSL/NDSL	USA TSCA
Calcium carbonate	NDSL	Yes.
Silica, crystalline, quartz	DSL	Yes.
1,2-Propylene glycol	DSL	Yes.
Titanium dioxide	DSL	Yes.
Hydrotreated heavy naphtha (petroleum)	DSL	Yes.
Carbon black	DSL	Yes.

NFPA National Fire Protection Association:

Health:	1
Fire:	1
Reactivity:	0

HMIS-Hazardous Materials Identification System

Health:	1*
Fire:	1
Physical Hazard:	0

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

CP65 California Proposition 65

OSHA (O) Occupational Safety and Health Administration.

ACGIH (G) American Conference of Governmental Industrial Hygienists.

A1 - Confirmed human carcinogen.

A2 - Suspected human carcinogen.

A3 - Animal carcinogen.

A4 - Not classifiable as a human carcinogen.

A5 - Not suspected as a human carcinogen.

IARC (I) International Agency for Research on Cancer.

1 - The agent (mixture) is carcinogenic to humans.

2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.

2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.

3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.

4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

NTP (N) National Toxicology Program.

1 - Known to be carcinogens.

2 - Reasonably anticipated to be carcinogens.



SAFETY DATA SHEET

Section 16: OTHER INFORMATION

Date of Preparation: Jan 30, 2015

Version: 2.0

Revision Date: Jan 30, 2015

Disclaimer: The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to silica contained in our products

Prepared by: Nexreg Compliance Inc.
Phone: (519) 488-5126
www.nexreg.com

Prepared for: Custom Building Products

End of Safety Data Sheet