
SAFETY DATA SHEET

Section 1: IDENTIFICATION

1.1 PRODUCT IDENTIFIER

Product Name: RedGard® SpeedCoat® Waterproofing Membrane
Product Code: Not Available

1.2 RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE

Product Use: Waterproofing Membrane

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEETS

Name/Address: Custom Building Products
Five Concourse Parkway, Suite 1900
Atlanta, GA 30328

Telephone Number: 1-(800)-272-8786

1.4 EMERGENCY TELEPHONE NUMBER

Emergency Telephone Number: INFOTRAC 1-800-535-5053 (US and Canada)
INTERNATIONAL + 1-352-323-3500

Section 2: HAZARD(S) IDENTIFICATION

2.1 CLASSIFICATION OF THE CHEMICAL IN ACCORDANCE WITH PARAGRAPH (d) OF 29 CFR 1910.1200 (OSHA HAZCOM2012)

| | |
|--|-------------|
| Flammable Liquid | Category 3 |
| Skin Irritation | Category 2 |
| Serious Eye Damage | Category 1 |
| Skin Sensitization | Category 1B |
| Specific Target Organ Toxicity—Single Exposure | Category 3 |
| Specific Target Organ Toxicity—Repeated Exposure | Category 1 |
| Carcinogenicity | Category 1A |
| Reproductive Toxicity | Category 1 |

2.2 LABEL ELEMENTS ACCORDING TO OSHA HAZCOM2012

2.2a SIGNAL WORD:
DANGER!

2.2b HAZARD STATEMENTS

Flammable liquid and vapor
Causes skin irritation
Causes serious eye damage
May cause an allergic skin reaction
May cause respiratory irritation
Causes damage to organs through prolonged or repeated exposure
May cause cancer

SAFETY DATA SHEET

May damage fertility or the unborn child (oral)

2.2c HAZARD PICTOGRAMS



2.2d PRECAUTIONARY STATEMENTS

| | |
|----------------------|--|
| i. PREVENTION | Keep away from heat/sparks/open flames/hot surfaces. Wash hands thoroughly after handling. Do not breathe fume/vapors/spray. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear impervious gloves/protective clothing/eye protection/face protection. Contaminated work clothing must not be allowed out of the workplace. |
| ii. RESPONSE | In case of fire: Use water to extinguish. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: call a poison center/doctor. If exposed or concerned: Get medical advice/attention. |
| iii. STORAGE | Store locked up. Store in a well-ventilated place. Keep cool. Keep container tightly closed. |
| iv. DISPOSAL | Dispose of contents/containers in accordance with all local, state, provincial, and federal regulations. |

2.3 ADDITIONAL INFORMATION

2.3a HNOC – HAZARDS NOT OTHERWISE CLASSIFIED

Not Applicable

2.3b UNKNOWN ACUTE TOXICITY

12.5% of the mixture consists of ingredient(s) of unknown acute toxicity.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 MIXTURES

| Chemical Name | CAS Number | Weight % |
|------------------------------|------------|-----------|
| Calcium Carbonate | 1317-65-3 | 30 – 60%* |
| Portland Cement | 65997-15-1 | 5 – 10%* |
| Decamethylcyclopentasiloxane | 541-02-6 | 3 – 7%* |
| Hexadecyltrimethoxysilane | 16415-12-6 | 3 – 7%* |

SAFETY DATA SHEET

| | | |
|----------------------------|------------|-------------|
| Trimethoxy vinylsilane | 2768-02-7 | 3 – 7%* |
| 2-Butoxyethanol | 111-76-2 | 3 – 7%* |
| Crystalline Silica, Quartz | 14808-60-7 | 0.1 – 1.0%* |
| Dibutyltin Diacetate | 1067-33-0 | 0.1 – 1.0%* |

*Means that the component will fall into one of the ranges specified due to batch-to-batch variability and to protect Confidential Business Information.

Section 4: FIRST-AID MEASURES

4.1 DESCRIPTION OF THE FIRST-AID MEASURES

| ROUTES OF EXPOSURE | DESCRIPTION |
|----------------------|--|
| Eye Contact: | In case of contact, immediately flush eyes with plenty of water for several minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately. |
| Skin Contact: | In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists. |
| Inhalation: | If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell. |
| Ingestion: | If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention. |

4.2 MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED

| ROUTES OF EXPOSURE | DESCRIPTION |
|----------------------|--|
| Eye Contact: | Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. |
| Skin Contact: | Causes skin irritation. Handling can cause dry skin, discomfort, irritation, and dermatitis. May cause sensitization by skin contact. |
| Inhalation: | May cause respiratory tract irritation. Causes damage to organs through prolonged or repeated exposure. This product contains crystalline silica. Prolonged or repeated inhalation of respirable crystalline silica from this product can cause silicosis, a serious disabling and fatal lung disease. |
| Ingestion: | May be harmful if swallowed. Ingestion may cause discomfort and/or distress, nausea or vomiting. May cause cancer. May damage fertility or the unborn child. |

4.3 INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

Note to Physicians: Symptoms may not appear immediately.

SAFETY DATA SHEET

Specific Treatments: In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

Section 5: FIRE-FIGHTING MEASURES

5.1 FLAMMABILITY

Flammability: Flammable by WHMIS/OSHA HAZCOM2012 Criteria

5.2 EXTINGUISHING MEDIA

5.2a. Suitable Extinguishing Media:
Carbon dioxide, dry chemicals or alcohol-resistant foam

5.2b. Unsuitable Extinguishing Media:
Water, halones

5.3 SPECIFIC HAZARDS ARISING FROM THE CHEMICAL

5.3a. Products of Combustion:
Hazardous combustion products: carbon monoxide, carbon dioxide, silicon dioxide, formaldehyde.

5.3b. Explosion Data

- i. **Sensitivity to Mechanical Impact:**
Not Available
- ii. **Sensitivity to Static Discharge:**
Not Available

5.4 SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS

Keep upwind of fire. Wear full fire fighting turn-out gear(full bunker gear) and respiratory protection (SCBA).

Section 6: ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.2 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP

Methods for Containment: Recover all usable material. Pick up large pieces, and then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for Cleaning-Up: Do not flush away with water. Dispose of unwanted material properly in accordance with all local, regional, national and international regulations.

SAFETY DATA SHEET

Section 7: HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING

- Handling:** Use in well-ventilated areas. Wear impervious gloves and eye protection. Do not mix with other chemical products, except as indicated by the manufacturers. Do not get in eyes. Do not get on skin or clothing. Do not breathe fumes. Do not take internally. Good housekeeping is important to prevent accumulation of dust.
- General Hygiene Advice:** Use good industrial hygiene practices and wear recommended personal protection. Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

- Storage:** Keep out of the reach of children. Store locked up. Keep container tightly closed. Store at room temperature and keep containers closed when not in use. Avoid any dust buildup by frequent cleaning and suitable construction of the storage area.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETER

Exposure Guidelines

| Occupational Exposure Limits | | |
|------------------------------|---|------------------------------|
| Chemical Name | OSHA-PEL | ACGIH-TLV |
| Calcium Carbonate | 5 mg/m ³ (Resp.) 15 mg/m ³ (Total) | 2 mg/m ³ (Resp.) |
| Portland Cement | 5 mg/m ³ (Resp.) 15 mg/m ³ (Total) | 10 mg/m ³ (Resp.) |
| Decamethylcyclopentasiloxane | Not Available | Not Available |
| Hexadecyltrimethoxysilane | Not Available | Not Available |
| Trimethoxy vinylsilane | Not Available | Not Available |
| 2-Butoxyethanol | 50 ppm | 20 ppm |
| Crystalline Silica, Quartz | 10 mg/m ³ | 0.025 mg/m ³ |
| Dibutyltin Diacetate | 0.1 mg/m ³ | 0.2 mg/m ³ |

8.2 EXPOSURE CONTROLS

- Engineering Controls:** Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

8.3 INDIVIDUAL PROTECTION MEASURES

8.3a. Personal Protective Equipment:

- i. **Eye/Face Protection:** Wear approved eye protection [properly fitted dust- or splash-proof chemical safety goggles/face (face shield)]

SAFETY DATA SHEET

- ii. **Skin Protection:**
 - 1. **Hand Protection:** Wear impervious gloves, such as nitrile.
 - 2. **Body Protection:** Wear suitable protective clothing
- iii. **Respiratory Protection:** A NIOSH approved respirator or filtering face piece, such as N95, is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).
- iv. **General Health and Safety Measures:** Handle according to established industrial hygiene and safety practices.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--|---|
| Appearance (physical state, color, etc.): | Red Liquid |
| Odor: | Characteristic |
| Odor Threshold: | Not Available |
| pH: | Not Available |
| Melting point/Freezing point: | Not Available |
| Initial boiling point and boiling range: | Not Available |
| Flash point: | 127°F (52.7°C) |
| Evaporation rate (Water=1): | Not available |
| Flammability: | Flammable, Category 3 in accordance to OSHA 2012. |
| Upper Flammability/Explosive Limit: | Not Available |
| Lower Flammability/Explosive Limit: | Not Available |
| Vapor Pressure | Not Available |
| Vapor Density: | Not Available |
| Relative Density: | 1.35 – 1.45 g/mL |
| Solubility in Water: | Not Available |
| Partition coefficient: n-octanol/water: | Not Available |
| Auto-ignition temperature: | Not Available |
| Decomposition Temperature: | Not Available |
| Viscosity (cps): | Not Available |
| VOC Content: | 81 g/L |

Section 10: STABILITY AND REACTIVITY

10.1. REACTIVITY

No dangerous reaction known under conditions of normal use.

10.2. CHEMICAL STABILITY

Stable under normal storage conditions. Keep dry in storage.

10.3. POSSIBILITY OF HAZARDOUS REACTION

No dangerous reaction known under conditions of normal use.

10.4. CONDITIONS TO AVOID

SAFETY DATA SHEET

Moisture and Heat.

10.5. INCOMPATIBLE MATERIALS

Reacts with water, bases and acids.

10.6. HAZARDOUS DECOMPOSITION PRODUCTS

If stored and handled properly: none known.

Section 11: TOXICOLOGICAL INFORMATION

11.1. LIKELY ROUTES OF EXPOSURE:

Skin contact, skin absorption, eye contact, inhalation, and ingestion.

11.2. SYMPTOMS RELATED TO PHYSICAL/CHEMICAL/TOXICOLOGICAL CHARACTERISTICS:

Eye Contact: Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Skin Contact: Causes skin irritation. Handling can cause dry skin, discomfort, irritation, and dermatitis. May cause sensitization by skin contact.

Inhalation: May cause respiratory tract irritation. Causes damage to organs through prolonged or repeated exposure. This product contains crystalline silica. Prolonged or repeated inhalation of respirable crystalline silica from this product can cause silicosis, a serious disabling and fatal lung disease.

Ingestion: May be harmful if swallowed. Ingestion may cause discomfort and/or distress, nausea or vomiting. Ingestion may cause cancer. Ingestion may damage fertility or the unborn child.

| Acute Toxicity | | | |
|------------------------------|--------------------------------|---|------------|
| Chemical Name | LC50 | LD50 | |
| Calcium Carbonate | Not Available | Oral: 6,450 mg/kg, rat | |
| Portland Cement | Not Available | Not Available | |
| Decamethylcyclopentasiloxane | Inhalation: 8.67 mg/L, 4h, rat | Oral: >5,000 mg/kg, rat Dermal:>2,000 mg/kg, rat | |
| Hexadecyltrimethoxysilane | Not Available | Not Available | |
| Trimethoxy vinylsilane | Inhalation: 16.8 mg/L, 4h, rat | Oral: 7.178 mg/kg, rat Dermal: 3,200 mg/kg, rabbit | |
| 2-Butoxyethanol | Not Available | Oral: 880 mg/kg, rat Dermal: 1,060 mg/kg, rat | |
| Crystalline Silica, Quartz | Not Available | Not Available | |
| Dibutyltin Diacetate | Inhalation: 75 mg/L, rat | Oral: 913 mg/kg ,rat Dermal: 2,266 mg/kg, rat | |
| Mixture ATE | Oral | Dermal | Inhalation |
| Calculated Data | 3,120 mg/kg | >2,000 mg/kg | >20 mg/L |

SAFETY DATA SHEET

| Carcinogenicity | |
|------------------------------|---|
| Chemical Name | Chemical Listed as Carcinogens or Potential Carcinogen (NTP,IARC,OSHA,ACGIH,CP65) |
| Calcium Carbonate | Not Listed |
| Portland Cement | ACGIH-A4 |
| Decamethylcyclopentasiloxane | Not Listed |
| Hexadecyltrimethoxysilane | Not Listed |
| Trimethoxy vinylsilane | Not Listed |
| 2-Butoxyethanol | I-3 |
| Crystalline Silica, Quartz | N-2, I-1, O-1, ACGIH-A2, CP65 |
| Dibutyltin Diacetate | Not Listed |

11.3. DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT AND LONG-TERM EXPOSURE

| SHORT-TERM | |
|--|--|
| Skin Corrosion/Irritation: | Causes skin irritation |
| Serious Eye Damage/Irritation: | Causes serious eye damage |
| Respiratory Sensitization: | Not Classified |
| Skin Sensitization: | May cause an allergic skin reaction |
| STOT-Single Exposure: | May cause respiratory irritation |
| Aspiration Hazard: | Not Classified |
| LONG-TERM | |
| Carcinogenicity: | May cause cancer |
| Germ Cell Mutagenicity: | Not Classified |
| Reproductive Toxicity: | May damage fertility or the unborn child (oral) |
| STOT-Repeated Exposure: | Causes damage to organs through prolonged or repeated exposure |
| Synergistic/Antagonistic Effects: | Not Classified |

Section 12: ECOLOGICAL INFORMATION

12.1. ECOTOXICITY

May cause long-term adverse effects to the aquatic environment. Keep from entry into sewers and waterways.

| Ecotoxicity | | |
|------------------------------|---------------------------|---------------------------------|
| Chemical Name | EC50/NOEC-48 Hours | LC50/NOEC-96 Hours |
| Calcium Carbonate | Not Available | Not Available |
| Portland Cement | Not Available | Not Available |
| Decamethylcyclopentasiloxane | Not Available | Not Available |
| Hexadecyltrimethoxysilane | Not Available | Not Available |
| Trimethoxy vinylsilane | 169 mg/L, Daphnia magna | 191 mg/L, Oncorhynchus mykiss |
| 2-Butoxyethanol | 1,550 mg/L, Daphnia magna | 1,474 mg/L, Oncorhynchus mykiss |
| Crystalline Silica, Quartz | Not Available | Not Available |
| Dibutyltin Diacetate | 35-127 mg/L, Algae | Not Available |

12.2. PERSISTENCE AND DEGRADABILITY

Not Available

12.3. BIOACCUMULATIVE POTENTIAL

SAFETY DATA SHEET

Not Available

12.4. MOBILITY IN SOIL
 Not Available

12.5. OTHER ADVERSE EFFECTS
 Not Available

Section 13: DISPOSAL CONSIDERATIONS

13.1. DISPOSAL METHOD
 Dispose of contents/containers in accordance with all local, state, provincial, and federal regulations

13.2. OTHER DISPOSAL CONSIDERATIONS
 Not Available

Section 14: TRANSPORT INFORMATION

| DOT (U.S.) | TDG (CANADA) | IATA |
|--|--|--|
| UN NUMBER: Not Regulated | UN NUMBER: Not Regulated | UN NUMBER: UN1993 |
| UN PROPER SHIPPING NAME: Not Regulated | UN PROPER SHIPPING NAME: Not Regulated | UN PROPER SHIPPING NAME: Flammable Liquid, n.o.s. (Trimethoxy vinylsilane, decamethylcyclopentasiloxane) |
| TRANSPORT HAZARD CLASS (ES): Not Regulated | TRANSPORT HAZARD CLASS (ES): Not Regulated | TRANSPORT HAZARD CLASS (ES): 3 |
| PACKING GROUP (if applicable): Not Regulated | PACKING GROUP (if applicable): Not Regulated | PACKING GROUP (if applicable): III |
| | | Limited Quantity Exception <= 5L |

SUMMARY: Product is NOT regulated under DOT/TDG transportation regulations. Product is regulated under IATA regulations.

14.1. ENVIRONMENTAL HAZARDS
 Not Available

14.2. TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE
 Not Available

14.3. SPECIAL PRECAUTIONS FOR USER
 Do not handle until all safety precautions have been read and understood.

SAFETY DATA SHEET

Section 15: REGULATORY INFORMATION

15.1. SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATIONS SPECIFIC FOR THE CHEMICAL


Canada: This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations and the SDS contains all the information required by the Hazardous Products Regulations.

US: SDS prepared pursuant to the Hazard Communication Standard (29 CFR 1910.1200) HazCom 2012

15.2. US FEDERAL INFORMATION:

| CHEMICAL NAME | SARA TITLE III | | | |
|------------------------------|-----------------------------|--------------------------|-----------------|-------------------|
| | SECTION 302 (EHS) TPQ (LBS) | SECTION 304 EHS RQ (LBS) | CERCLA RQ (LBS) | SECTION 313 (TRI) |
| Calcium Carbonate | Not Listed | Not Listed | Not Listed | Not Listed |
| Portland Cement | Not Listed | Not Listed | Not Listed | Not Listed |
| Decamethylcyclopentasiloxane | Not Listed | Not Listed | Not Listed | Not Listed |
| Hexadecyltrimethoxysilane | Not Listed | Not Listed | Not Listed | Not Listed |
| Trimethoxy vinylsilane | Not Listed | Not Listed | Not Listed | Not Listed |
| 2-butoxyethanol | Not Listed | Not Listed | 500 | Listed |
| Crystalline Silica, Quartz | Not Listed | Not Listed | Not Listed | Not Listed |
| Dibutyltin Diacetate | Not Listed | Not Listed | Not Listed | Not Listed |

15.3. US STATE RIGHT TO KNOW LAWS:

| | |
|---|---|
| California Proposition 65: |  WARNING: This product can expose you to chemicals including crystalline silica which is known to the State of California to cause cancer and methanol which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov . |
| Other U.S. States "Right to Know" Lists: | Calcium carbonate: CAS#1317-65-3 Portland Cement: CAS#65997-15-1 Decamethylcyclopentasiloxane: CAS#541-02-6 Hexadecyltrimethoxysilane: CAS#16415-12-6 Trimethoxy vinylsilane: CAS#2768-02-7 2-Butoxyethanol: CAS#111-76-2 Silica, quartz: CAS#14808-60-7 Methanol: CAS#67-56-1 |

15.4. GLOBAL INVENTORIES


| Chemical Name | USA TSCA | Canada DSL/NDSL |
|------------------------------|----------|-----------------|
| Calcium Carbonate | Yes | NDSL(*) |
| Portland Cement | Yes | DSL |
| Decamethylcyclopentasiloxane | Yes | DSL |
| Hexadecyltrimethoxysilane | Yes | DSL |
| Trimethoxy vinylsilane | Yes | DSL |
| 2-butoxyethanol | Yes | DSL |
| Crystalline Silica, Quartz | Yes | DSL |
| Dibutyltin Diacetate | Yes | DSL |

*Exemption: Natural occurring chemical












SAFETY DATA SHEET

15.5. NFPA AND HMIS RATINGS:

| | |
|--|--|
| HEALTH HAZARD 4 EXTREME - Highly toxic - May be fatal on short-term exposure. 3 SERIOUS - Toxic - Full protective suit and breathing apparatus should be worn. 2 MODERATE - Breathing apparatus and face mask must be worn. 1 SLIGHT - Breathing apparatus may be worn. 0 MINIMAL - No precautions necessary. | FLAMMABILITY HAZARD 4 EXTREME - Extremely flammable gas or liquid. Flash Point below 73°F. 3 SERIOUS - Flammable. Flash Point 73°F to 300°F. 2 MODERATE - Combustible. Requires moderate heating to ignite. Flash Point below 200°F. 1 SLIGHT - Slightly combustible. Requires strong heating to ignite. 0 MINIMAL - Will not burn under normal conditions. |
| SPECIFIC HAZARD OXIDIZER OX ACID AC ALKALI AL CORROSIVE CO Use NO WATER W RADIATION RA | INSTABILITY HAZARD 4 EXTREME - Explosive at room temperature. 3 SERIOUS - May detonate if shocked or heated under confinement or mixed with water. 2 MODERATE - Unstable. May react with water. 1 SLIGHT - May react if heated or mixed with water. 0 MINIMAL - Normally stable. Does not react with water. |



| Hazard Index | |
|--------------|------------------------|
| 4 | Severe Hazard |
| 3 | Serious Hazard |
| 2 | Moderate Hazard |
| 1 | Slight Hazard |

| | | |
|------------------------------|--|--|
| 2 HEALTH | PROTECTIVE EQUIPMENT INDEX | |
| 0 FLAMMABILITY | A  | G  |
| 0 REACTIVITY | B  | H  |
| G PERSONAL PROTECTION | C  | I  |
| | D  | J  |
| | E  | K  |
| | F  | X Ask your supervisor for special handling instructions. |

15.6. SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

| | |
|------------------|--|
| CP65 | California Proposition 65 |
| OSHA (O) | Occupational Safety and Health Administration |
| ACGIH (G) | American Conference of Governmental Industrial Hygienists <ul style="list-style-type: none"> • A1 – Confirmed human carcinogen • A2 – Suspected human carcinogen • A3 – Animal carcinogen • A4 – Not classifiable as a human carcinogen • A5 – Not suspected a human carcinogen |
| IARC (I) | International Agency for Research on Cancer <ul style="list-style-type: none"> • 1 – The agent (mixture) is carcinogenic to humans • 2A – The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient |

SAFETY DATA SHEET

| | |
|----------------|---|
| | evidence of carcinogenicity in experimental animals. <ul style="list-style-type: none"> • 2B – The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals. • 3 – The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans. • 4 – The agent (mixture, exposure circumstance) is probably not carcinogenic to humans. |
| NTP (N) | National Toxicology Program <ul style="list-style-type: none"> • 1 – Known to be carcinogens • 2 – Reasonably anticipated to be carcinogens |

Section 16: OTHER INFORMATION

Date of Preparation: July 19, 2016

Version: 1.1

Revision Date: August 1, 2018

Disclaimer: The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to silica contained in our products.

Prepared by: Custom Building Products
 Phone: (562)-968-2980
www.custombuildingproducts.com

End of Safety Data Sheet