

WOOD UR

NEW!

OCK
Images™

- Easy troweling results in faster installation times
- Excellent green grab for trouble-free installations
- Superior elasticity allows for natural expansion and contraction of wood
- Low odor formulation ideal for occupied environments



For over 50 years Custom Building Products has been an industry leader in flooring and tile and stone installation systems. Now, CUSTOM is proud to add Adhesive flooring products to our wide range of product offerings. From the brand you trust, we know flooring, Count on CUSTOM!

FOR USE WITH:

- Solid Wood
- Engineered Wood
- Bamboo
- Ceramic Tile
- Natural Stone Inlays
- Plywood Panels
- Underlayments



RH
80%



Working Time
60-90 Minutes



Heavy Traffic
24 Hours

TROWEL RECOMMENDATIONS



1/4" x 1/4" x 1/4" SQ
Wood Flooring > 5/8"
(16 mm) thick



1/4" x 1/8" x 1/4" SQ
Solid or Engineered Wood
1/2" - 5/8" (12.7-16 mm) Thick



3/16" x 5/32" V
Engineered Wood
Up to 1/2" (12.7 mm) Thick



CUSTOM®

WOOD UR

Ultimate Adhesive

WOOD UR is a professional grade, water free, urethane adhesive. This classic formulation has been developed to maximize bond strength and elasticity, while minimizing effort needed to trowel. All of this results in a reliable wood adhesive suited for any variety of small or large job.

Suitable as an adhesive:

- Solid Wood Plank
- Engineered Wood Plank
- Bamboo
- Ceramic Tile
- Natural Stone Inlays
- Plywood Panels [for nail down/double bond installations]
- Underlayments [Recycled rubber/cork]

Acceptable Substrate Conditions:

- RH – 80 % / ASTM F2170 Relative Humidity in Concrete Floor Slabs
- pH [Substrate] – up to 12
- Adhesive is suitable for MVER – up to 5 lbs. / per ASTM F1869 Moisture Vapor Emission Rate – See wood flooring manufacture for product limitations and requirements
- Contact Technical Services for test results/readings outside above conditions

Suitable Substrates:

- Flooring underlayment and Wood Manufacturer approved substrates
 - Cement-based self-leveling underlayment and patching compounds
 - Cement/epoxy terrazzo
 - Concrete (industry approved) – at least 14 days old with an appropriate moisture vapor barrier properly installed
 - Epoxy Coatings
 - Existing well bonded floor coverings
 - Plywood and other approved wood substrates
 - Properly prepared primed/sealed gypsum underlayment per ASTM F2419
 - Radiant heated floors (temperature should not exceed 85° F)
- * All surfaces / substrates above require proper surface preparation*

Applicable Standards:

- NWFA / National Wood Flooring Association – Wood Flooring Installation Guidelines
- ASTM F710 Standard Practice for Preparing Concrete Floors to Receive Resilient Flooring
- ASTM E96 Standard Test Methods for Water Vapor Transmission of Materials
- ASTM E492 Standard Test Method for Laboratory Measurement of Impact Sound Transmission
- ASTM E90 Standard Test Method for Laboratory Measurement of Airborne Sound Transmission Loss of Building Partitions and Elements
- ASTM E2179 Standard Test Method for Laboratory Measurement of the Effectiveness of Floor Coverings in Reducing Impact Sound Transmission Through Concrete Floors
- ICRI / International Concrete Institute
- ASTM F2419 Standard Practice of Thick Poured Gypsum Concrete Underlayments and Preparation of the Surface

Ordering Information

ITEM CODE	SIZE	PACKAGE
UAWAT5	5 gal (18.9 L)	Pail

Coverage




Wood Flooring > 5/8" thick	30 – 35 sq. ft./gallon	 1/4" x 1/4" x 1/4" SQ
Solid or Engineered Wood from 1/2" to 5/8" thick	40 – 50 sq. ft./gallon	 1/4" x 1/8" x 1/4" SQ
Engineered Wood from up to 1/2" thick	45 – 55 sq. ft./gallon	 3/16" x 5/32" V

Chart for estimating purposes. Coverage may vary based on installation practices and jobsite conditions. For more sizes, use the material calculator at CustomBuildingProducts.com or contact CUSTOM Technical Services at 800-282-8786.

Warranty:

- **2 Years** – Product only, unopened and properly stored.
- **15 Year System** – CUSTOM Adhesive and CustomTECH Floor Preparation Systems.
- **Warranty MATCH** – CUSTOM Adhesives & CustomTECH Floor Preparation. Products/Systems are warranted equal to the Flooring manufacturer's warranty term.

©2020 Custom Building Products. All rights reserved. The CUSTOM® logo and select product logos are registered trademarks of Custom Building Products, Inc. CUSTOM may make product modifications at any time without notice. Visit custombuildingproducts.com for updated technical data sheets and SDS information.

Custom Building Products
800-272-8786
custombuildingproducts.com/flooringadhesives

SS209 7/20N

