

REDGARD®. The ONE Name to Trust for Waterproofing and Crack Isolation.



RedGuard® Waterproofing and Crack Prevention Membrane

#1 selling and top performing liquid applied waterproofing and crack isolation membrane.*



RedGuard® SpeedCoat® Rapid Curing Waterproofing Membrane

Introducing a revolutionary formula that saves days, not hours on shower installations using cross-linking, moisture-cure technology.



RedGuard® Fabric Membrane

100% waterproof and vapor proof fabric membrane for fast and easy preparation for walls and floors.



RedGuard® Uncoupling Mat

The lightweight alternative to backerboard on floors for crack isolation. Waterproof, vaporproof, and made from 70% recycled content by weight.



Trust the proven RedGuard brand for waterproofing and crack prevention. Ask for it by name when you buy tile installation materials.

*Performance based on 2016 Intertek industry study. See details on the CUSTOM website.



CUSTOM®

TILE INSTALLATION SYSTEMS



RedGard® Waterproofing and Crack Prevention Membrane

RedGard as Crack Prevention Membrane:

SIZE	COVERAGE
1 gallon (3.78 L)	100 sq. ft. (9.3 M ²)
3.5 gallon (13.25 L)	350 sq. ft. (32.5 M ²)

RedGard as Crack Prevention Membrane Meeting ANSI A118.12:

SIZE	COVERAGE
1 gallon (3.78 L)	25 sq. ft. (2.3 M ²)
3.5 gallon (13.25 L)	88 sq. ft. (8.2 M ²)

RedGard as Waterproof Membrane:

SIZE	COVERAGE
1 gallon (3.78 L)	55 sq. ft. (5.1 M ²)
3.5 gallon (13.25 L)	192 sq. ft. (17.8 M ²)

RedGard as IAPMO Pan Liner Meeting ANSI A118.10:

SIZE	COVERAGE
1 gallon (3.78 L)	40 sq. ft. (3.7 M ²)
3.5 gallon (13.25 L)	140 sq. ft. (13 M ²)



RedGard® SpeedCoat® Rapid Curing Waterproofing Membrane

	IAPMO Shower Pan		General Waterproofing	
	COATS	COVERAGE	COATS	COVERAGE
Over CUSTOM SpeedSlope® Rapid Setting Sloping Mortar; or WonderBoard® Lite Backerboard and other smooth concrete	2	110 ft ² (10.2 m ²)	1	220 ft ² (20.4 m ²)
Over Portland Cement Mortar Beds	2	65 ft ² (6 m ²)	1	130 ft ² (12 m ²)

Average Curing Time Required for Full Waterproofing and Flood Testing:

(2 Coats Used For All Conditions)*

	RedGard® SpeedCoat®	Traditional Liquid Membrane
Cold/wet	4 hours	4 days
Cold/dry	8 hours	>1 day
Hot/wet	2 hours	>1 day
Hot/dry	2 hours	24 hours

*Times are approximate and can vary based on installation practices and jobsite conditions.



RedGard® Uncoupling Mat

Available Sizes:

RedGard Uncoupling Mat

SIZE
39" x 16' 5" (1 m x 5 m)
39" x 98' 5" (1 m x 30 m)

RedGard Seam Tape

SIZE
4.7" x 16' 5" (120 mm x 5 m) Roll
6" x 98' 5" (150 mm x 30 m) Roll



RedGard® Fabric Membrane

Available Size:

SIZE
323 sq ft (1m X 30m)

Charts are for estimating purposes. Coverage may vary based on installation practices and jobsite conditions. For more tile and joint sizes, use the material calculator at CustomBuildingProducts.com or contact CUSTOM Technical Services at 800-282-8786.



Select a qualifying system of Prep, Set and Grout products and CUSTOM will warranty the tile installation for life, including tile, materials and labor. See website for complete details.

©2021 Custom Building Products. All rights reserved. The CUSTOM® logo and select product logos are registered trademarks of Custom Building Products, Inc. CUSTOM may make product modifications at any time without notice. Visit custombuildingproducts.com for updated technical data sheets and SDS information.

Custom Building Products
800-272-8786
custombuildingproducts.com

SS178 7/21R

