

Ceramic Tile Caulk



1. Product Name

Ceramic Tile Caulk

2. Product Description

Our ceramic tile caulk is for caulking around sinks, tubs, showers and where tile meets tile or another surface. Also adheres bath fixtures and loose tile. Do not use to install grab bars. Maximum joint width and depth should not exceed 1/4" (6 mm). Do not use in areas with constant water exposure. For interior use only.

Key Features

- Use around tubs and sinks
- Use where horizontal and vertical surfaces meet
- Siliconized for ease of use
- Available in sanded and non-sanded versions to match grout texture -Mold and mildew resistant

Composition of Product

Siliconized acrylic latex resins with fine fillers and colored pigments

Benefits of Product in the Installation

- For caulking around sinks, tubs and showers
- Adheres bath fixtures and loose tile.
- For joint up to 1/4" (6mm) wide and deep
- For interior use.
- Available in sanded and non-sanded versions to match grout texture.
- Mold and mildew resistant

Limitations to the Product

- Do not use to install grab bars.
- Maximum joint width and depth should not exceed 1/4" (6 mm).
- Do not use in areas with constant water exposure

Packaging

10.5 oz (310 ml) cartridge

Technical Chart

| | |
|-----------------------------|------------|
| Tack-Free Time (ASTM C-679) | 30 Minutes |
| Paintable | >Yes |
| Slump | < 0.15 mm |
| Shrinkage | < 30% |
| Stain Resistance | Excellent |

| | |
|------------------|-----------|
| Crack Resistance | Excellent |
| pH | 7-9 |

3. Instructions

General Surface Prep

USE CHEMICAL-RESISTANT GLOVES, such as nitrile, when handling product.

Application of Product

Surfaces should be clean, dry and free of all contamination. Place cartridge in standard caulking gun. Cut tip off nozzle on a slant to desired opening size and completely fill joints with caulk. Smooth with wet finger. Clean off excess caulk with soap and water before it cures. Do not apply when temperature falls below 50°F (10°C).

Curing of Product

Minimum 24 hours before exposing to water. Cure time may be extended, depending on caulking thickness and ambient conditions.

Cleaning of Equipment

Clean tools with water before material dries.

Storage

Replace cap after each use. Store away from extreme heat or cold. Keep from freezing.

Health Precautions

Contains Petroleum Distillates. If ingested, do not induce vomiting, call a physician immediately. Use with adequate ventilation. Nonflammable. KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY. AVOID EYE CONTACT.

4. Size & Availability

Sanded

| Location | Color # | Color | Item Code | Size | Package |
|----------|---------|---------------|------------|-----------------------------|---------|
| USA | #9 | Natural Gray | PC0910S-6 | 10.5 oz. (310 Cartridge ml) | |
| USA | #11 | Snow White | PC1110S-6 | 10.5 oz. (310 Cartridge ml) | |
| USA | #19 | Pewter | PC1910S-6 | 10.5 oz. (310 Cartridge ml) | |
| USA | #60 | Charcoal | PC6010S-6 | 10.5 oz. (310 Cartridge ml) | |
| USA | #115 | Platinum | PC11510S-6 | 10.5 oz. (310 Cartridge ml) | |
| USA | #122 | Linen | PC12210S-6 | 10.5 oz. (310 Cartridge ml) | |
| USA | #165 | Delorean Gray | PC16510S-6 | 10.5 oz. (310 Cartridge ml) | |
| USA | #380 | Haystack | PC38010S-6 | 10.5 oz. (310 Cartridge ml) | |
| USA | #381 | Bright White | PC38110S-6 | 10.5 oz. (310 Cartridge ml) | |
| USA | #382 | Bone | PC38210S-6 | 10.5 oz. (310 Cartridge ml) | |
| USA | #386 | Oyster Gray | PC38610S-6 | 10.5 oz. (310 Cartridge ml) | |
| USA | #544 | Rolling Fog | PC54410S-6 | 10.5 oz. (310 Cartridge ml) | |
| USA | #640 | Arctic White | PC64010S-6 | 10.5 oz. (310 Cartridge ml) | |
| USA | #646 | Coffee Bean | PC64610S-6 | 10.5 oz. (310 Cartridge ml) | |
| USA | #647 | Brown Velvet | PC64710S-6 | 10.5 oz. (310 Cartridge ml) | |
| Canada | #9 | Natural Gray | CPC0910S-6 | 10.5 oz. (310 Cartridge ml) | |

Ceramic Tile Caulk

| | | | | |
|--------|------|---------------|-------------|-----------------------------|
| Canada | #10 | Antique White | CPC1010S-6 | 10.5 oz. (310 Cartridge ml) |
| Canada | #11 | Snow White | CPC1110S-6 | 10.5 oz. (310 Cartridge ml) |
| Canada | #19 | Pewter | CPC1910S-6 | 10.5 oz. (310 Cartridge ml) |
| Canada | #52 | Tobacco Brown | CPC5210S-6 | 10.5 oz. (310 Cartridge ml) |
| Canada | #60 | Charcoal | CPC6010S-6 | 10.5 oz. (310 Cartridge ml) |
| Canada | #105 | Earth | CPC10510S-6 | 10.5 oz. (310 Cartridge ml) |
| Canada | #122 | Linen | CPC12210S-6 | 10.5 oz. (310 Cartridge ml) |
| Canada | #145 | Light Smoke | CPC14510S-6 | 10.5 oz. (310 Cartridge ml) |
| Canada | #165 | Delorean Gray | CPC16510S-6 | 10.5 oz. (310 Cartridge ml) |
| Canada | #380 | Haystack | CPC38010S-6 | 10.5 oz. (310 Cartridge ml) |
| Canada | #381 | Bright White | CPC38110S-6 | 10.5 oz. (310 Cartridge ml) |
| Canada | #382 | Bone | CPC38210S-6 | 10.5 oz. (310 Cartridge ml) |

Related Products

Polyblend® Plus Sanded Grout
Prism® Ultimate Performance Grout

Non-Sanded

| Location | Color # | Color | Item Code | Size | Package |
|----------|---------|---------------|-------------|-------------------|-----------|
| USA | #10 | Antique White | PC1010N-6 | 10.5 oz. (310 ml) | Cartridge |
| USA | #11 | Snow White | PC1110N-6 | 10.5 oz. (310 ml) | Cartridge |
| USA | #122 | Linen | PC12210N-6 | 10.5 oz. (310 ml) | Cartridge |
| USA | #165 | Delorean Gray | PC16510N-6 | 10.5 oz. (310 ml) | Cartridge |
| USA | #381 | Bright White | PC38110N-6 | 10.5 oz. (310 ml) | Cartridge |
| Canada | #10 | Antique White | CPC1010N-6 | 10.5 oz. (310 ml) | Cartridge |
| Canada | #11 | Snow White | CPC1110N-6 | 10.5 oz. (310 ml) | Cartridge |
| Canada | #122 | Linen | CPC12210N-6 | 10.5 oz. (310 ml) | Cartridge |
| Canada | #165 | Delorean Gray | CPC16510N-6 | 10.5 oz. (310 ml) | Cartridge |
| Canada | #381 | Bright White | CPC38110N-6 | 10.5 oz. (310 ml) | Cartridge |

Additional colors may be available in select markets.

See our color card for truest color representation when selecting or specifying a grout color. Final installed shade may vary with the tile type, color and porosity as well as jobsite conditions and finishing techniques. For best results, perform a test on a small, inconspicuous area or create a sample board prior to installation.

5. Product Maintenance

Properly installed product requires no special maintenance. Routine cleaning should be done with neutral cleaners. **Maintenance** Clean with a neutral cleaner such as Aquamix AquaKleen or Tilelab Grout & Tile Cleaner

6. Technical Services Information

For technical assistance, contact Custom® Building Products.

7. Filing System

Additional product information is available from the manufacturer upon request.

Ceramic Tile Caulk

Coverage Chart