

Ceramic Tile Caulk



1. Product Name

Ceramic Tile Caulk

2. Product Description

Our ceramic tile caulk is for caulking around sinks, tubs, showers and where tile meets tile or another surface. Also adheres bath fixtures and loose tile. Do not use to install grab bars. Maximum joint width and depth should not exceed 1/4" (6 mm). Do not use in areas with constant water exposure. For interior use only.

Key Features

- Use around tubs and sinks
- Use where horizontal and vertical surfaces meet
- Siliconized for ease of use
- Available in sanded and non-sanded versions to match grout texture -Mold and mildew resistant

Composition of Product

Siliconized acrylic latex resins with fine fillers and colored pigments

Benefits of Product in the Installation

- For caulking around sinks, tubs and showers
- Adheres bath fixtures and loose tile.
- For joint up to 1/4" (6mm) wide and deep
- For interior use.
- Available in sanded and non-sanded versions to match grout texture.
- Mold and mildew resistant

Limitations to the Product

- Do not use to install grab bars.
- Maximum joint width and depth should not exceed 1/4" (6 mm).
- Do not use in areas with constant water exposure

Packaging

10.5 oz (310 ml) cartridge

Technical Chart

Tack-Free Time (ASTM C-679)	30 Minutes
Paintable	>Yes
Slump	< 0.15 mm
Shrinkage	< 30%
Stain Resistance	Excellent

Crack Resistance
pH

Excellent
7-9

3. Instructions

General Surface Prep

USE CHEMICAL-RESISTANT GLOVES, such as nitrile, when handling product.

Application of Product

Surfaces should be clean, dry and free of all contamination. Place cartridge in standard caulking gun. Cut tip off nozzle on a slant to desired opening size and completely fill joints with caulk. Smooth with wet finger. Clean off excess caulk with soap and water before it cures. Do not apply when temperature falls below 50°F (10°C).

Curing of Product

Minimum 24 hours before exposing to water. Cure time may be extended, depending on caulking thickness and ambient conditions.

Cleaning of Equipment

Clean tools with water before material dries.

Storage

Replace cap after each use. Store away from extreme heat or cold. Keep from freezing.

Health Precautions

Contains Petroleum Distillates. If ingested, do not induce vomiting, call a physician immediately. Use with adequate ventilation. Nonflammable. KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY. AVOID EYE CONTACT.

4. Size & Availability

Sanded

Location	Color #	Color	Item Code	Size	Package
USA	#9	Natural Gray	PC0910S-6	10.5 oz. (310 Cartridge ml)	
USA	#11	Snow White	PC1110S-6	10.5 oz. (310 Cartridge ml)	
USA	#19	Pewter	PC1910S-6	10.5 oz. (310 Cartridge ml)	
USA	#60	Charcoal	PC6010S-6	10.5 oz. (310 Cartridge ml)	
USA	#115	Platinum	PC11510S-6	10.5 oz. (310 Cartridge ml)	
USA	#122	Linen	PC12210S-6	10.5 oz. (310 Cartridge ml)	
USA	#165	Delorean Gray	PC16510S-6	10.5 oz. (310 Cartridge ml)	
USA	#380	Haystack	PC38010S-6	10.5 oz. (310 Cartridge ml)	
USA	#381	Bright White	PC38110S-6	10.5 oz. (310 Cartridge ml)	
USA	#382	Bone	PC38210S-6	10.5 oz. (310 Cartridge ml)	
USA	#386	Oyster Gray	PC38610S-6	10.5 oz. (310 Cartridge ml)	
USA	#544	Rolling Fog	PC54410S-6	10.5 oz. (310 Cartridge ml)	
USA	#640	Arctic White	PC64010S-6	10.5 oz. (310 Cartridge ml)	
USA	#646	Coffee Bean	PC64610S-6	10.5 oz. (310 Cartridge ml)	
USA	#647	Brown Velvet	PC64710S-6	10.5 oz. (310 Cartridge ml)	
Canada	#9	Natural Gray	CPC0910S-6	10.5 oz. (310 Cartridge ml)	

Ceramic Tile Caulk

Canada	#10	Antique White	CPC1010S-6	10.5 oz. (310 Cartridge ml)
Canada	#11	Snow White	CPC1110S-6	10.5 oz. (310 Cartridge ml)
Canada	#19	Pewter	CPC1910S-6	10.5 oz. (310 Cartridge ml)
Canada	#52	Tobacco Brown	CPC5210S-6	10.5 oz. (310 Cartridge ml)
Canada	#60	Charcoal	CPC6010S-6	10.5 oz. (310 Cartridge ml)
Canada	#105	Earth	CPC10510S-6	10.5 oz. (310 Cartridge ml)
Canada	#122	Linen	CPC12210S-6	10.5 oz. (310 Cartridge ml)
Canada	#145	Light Smoke	CPC14510S-6	10.5 oz. (310 Cartridge ml)
Canada	#165	Delorean Gray	CPC16510S-6	10.5 oz. (310 Cartridge ml)
Canada	#380	Haystack	CPC38010S-6	10.5 oz. (310 Cartridge ml)
Canada	#381	Bright White	CPC38110S-6	10.5 oz. (310 Cartridge ml)
Canada	#382	Bone	CPC38210S-6	10.5 oz. (310 Cartridge ml)

Related Products

Polyblend® Plus Sanded Grout
Prism® Ultimate Performance Grout

Non-Sanded

Location	Color #	Color	Item Code	Size	Package
USA	#10	Antique White	PC1010N-6	10.5 oz. (310 ml)	Cartridge
USA	#11	Snow White	PC1110N-6	10.5 oz. (310 ml)	Cartridge
USA	#122	Linen	PC12210N-6	10.5 oz. (310 ml)	Cartridge
USA	#165	Delorean Gray	PC16510N-6	10.5 oz. (310 ml)	Cartridge
USA	#381	Bright White	PC38110N-6	10.5 oz. (310 ml)	Cartridge
Canada	#10	Antique White	CPC1010N-6	10.5 oz. (310 ml)	Cartridge
Canada	#11	Snow White	CPC1110N-6	10.5 oz. (310 ml)	Cartridge
Canada	#122	Linen	CPC12210N-6	10.5 oz. (310 ml)	Cartridge
Canada	#165	Delorean Gray	CPC16510N-6	10.5 oz. (310 ml)	Cartridge
Canada	#381	Bright White	CPC38110N-6	10.5 oz. (310 ml)	Cartridge

Additional colors may be available in select markets.

See our color card for truest color representation when selecting or specifying a grout color. Final installed shade may vary with the tile type, color and porosity as well as jobsite conditions and finishing techniques. For best results, perform a test on a small, inconspicuous area or create a sample board prior to installation.

5. Product Maintenance

Properly installed product requires no special maintenance. Routine cleaning should be done with neutral cleaners. **Maintenance** Clean with a neutral cleaner such as Aquamix AquaKleen or Tilelab Grout & Tile Cleaner

6. Technical Services Information

For technical assistance, contact Custom® Building Products.

7. Filing System

Additional product information is available from the manufacturer upon request.

Ceramic Tile Caulk

Coverage Chart