

TileLab® Grout Sealer (Aerosol)



1. Product Name

TileLab® Grout Sealer (Aerosol)

2. Product Description

TileLab® Grout Sealer is a ready-to-use, water-based, penetrating sealer that resists most common oil and water-based stains. With a 360 nozzle, it is a quick and easy way to apply a sealer to sanded or non-sanded grout while in a standing position. The steady stream from the nozzle and the foaming action of the sealer makes it easy to aim and seal. Grout Sealer makes cleaning easier.

USES

Protects sanded and non-sanded grout joints from grease, coffee, wine, cooking oil, bath oils, colored juices, ketchup, mustard and every-day dust and dirt to keep grout bright and new.

Key Features

- Penetrates to protect grout against stains

Packaging

15 oz. (425 gm) Aerosol Can

Technical Chart

- Stain resistant to most household contaminants (CTI-072)
- Does not darken grout
- Complies with all Federal and SCAQMD Standards for VOCs

3. Instructions

General Surface Prep

Surface should be dry, clean and free of waxes, sealers or finishes. TileLab® Heavy-Duty Stripper & Cleaner or Aqua Mix® Heavy-Duty Tile & Grout Cleaner will clean the surface or strip wax and acrylic finishes. New installations need to be cured 48 - 72 hours before application. Protect painted surfaces. Test product in obscure area to ensure desirable results. Sealer can be applied 48 hours after grout has been installed.

Application of Product

USE CHEMICAL-RESISTANT GLOVES, such as nitrile, when handling product.

SHAKE CAN WELL. Hold aerosol container in an upright or inverted position pointing away from the applicator while spraying. Keep spray tip 18" to 24" (45 to 60 cm) from surface while applying sealer.

Cleaning of Equipment

If excessive sealer is applied, wipe tile or stone surface with a cloth. Protect painted and surrounding areas from overspray.

Health Precautions

MAY BE HARMFUL. Do not breathe fumes. Wear a vapor mask or NIOSH compliant respirator. Do not swallow. Do not get in eyes, or on skin or clothing. Wear rubber gloves and safety glasses. Keep out of reach of children. Remove children and pets from area during application. If dizziness occurs during application, move to fresh air and ventilate applied room. **FIRST AID TREATMENT:** If swallowed, do not induce vomiting. Get medical attention or contact a poison control center immediately. If eye contact occurs, flush immediately with plenty of water for 15 minutes. If contact with sensitive skin occurs, wash with soap and water. Call physician if necessary. **CONTENTS UNDER PRESSURE. CONTAINER MAY EXPLODE IF HEATED.** Do not puncture. Do not burn. Store away from heat.

4. Size & Availability

Location	Item Code	Size	Package
USA	TLASGSRA15Z	15 oz. (425 gm)	12 pack case

5. Product Warranty

Custom® Building Products warrants to the original consumer purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom's® sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom's® printed instructions. Custom® makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country or territory to another. For details and complete warranty information, visit [/reference-library/warranties.aspx](#)

6. Product Maintenance

Properly installed product requires no special maintenance.

7. Technical Services Information

For technical assistance contact Custom® Building Products.

8. Filing System

Additional product information is available from the manufacturer upon request.

TileLab® Grout Sealer (Aerosol)

Coverage Chart