

TileLab® Stone Sealer & Enhancer



1. Product Name

TileLab® Stone Sealer & Enhancer

2. Product Description

Color enhancer and penetrating sealer for all types of porous natural stone and grout. Rejuvenates the color and appearance of worn, faded stone, tumbled-marble and other rustic-look stones. Can also be used to darken the color of grout. Provides long-lasting protection against oil, grease and stains. Its water-based, low-odor formula can be used for interior and exterior use.

Key Features

- Seals for stain protection and enhances the look

Uses

- Unsealed natural stone such as marble, granite, slate, limestone, travertine, quartzite, and sandstone
- Effective for interior and exterior applications

Benefits of Product in the Installation

- Excellent stain resistance to most household contaminants (CTI-072)
- Darkens most stone to a "wet look"
- Complies with all Federal and SCAQMD Standards for VOCs

Packaging

24 fl. oz. (709 ml) Spray Bottle

3. Instructions

General Surface Prep

Surface should be dry, clean and free of waxes, sealers, or finishes. Do not apply directly over silicone sealers, oil or wax based finishes. TileLab® Heavy-Duty Stripper & Cleaner will clean the surface and remove wax or old acrylic finishes. Place a few drops of water on various tiles. If water doesn't penetrate, additional removal is necessary. Gloss Sealer & Finish can be applied over any TileLab® sealer except Stone Sealer & Enhancer. New installations need to be cured at least 48 hours before application. Clay and Saltillo tile may require extended drying time depending on temperature and humidity. Make sure the tiles are completely dry before application. Test product in obscure area to ensure desirable results.

Application of Product

USE CHEMICAL-RESISTANT GLOVES, such as nitrile, when

handling product.

Apply liberally using a new mop, paint pad or sponge. Allow to penetrate for up to 5 minutes. Immediately wipe off any sealer completely before it dries. Immediately apply a second coat. Ensure no residue is left to dry on the surface. Do not use outside if inclement weather is expected within 24 hours. Clean off any residue left on the surface with an appropriate TileLab® cleaner. Note: The more porous the stone, the deeper the color enhancement.

Cleaning of Equipment

Clean tools and hands with soap and water immediately after use.

Health Precautions

MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear skin and eye protection. Contains ethylene glycol, dibutyl phthalate, dipropylene glycol methyl ether and acrylic polymer. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting, seek medical attention. KEEP OUT OF REACH OF CHILDREN.

4. Size & Availability

Location	Item Code	Size	Package
USA	TLSES24Z	24 fl. oz. (709 ml)	Spray Bottle
Canada	CSSSESQT-3-3	1 qt (946 ml)	Bottle

5. Product Warranty

Custom® Building Products warrants to the original purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom's® sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom's® printed instructions. Custom® makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country or territory to another. For details and complete warranty information, visit [/reference-library/warranties.aspx](#)

6. Product Maintenance

Use an appropriate TileLab® or StoneSpecific® cleaner for routine cleaning. Reapply Matte Sealer & Finish to clean, dry surface when needed depending on use and surface traffic.

7. Technical Services Information

For technical assistance, contact Custom® Building Products.

8. Filing System

Additional product information is available from the manufacturer upon request.

TileLab® Stone Sealer & Enhancer

Coverage Chart