StoneSpecific® Polished Marble, Travertine & Limestone Sealer



1. **Product Name**

   StoneSpecific® Polished Marble, Travertine & Limestone Sealer

2. **Product Description**

   Optimum protection on medium-density polished stone – marble, travertine and limestone. Designed to penetrate and seal the polished stone surfaces to provide optimal protection, keeping your natural stone clean, vibrant and new. StoneSpecific® Low VOC (Volatile Organic Compound) formulas help provide better indoor and outdoor air quality compared to similar traditional products. Complies with EPA and CARB VOC Requirements.

   Key Features

   - Premium water-based formula
   - Low odor and pH neutral
   - Interior and Exterior Use
   - For commercial or residential applications
   - Allows moisture vapor transmission
   - Also protects sanded or non-sanded grout

   Benefits of Product in the Installation

   When optimum protection is required for polished natural stone. Protects fabricated or tiled stone surfaces covering kitchens, baths, walls or floor surfaces.

   Packaging

   1 quart (946 ml) bottle

   Technical Chart

   - Excellent stain resistance to most household contaminants (CTI-072)
   - No darkening of stone

3. **Instructions**

   General Surface Prep

   Surface should be dry, clean and free of waxes, sealers or finishes. TileLab® Heavy-Duty Cleaner & Stripper will clean the surface or strip wax and acrylic finishes. New installations: Allow grout to cure 48 hours before applying sealer.

   Application of Product

   WEAR IMPERVIOUS GLOVES, such as nitrile, and eye protection when handling product.

   Test product in obscure area to ensure desirable results. Apply liberally using a new mop, lambswool applicator or sponge. Maintain a thin, even coat to cover surface, working-in sealer for 5 - 10 minutes. Surface must stay wet letting sealer soak for additional 10 minutes, allowing for maximum penetration. Immediately after, wipe off any sealer completely before it dries. If initial coat has been absorbed, apply additional coat 15 minutes after first application.

   Cleaning of Equipment

   Clean tools and hands with soap and water immediately after use.

   Health Precautions

   CAUTION: MAY IRRITATE EYES. MAY IRRITATE SKIN. MAY CAUSE RESPIRATORY IRRITATION. Do not mix with other chemical products. Do not get on skin or clothing. Do not get in eyes. Do not breathe fumes. Do not swallow. **KEEP OUT OF REACH OF CHILDREN.** Use onlye in a well-ventilated area. Wear chemical resistant gloves, CSA approved respirator, and eye protection. **FIRST AID TREATMENT:** Contains: Fluoropolymer, quarternary amine compound and d-Limonene. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water. If breathed in, move person into fresh air. In emergency, call (800) 535-5053.

4. **Size & Availability**

Item Code	Size	Location	Package
CSSPMSQT-3	1 qt (946 ml)	Canada	Bottle

5. **Product Warranty**

   Custom® Building Products warrants to the original consumer purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom's sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom's printed instructions. Custom makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country/territory to another.

6. **Product Maintenance**

   Do not use cleaners containing ammonia, acids or bleach; use StoneSpecific Marble, Travertine, Limestone & Slate

StoneSpecific® Polished Marble, Travertine & Limestone Sealer

Cleaner/Resealer. Tile industry experts recommend testing sealed surfaces every two years. Apply a few drops of water on the surface. If it soaks in, a coat of StoneSpecific Polished Marble, Travertine & Limestone Sealer will be necessary to keep protection at peak performance.

7. Technical Services Information

For technical assistance, contact Custom Building Products or visit custombuildingproducts.com.

8. Filing System

Additional product information is available from the manufacturer upon request.

Coverage Chart