

Aqua Mix® Pro-Solv®



1. Product Name

Aqua Mix® Pro-Solv®

2. Manufacturer

Custom Building Products
Technical Services
10400 Pioneer Boulevard, Unit 3
Santa Fe Springs, CA 90670
Customer Support: 800-272-8786
Technical Services: 800-282-8786
Fax: 800- 200-7765
Email: contactus@cbpmail.net
custombuildingproducts.com

3. Product Description

An economical, no-sheen, natural look, solvent-based, penetrating sealer formulated to resist stains on porous stone and tile. May also be used as a pre-grouting sealer. Allows moisture vapor transmission. It is also a good grout sealer.

Key Features

- Excellent stain protection
- No-sheen natural look
- Safe solvent-based formula

Limitations to the Product

- Do not allow product to come in contact with any non-recommended surface
- May slightly lighten or darken some stone surfaces
- Sealer will not prevent surface wear or etching from acids or caustic chemicals

Technical Chart

Property	Test Method	Typical Results
Stain Resistance	CTI-072	Good
pH		n/a
Darken Stone		No
Cure Time		24 Hours
Expected Wear		Up to 10 Years

Environmental Consideration

Complies with all Federal EPA and SCAQMD standards for VOC

4. Instructions

General Surface Prep

Surface should be dry, clean and free of waxes, sealers or finishes. New installations need to dry 48 hours before application. Protect surrounding surfaces. Test product in an inconspicuous area to ensure desirable results.

Application of Product

USE CHEMICAL-RESISTANT GLOVES, such as nitrile, when handling product.

Read entire label before using. Apply using a cotton mop, paint pad applicator, roller or brush. Allow it to penetrate for up to 5 minutes. Wipe surface completely dry using clean, dry cotton or paper towels after each application. Porous surfaces may require additional applications. Conduct a test to see if surface is completely sealed after 2 hours by applying drops of water on the surface. If it penetrates, an additional application is necessary.

Cleaning of Equipment

Clean tools with mineral spirits immediately after use.

Health Precautions

COMBUSTIBLE. MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Keep away from heat and sources of ignition. Wear skin and eye protection. Do not breathe vapor or spray. Contains petroleum distillates, methyl alcohol, dibutyltin dilaurate, and 3-aminopropyltriethoxysilane. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If respiratory tract is irritated, remove to fresh air. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting. Seek medical attention.

5. Size & Availability

Location	Item Code	Size	Package
USA	100057	1 Pt. (473 ml)	Bottle
USA	100058-4	1 Qt. (946 ml)	Bottle
USA	100059	1 Gal. (3.8 L)	Bottle
USA	100060*	5 Gal. (19 L)	Pail

* Indicates a special order item

6. Product Warranty

Custom® Building Products warrants to the original purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom's® sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom's® printed instructions. Custom® makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country or territory to another. For details and complete warranty information, visit [/reference-library/warranties.aspx](http://reference-library/warranties.aspx)

Aqua Mix® Pro-Solv®

7. Product Maintenance

Aqua Mix® Concentrated Stone & Tile Cleaner, AquaKleen® is recommended for routine spray and wipe cleaning and resealing.

8. Technical Services Information

For technical assistance contact Custom® Building Products.

9. Filing System

Additional product information is available from the manufacturer upon request.
