Aqua Mix® SameDay™ Grout Sealer



1. **Product Name**
   Aqua Mix® SameDay™ Grout Sealer

2. **Manufacturer**
   Custom Building Products
   Technical Services
   10400 Pioneer Boulevard, Unit 3
   Santa Fe Springs, CA 90670
   Customer Support: 800-272-8786
   Technical Services: 800-282-8786
   Fax: 800- 200-7765
   Email: contactus@cbpmail.net
   custombuildingproducts.com

3. **Product Description**

   A no-sheen, natural look, water-based, nonflammable, aerosol sealer with a 360 nozzle specially formulated for grout. This innovative spray is a quick and easy way to apply a grout sealer. SameDay Grout Sealer can be applied as soon as 2 hours after grouting, making sealing an efficient, economical process. The easy-to-spray nozzle places more sealer on the grout.

   Key Features

   - Easy aerosol application
   - No-sheen natural look
   - Safe, nonflammable formula

   Limitations to the Product

   - Do not allow sealer to come in contact with any non-recommended surface
   - Sealer will not prevent surface wear or etching from acids

   Environmental Consideration
   Complies with all Federal EPA and SCAQMD standards for VOC

4. **Instructions**
   General Surface Prep
   Surface should be dry, clean and free of waxes, sealers or finishes. TileLab® Heavy-Duty Stripper & Cleaner or Aqua Mix® Heavy-Duty Tile & Grout Cleaner will clean the surface or strip wax and acrylic finishes. Protect surrounding surfaces. Test product in an inconspicuous area to ensure desirable results.

   Application of Product
   USE CHEMICAL-RESISTANT GLOVES, such as nitrile, when handling product.

   Read entire label before using. Protect all surrounding surfaces. SHAKE WELL before using. For new installations, sealer can be applied as soon as 2 hours after grouting. Grout joints must be clean, dry, and free of existing sealers or coatings. Invert can and point nozzle toward the grout, keeping nozzle 18"-24" (45 cm to 60 cm) from the surface. Press nozzle forward and spray along grout lines. NOTE: Be sure to completely wipe surface DRY within 5 minutes of each application using dry paper, cotton or microfiber towels. If 2 or more coats are applied, allow a minimum of 30 minutes drying time between coats. Be careful not to directly rub fresh grout if sealer is applied same day as grout. After 2 hours conduct a test to determine if surface is completely sealed by applying water droplets to the surface. If water is absorbed, apply an additional coat. Wait 3 hours and repeat the test. Ready for surface traffic 2 hours after final coat. Keep area dry for 24 hours after application. May be reapplied as needed to grout joints that are clean and dry.

   Cleaning of Equipment
   Clean tools with mineral spirits immediately after use.

   Health Precautions
   MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear skin and eye protection. Do not breathe vapor or spray. Contains octyl triethoxy silane. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If respiratory tract is irritated, remove to fresh air. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting. Seek medical attention.

5. **Size & Availability**

Location	Item Code	Size	Package
USA	100557	15 Oz. (444 ml)	Aerosol
Canada	C100557	15 Oz. (444 ml)	Aerosol

6. **Product Warranty**
   Custom® Building Products warrants to the original purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom's® sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom's® printed instructions. Custom® makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country or territory to another. For details and complete warranty information, visit /reference-library/warranties.aspx

7. **Product Maintenance**
   Aqua Mix® Concentrated Stone & Tile Cleaner, AquaKleen® or AquaShield® Cleaner & Resealer is recommended for routine spray and wipe cleaning and resealing.

CUSTOM® A QUIKRETE® COMPANY

Aqua Mix® SameDay™ Grout Sealer

8. Technical Services Information

For technical assistance contact Custom® Building Products.

9. Filing System

Additional product information is available from the manufacturer upon request.