

Aqua Mix® Non-Cement Grout Haze Remover



Grout Type	Time Grout has Cured		
	24 hrs	4-7 days	28+ days
Single Component, Premixed and Urethane	5-10 sec	1 min	3-5 min
Light Epoxy Haze	2-3 min	5 min	n/a

1. Product Name

Aqua Mix® Non-Cement Grout Haze Remover

2. Product Description

AQUA MIX NON-CEMENT GROUT HAZE REMOVER is a safe cleaner that effectively removes Single Component®, premixed, urethane, and light epoxy grout haze from the face of most common tile and natural stone products.

Key Features

- Removes single component, urethane and light epoxy grout haze
- Non-acidic formula

Limitations to the Product

- Do not allow cleaner to come in contact with any non-recommended surface
- Do not use excessive amounts of water during cleanup process as grout pigment may be washed out.
- Avoid scrubbing directly on the grout joints.
- For moderate-heavy epoxy grout haze or any epoxy grout haze cured for more than 7 days, use Aqua Mix Sealer & Coating Remover

Technical Chart

Property	Test Method	Requirement	Typical Results
	pH	n/a	11-12 (alkaline)

- Complies with all federal EPA and SCAQMD standards for VOC

Application of Product

USE CHEMICAL-RESISTANT GLOVES, such as nitrile, when handling product.

DO NOT KNEEL IN THIS PRODUCT. AVOID ALL SKIN CONTACT.

Read entire label before using.
Put on rubber gloves and eye protection

- Grout installations should be cured overnight at a minimum and be clean
- Sweep, vacuum, or wipe surface
- Apply solution to surface and allow to dwell for the time indicated below:

- After dwell time, agitate with a white nylon scrub brush or scrub pad.
- Clean up dirty solution. Do not allow solution to dry on surface.
- Rinse with clean water

Cleaning of Equipment

Clean tools with soap and water

Storage

- Close container tightly after each use
- Store in original container only
- Store in and use in temperatures between 45° F to 85° F (7° C to 29° C)
- Store in areas inaccessible to small children
- Do not reuse empty container, wrap and discard in trash or recycle

Health Precautions

CORROSIVE. CAUSES BURNS. HARMFUL IF SWALLOWED. Wear skin and eye protection. Do not breathe vapor or spray. Contains sodium hydroxide and ethylene glycol monobutyl ether. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If respiratory tract is irritated, remove to fresh air. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting. Seek medical attention.

3. Size & Availability

Location	Item Code	Size	Package
USA	010900-4	1 qt (946 ml)	Bottle
USA	010901	1 gallon (3.8 L)	Bottle
USA	010384*	5 gallon (19 L)	Pail

* Indicates a special order item

4. Product Warranty

Custom® Building Products warrants to the original consumer purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom's® sole liability under this warranty shall be limited to the replacement of the

Aqua Mix® Non-Cement Grout Haze Remover

product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom's® printed instructions. Custom® makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country/territory to another. This warranty is not transferrable.

5. Product Maintenance

Properly applied product requires no special maintenance.

6. Technical Services Information

For technical assistance, contact Custom technical services at 800-282- 8786 or visit custombuildingproducts.com.

7. Filing System

Additional product information is available from the manufacturer upon request.
