

Aqua Mix® Ex-Treme®



1. Product Name

Aqua Mix® Ex-Treme®

2. Manufacturer

Custom Building Products
Technical Services
10400 Pioneer Boulevard, Unit 3
Santa Fe Springs, CA 90670
Customer Support: 800-272-8786
Technical Services: 800-282-8786
Fax: 800-200-7765
Email: contactus@cbpmail.net
custombuildingproducts.com

3. Product Description

A nonflammable, heavy-viscosity acidic cleaner designed to remove years of accumulated discoloration from air pollution or carbon buildup, stains from smoke, soot, red soil and rust. It is a safer alternative to traditional harsh acids.

Key Features

- Removes mineral deposits, rust stains and red dirt stains
- Safer alternative to traditional harsh acids
- Removes hydrocarbon, smoke and soot stains

Uses

Unpolished natural stone, concrete pavers, masonry surfaces, ceramic, porcelain, grout, quarry, saltillo, terra-cotta, and other acid resistant tile and stone.

Limitations to the Product

- Do not use on polished, acid-sensitive stone (such as marble and limestone)
- Do not allow product to come in contact with any non-recommended surface
- Do not mix with ammoniated cleaners, such as bleach, as harmful fumes will result
- Acids of all kinds may etch, lighten, or change the color of cementitious material, metallic glazes and some natural stones such as marble and limestone

Technical Chart

- pH 2-3
- Complies with all Federal EPA and SCAQMD standards for VOC

4. Instructions

General Surface Prep

Test a small area according to application instructions to determine desired results.

Application of Product

USE CHEMICAL-RESISTANT GLOVES, such as nitrile, when handling product.

Read entire label before using. Remove loose debris. Pre-wet the surface with water and remove excess before applying solution. Mix Ex-Treme® as follows:

LIGHT BUILDUP: Mix 1 part cleaner to 4 parts water.

MODERATE BUILDUP: Mix 1 part cleaner to 2 parts water.

HEAVY BUILDUP: Use undiluted.

Liberally apply solution with paint roller, brush or sponge. Allow to dwell up to 30 minutes. DO NOT ALLOW SOLUTION TO DRY ON SURFACE. Apply additional solution if drying occurs. Agitate with scrub brush thoroughly rinse with clean water. For vertical surfaces a garden hose or high-pressure washer may be used to rinse area. Mop or wet vacuum dirty solution. Heavy buildup may require additional applications and a longer dwell time.

Health Precautions

MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear skin and eye protection. Contains glycol ether PNB, oxalic acid, and glycolic acid. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting, seek medical attention. KEEP OUT OF REACH OF CHILDREN.

5. Size & Availability

Location	Item Code	Size	Package
USA	100991*	1 gal (3.8 L)	Bottle
Canada	C100991*	1 gal (3.8 L)	Bottle

* Indicates a special order item

6. Product Warranty

Custom® Building Products warrants to the original purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom's® sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom's® printed instructions. Custom® makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country or territory to another. For details and complete warranty information, visit custombuildingproducts.com

7. Product Maintenance

Properly installed product requires no special maintenance.

Aqua Mix® Ex-Treme®

8. Technical Services Information

For technical assistance contact Custom® Building Products.

9. Filing System

Additional product information is available from the manufacturer upon request.
