

# Aqua Mix® Grout Haze Clean-Up



## 1. Product Name

Aqua Mix® Grout Haze Clean-Up

## 2. Manufacturer

Custom Building Products  
 Technical Services  
 10400 Pioneer Boulevard, Unit 3  
 Santa Fe Springs, CA 90670  
 Customer Support: 800-272-8786  
 Technical Services: 800-282-8786  
 Fax: 800- 200-7765  
 Email: [contactus@cbpmail.net](mailto:contactus@cbpmail.net)  
[custombuildingproducts.com](http://custombuildingproducts.com)

## 3. Product Description

A safe and effective concentrated cleaner that is added to the grout cleanup water for removal of cementitious grout haze and latex additive film from tile during the grout cleanup process. It may also be used full-strength to remove light grout residue within the first 10 days after grouting.

### Key Features

- Add to clean-up water
- Removes grout haze and latex additive film
- Non-acidic formula

### Uses

Unpolished natural stone (such as granite, limestone, marble, slate, and travertine), polished granite, ceramic, porcelain, quarry, Saltillo, terra-cotta, cement pavers, masonry surfaces, and other stone and tile surfaces

### Limitations to the Product

- Do not allow product to come in contact with any non-recommended surface
- Do not use on polished marble or any other acid-sensitive tile or stone
- Do not use excessive amounts of water during cleanup process as grout pigment may be washed out

### Environmental Consideration

Complies with all Federal EPA and SCAQMD standards for VOC.

### Application of Product

**USE CHEMICAL-RESISTANT GLOVES, such as nitrile, when handling product.**

**DURING GROUT CLEANUP:** Read entire label before using. Perform grout cleanup per grout manufacturer's instructions. Mix 3 to 5 oz (90 to 147 mL) of Grout Haze Clean-Up per gallon (3.8 L) of water. Wet a grout sponge or terry cloth towel with the cleaning solution, wring out excess liquid. Wipe diagonally across the tile. Repeat steps 4 and 5 every 10 to 15 ft (.9 M to 1.3 M) or as necessary. Remove residual cleaning solution using a clean grout sponge or terry cloth towel dampened with clean water only.

**AFTER GROUT CLEANUP WITHIN 10 DAYS OF GROUTING:** Use full strength if grout haze was not completely removed during grout cleanup. Apply directly to surface and agitate with white nylon scrub pad or brush. Allow product to dwell for 5 to 10 minutes for stubborn areas or heavier grout residue. Rinse with clean water to remove residual cleaning solution.

### Health Precautions

MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear skin and eye protection. Contains EDTA acid, sodium tripolyphosphate, trisodium citrate dihydrate, and Beta-Alanine, N - (2-carboxyethyl)-N-(2-ethylhexyl)-monosodium salt. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting, seek medical attention.

## 4. Size & Availability

Location	Item Code	Size	Package
USA	010461	1 Pint (473 ml)	Bottle
Canada	C010461	1 Pint (473 ml)	Bottle

## 5. Product Warranty

Custom® Building Products warrants to the original purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom's® sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom's® printed instructions. Custom® makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country or territory to another. For details and complete warranty information, visit [custombuildingproducts.com](http://custombuildingproducts.com)

## 6. Product Maintenance

Properly installed product requires no special maintenance.

## 7. Technical Services Information

For technical assistance contact Custom® Building Products.

## 8. Filing System

Additional product information is available from the manufacturer upon request.