# Aqua Mix® KnockDown®

## 1. Product Name

Aqua Mix® KnockDown®

## 2. Manufacturer

Custom Building Products
Technical Services
10400 Pioneer Boulevard, Unit 3
Santa Fe Springs, CA 90670
Customer Support: 800-272-8786
Technical Services: 800-282-8786
Fax: 800- 200-7765
Email: contactus@cbpmail.net
custombuildingproducts.com

## 3. Product Description

A non-acidic honing powder that removes light surface scratches, moderate acid etching and wear patterns to produce a flat, even and honed finish. It is excellent for safely honing polished marble, limestone or travertine to a smooth honed surface when a honed, unpolished finish is desired.

### Key Features

- Removes scratches, acid etching and traffic wear patterns
- Produces an even, flat, honed finish
- Safe, acid-free formula

### Limitations to the Product

- Do not allow product to come in contact with any non-recommended surface.
- Not intended for use as a pre-polish powder

### Technical Chart

| Property | Result |
|---|---|
| pH | 7-9 |

### Environmental Consideration

Complies with all Federal EPA and SCAQMD standards for VOC.

## 4. Instructions

### General Surface Prep

Test a small area according to application instructions to determine desired results.

### Application of Product

**USE CHEMICAL-RESISTANT GLOVES, such as nitrile, when handling product.**

Read entire label before using. Test in a small inconspicuous area to determine desired results. Sweep or vacuum surface. Protect baseboards, carpet, etc. with protective plastic and/or blue painters tape. Surface must be free of existing sealers or coatings. Liberally apply KnockDown® to the stone surface. Add water to form a slurry. Refinish using a weighted floor machine fitted with a natural hair or synthetic fiber tan floor pad or use a hand polishing machine. If lippage is present, use two pads, double stacked. Keep slurry wet while buffing. Add KnockDown® as needed. Harder stones will require a thicker slurry. Buff area until the desired level of hone has been achieved squeegee slurry from a small area to check for desired results prior to removing slurry. Rinse well and use a wet vacuum to remove all excess compound.

### Health Precautions

MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear skin and eye protection. Contains nonreactive mineral powders. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting, seek medical attention. KEEP OUT OF REACH OF CHILDREN.

## 5. Size & Availability

| Location | Item Code | Size | Package |
|---|---|---|---|
| USA | 100287 | 2 lb (.9 kg) | Bottle |

## 6. Product Warranty

Custom® Building Products warrants to the original purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom's® sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom's® printed instructions. Custom® makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country or territory to another. For details and complete warranty information, visit custombuildingproducts.com

## 7. Product Maintenance

Properly installed product requires no special maintenance.

## 8. Technical Services Information

For technical assistance contact Custom® Building Products.

## 9. Filing System

Additional product information is available from the manufacturer upon request.



CUSTOM BUILDING PRODUCTS
CUSTOM®
A QUIKRETE® COMPANY