

SimplePrep® Pre-Mixed Floor Patch



Storage

Keep from freezing. Close container after each use.

Health Precautions

Avoid eye contact. If eye contact occurs, flush with water for 15 minutes. Consult a physician immediately. Do not take internally. Keep out of reach of children.

3. Size & Availability

Location	Item Code	Size	Color	Package
USA	FPQT	1 quart (.946 L)	Gray	Pail
USA	FP1	1 gallon (3.78 L)	Gray	Pail
Canada	CFPQT	1 quart (.946 L)	Gray	Pail
Canada	CFP1	1 gallon (3.78 L)	Gray	Pail

4. Product Warranty

Custom® Building Products warrants to the original consumer purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom's® sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom's® printed instructions. Custom® makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country/territory to another. For details and complete warranty information, visit </reference-library/warranties.aspx>

5. Product Maintenance

Do not use as a wear surface.

6. Technical Services Information

For technical assistance, contact Custom® Building Products.

7. Filing System

Additional product information is available from the manufacturer upon request.

1. Product Name

SimplePrep® Pre-Mixed Floor Patch

2. Product Description

Repairs holes and cracks in concrete and plywood floors prior to installing tile or other flooring.

Key Features

- Ready to use
- No mixing
- Smooths and fills minor dips and imperfections

Suitable Substrates

- For interior use only
- Concrete
- Ceramic tile
- Exterior Grade Plywood
- Vinyl flooring

Limitations to the Product

- Do not use as a wear surface.
- Use on non-porous surfaces may lead to an extended drying time.

Packaging

- 1 quart (.946 L) pail
- 1 gallon (3.78 L) pail

Bonding to Plywood and OSB Surfaces

Plywood flooring, including those under resilient flooring, must be structurally sound and meet all ANSI and deflection requirements (no flex or movement). For questions about proper subfloor installation, call Technical Services.

Application of Product

Stir contents thoroughly. Lightly dampen the area to be patched with clean water. Use smooth edge of trowel or putty knife to apply compound. May be smoothed or feather edged. Fills greater than 1/4" (6 mm) deep require two or more applications. Remove excess with a cloth.

Cleaning of Equipment

Quickly clean tools with warm soapy water.