

# SimpleGrout® Pre-Mixed Grout

## 1. Product Name

SimpleGrout® Pre-Mixed Grout

## 2. Product Description

The no-mix, no-mess alternative to traditional grout. This sanded, shrink and crack-resistant formula is also resistant to common household stains. SimpleGrout pre-mixed grout is easy to use and ideal for grout restoration.

## Key Features

- Ready to use
- No mixing
- No mess
- Stain resistant
- No shrinking
- For joints 1/16" to 1/2"



## Technical Chart

Not available.

## Limitations to the Product

- Porous stone can be stained by grout; follow directions in Surface Preparation.
- Do not use in steam rooms, areas exposed to prolonged water exposure or underwater.
- Some ceramic, glass, marble, metal or stone tiles can be scratched or damaged by the quartz sand filler. Perform a test on a small area prior to use. [Polyblend® NonSanded Grout](#) may be appropriate for joints up to 1/8" or for tile not suited for sanded grout.
- Not for use in movement joints or changes of plane in the tile installation. In these areas use an appropriate caulk or sealant such as [Commercial 100% Silicone Caulk](#) or [Polyblend® Ceramic Tile Caulk](#).

## 3. Instructions

**USE CHEMICAL-RESISTANT GLOVES, such as nitrile, when handling product.** Tile must be firmly attached and cured prior to grouting; please wait at least 24 hours for any dry set mortar meeting ANSI A118.4 standards, and at least 48 hours when using pre-mixed adhesives. Remove spacers and any loose materials from joints. Pre-sealing porous tile or stone with an appropriate TileLab® or Aqua Mix® sealer may be necessary to prevent grout staining. Surfaces and materials should be maintained at a temperature above 50° F (10° C) or below 100° F (38° C) for 72 hours.

## Application of Product

Stir grout prior to application. Lightly dampen absorptive, porous tile with clean, cool water. Holding a rubber grout float at a 45° angle, force grout diagonally into joints ensuring joints are completely filled. Remove excess grout using edge of float held at a 90° angle. Work on an area about 5 to 10 square feet at a time. Shaping joints and cleanup must begin immediately using a damp, small pore, grout sponge in a circular motion. Use clean water and sponge, changing water frequently. Wait 4 hours before removing haze from tile surface with a soft, dry cloth. If a haze still exists after 24 hours, remove it with TileLab® Heavy-Duty Stripper & Cleaner or Aqua Mix® Non-Cement Grout Haze Remover. Do not grout when temperature is below 50°F (10°C). **For rejuvenating old grout:** Clean old grout joints thoroughly with TileLab® Sulfamic Acid Cleaner or Aqua Mix® Sulfamic Acid Crystals, following instructions on product data sheets and packaging. Allow grout joints to dry overnight. Apply new grout on top of old grout according to application instructions. Allow it to dry for two hours and then remove any haze remaining on the surface with a soft, dry cloth.

## 4. Availability & Cost

Location	Item Code	Size	Color	Package
USA	PMG09QT	1 qt. (.946 L)	Natural Gray	Pail

USA	PMG105QT	1 qt. (.946 L)	Earth	Pail
USA	PMG122QT	1 qt. (.946 L)	Linen	Pail
USA	PMG165QT	1 qt. (.946 L)	Delorean Gray	Pail
USA	PMG333QT	1 qt. (.946 L)	Alabaster	Pail
USA	PMG380QT	1 qt. (.946 L)	Haystack	Pail
USA	PMG381QT	1 qt. (.946 L)	Bright White	Pail
USA	PMG091-2	1 gal. (3.78 L)	Natural Gray	Pail
USA	PMG1051-2	1 gal. (3.78 L)	Earth	Pail
USA	PMG1221-2	1 gal. (3.78 L)	Linen	Pail
USA	PMG1651-2	1 gal. (3.78 L)	Delorean Gray	Pail
USA	PMG3331-2	1 gal. (3.78 L)	Alabaster	Pail
USA	PMG3801-2	1 gal. (3.78 L)	Haystack	Pail
USA	PMG3811-2	1 gal. (3.78 L)	Bright White	Pail
Canada	CPMG122QT	1 qt. (.946 L)	Linen	Pail
Canada	CPMG165QT	1 qt. (.946 L)	Delorean Gray	Pail
Canada	CPMG333QT	1 qt. (.946 L)	Alabaster	Pail
Canada	CPMG381QT	1 qt. (.946 L)	Bright White	Pail
Canada	CPMG1221-2	1 gal. (3.78 L)	Linen	Pail
Canada	CPMG1651-2	1 gal. (3.78 L)	Delorean Gray	Pail
Canada	CPMG3331-2	1 gal. (3.78 L)	Alabaster	Pail
Canada	CPMG3801-2	1 gal. (3.78 L)	Haystack	Pail
Canada	CPMG3811-2	1 gal. (3.78 L)	Bright White	Pail

See our color card for truest color representation when selecting or specifying a grout color. Final installed shade may vary with the tile type, color and porosity as well as jobsite conditions and finishing techniques. For best results, perform a test on a small, inconspicuous area or create a sample board prior to installation.

## 5. Product Warranty

Custom® Building Products warrants to the original consumer purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom's® sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom's® printed instructions. Custom® makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country/territory to another. For details and complete warranty information, visit [custombuildingproducts.com](http://custombuildingproducts.com).

## 6. Product Maintenance

Keep grout clean with an appropriate TileLab® or Aqua Mix® cleaner. **Maintenance** Clean with a neutral cleaner such as Aquamix AquaKleen or Tilelab Grout & Tile Cleaner

## Curing of Product

Typically 24 hours for temperature above 50° F (10° C). Allow 3 days prior to water exposure for shower walls and 7 days for shower floors.

## 7. Technical Services Information

For technical assistance, contact Custom® Building Products.

## 8. Filing System

Additional product information is available from the manufacturer upon request.

## Cleaning of Equipment

Clean tools and hands with water before material dries.

## Health Precautions

Contains Petroleum Distillates. If ingested, do not induce vomiting and call a physician immediately. Use with adequate ventilation. Non-flammable. KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY. KEEP FROM FREEZING.

## 9. Technical Services Information

For technical assistance, contact Custom® Building Products.

## 10. Filing System

Additional product information is available from the manufacturer upon request.

## Coverage Chart

### 1 gallon pail of Simple Grout in ft<sup>2</sup> (m<sup>2</sup>) per gallon

Tile Size Width x Length x Thickness	Joint Width					
	1/16" (1.6 mm)	1/8" (3 mm)	3/16" (4.8 mm)	1/4" (6.3 mm)	3/8" (9.5 mm)	1/2" (13 mm)
1" x 1" x 1/4" (2.5 x 2.5 x .64 cm)	55 ft <sup>2</sup> (5.1 m <sup>2</sup> )	31 ft <sup>2</sup> (2.9 m <sup>2</sup> )	23 ft <sup>2</sup> (2.1 m <sup>2</sup> )	19 ft <sup>2</sup> (1.8 m <sup>2</sup> )	15 ft <sup>2</sup> (1.4 m <sup>2</sup> )	14 ft <sup>2</sup> (1.3 m <sup>2</sup> )
2" x 2" x 1/4" (5 x 5 x .64 cm)	103 ft <sup>2</sup> (9.6 m <sup>2</sup> )	55 ft <sup>2</sup> (5.1 m <sup>2</sup> )	39 ft <sup>2</sup> (3.6 m <sup>2</sup> )	31 ft <sup>2</sup> (2.9 m <sup>2</sup> )	23 ft <sup>2</sup> (2.1 m <sup>2</sup> )	19 ft <sup>2</sup> (1.8 m <sup>2</sup> )
3" x 3" x 1/4" (7.6 x 7.6 x .64 cm)	152 ft <sup>2</sup> (14.1 m <sup>2</sup> )	79 ft <sup>2</sup> (7.3 m <sup>2</sup> )	55 ft <sup>2</sup> (5.1 m <sup>2</sup> )	43 ft <sup>2</sup> (4 m <sup>2</sup> )	31 ft <sup>2</sup> (2.9 m <sup>2</sup> )	25 ft <sup>2</sup> (2.3 m <sup>2</sup> )
4.25" x 4.25" x 1/4" (10.8 x 10.8 x .64 cm)	213 ft <sup>2</sup> (19.8 m <sup>2</sup> )	110 ft <sup>2</sup> (10.2 m <sup>2</sup> )	75 ft <sup>2</sup> (7.0 m <sup>2</sup> )	58 ft <sup>2</sup> (5.4 m <sup>2</sup> )	41 ft <sup>2</sup> (3.8 m <sup>2</sup> )	32 ft <sup>2</sup> (3.0 m <sup>2</sup> )
6" x 6" x 1/4" (15.2 x 15.2 x .64 cm)	298 ft <sup>2</sup> (27.7 m <sup>2</sup> )	152 ft <sup>2</sup> (14.1 m <sup>2</sup> )	103 ft <sup>2</sup> (9.6 m <sup>2</sup> )	79 ft <sup>2</sup> (7.4 m <sup>2</sup> )	55 ft <sup>2</sup> (5.1 m <sup>2</sup> )	43 ft <sup>2</sup> (4.0 m <sup>2</sup> )
8" x 8" x 3/8" (20.3 x 20.3 x 1 cm)	263 ft <sup>2</sup> (24.4 m <sup>2</sup> )	134 ft <sup>2</sup> (12.4 m <sup>2</sup> )	91 ft <sup>2</sup> (8.5 m <sup>2</sup> )	69 ft <sup>2</sup> (6.4 m <sup>2</sup> )	47 ft <sup>2</sup> (4.4 m <sup>2</sup> )	37 ft <sup>2</sup> (3.4 m <sup>2</sup> )
12" x 12" x 3/8" (30.5 x 30.5 x 1 cm)	393 ft <sup>2</sup> (36.5 m <sup>2</sup> )	199 ft <sup>2</sup> (18.5 m <sup>2</sup> )	134 ft <sup>2</sup> (12.4 m <sup>2</sup> )	101 ft <sup>2</sup> (9.4 m <sup>2</sup> )	69 ft <sup>2</sup> (6.4 m <sup>2</sup> )	53 ft <sup>2</sup> (4.9 m <sup>2</sup> )
16" x 16" x 3/8" (40.6 x 40.6 x 1 cm)	523 ft <sup>2</sup> (48.6 m <sup>2</sup> )	263 ft <sup>2</sup> (24.4 m <sup>2</sup> )	177 ft <sup>2</sup> (16.4 m <sup>2</sup> )	134 ft <sup>2</sup> (12.4 m <sup>2</sup> )	91 ft <sup>2</sup> (8.5 m <sup>2</sup> )	69 ft <sup>2</sup> (6.4 m <sup>2</sup> )
18" x 18" x 3/8" (45.7 x 45.7 x 1 cm)	588 ft <sup>2</sup> (54.6 m <sup>2</sup> )	296 ft <sup>2</sup> (27.5 m <sup>2</sup> )	199 ft <sup>2</sup> (18.5 m <sup>2</sup> )	150 ft <sup>2</sup> (13.9 m <sup>2</sup> )	101 ft <sup>2</sup> (9.4 m <sup>2</sup> )	77 ft <sup>2</sup> (7.2 m <sup>2</sup> )
20" x 20" x 3/8" (50.8 x 50.8 x 1 cm)	653 ft <sup>2</sup> (60.7 m <sup>2</sup> )	328 ft <sup>2</sup> (30.5 m <sup>2</sup> )	220 ft <sup>2</sup> (20.4 m <sup>2</sup> )	166 ft <sup>2</sup> (15.4 m <sup>2</sup> )	112 ft <sup>2</sup> (10.4 m <sup>2</sup> )	85 ft <sup>2</sup> (7.9 m <sup>2</sup> )
24" x 24" x 3/8" (61 x 61 x 1 cm)	782 ft <sup>2</sup> (72.6 m <sup>2</sup> )	393 ft <sup>2</sup> (36.5 m <sup>2</sup> )	263 ft <sup>2</sup> (24.4 m <sup>2</sup> )	199 ft <sup>2</sup> (18.5 m <sup>2</sup> )	134 ft <sup>2</sup> (12.4 m <sup>2</sup> )	101 ft <sup>2</sup> (9.4 m <sup>2</sup> )
6" x 24" x 3/8" (15.2 x 61 x 1 cm)	315 ft <sup>2</sup> (29.3 m <sup>2</sup> )	160 ft <sup>2</sup> (14.8 m <sup>2</sup> )	108 ft <sup>2</sup> (10 m <sup>2</sup> )	82 ft <sup>2</sup> (7.6 m <sup>2</sup> )	56 ft <sup>2</sup> (5.2 m <sup>2</sup> )	43 ft <sup>2</sup> (4.0 m <sup>2</sup> )
12" x 24" x 3/8" (30.5 x 61 x 1 cm)	523 ft <sup>2</sup> (48.6 m <sup>2</sup> )	263 ft <sup>2</sup> (24.5 m <sup>2</sup> )	177 ft <sup>2</sup> (16.4 m <sup>2</sup> )	134 ft <sup>2</sup> (12.4 m <sup>2</sup> )	91 ft <sup>2</sup> (8.4 m <sup>2</sup> )	69 ft <sup>2</sup> (6.4 m <sup>2</sup> )
6" x 36" x 3/8" (15.2 x 91.4 x 1 cm)	338 ft <sup>2</sup> (31.4 m <sup>2</sup> )	171 ft <sup>2</sup> (15.9 m <sup>2</sup> )	115 ft <sup>2</sup> (10.7 m <sup>2</sup> )	87 ft <sup>2</sup> (8.1 m <sup>2</sup> )	60 ft <sup>2</sup> (5.6 m <sup>2</sup> )	46 ft <sup>2</sup> (4.3 m <sup>2</sup> )
9 x 36" x 3/8" (22.9 x 91.4 x 1 cm)	471 ft <sup>2</sup> (43.8 m <sup>2</sup> )	238 ft <sup>2</sup> (22.1 m <sup>2</sup> )	160 ft <sup>2</sup> (14.9 m <sup>2</sup> )	121 ft <sup>2</sup> (11.2 m <sup>2</sup> )	82 ft <sup>2</sup> (7.6 m <sup>2</sup> )	62 ft <sup>2</sup> (5.8 m <sup>2</sup> )
12" x 48" x 3/8" (30.5 x 122 x 1 cm)	627 ft <sup>2</sup> (58.2 m <sup>2</sup> )	315 ft <sup>2</sup> (29.3 m <sup>2</sup> )	212 ft <sup>2</sup> (19.7 m <sup>2</sup> )	160 ft <sup>2</sup> (14.9 m <sup>2</sup> )	108 ft <sup>2</sup> (10 m <sup>2</sup> )	82 ft <sup>2</sup> (7.6 m <sup>2</sup> )

### 1 quart pail of Simple Grout in ft<sup>2</sup> (m<sup>2</sup>) per quart

Tile Size Width x Length x Thickness	Joint Width					
	1/16" (1.6 mm)	1/8" (3 mm)	3/16" (4.8 mm)	1/4" (6.3 mm)	3/8" (9.5 mm)	1/2" (13 mm)
1" x 1" x 1/4" (2.5 x 2.5 x .64 cm)	14 ft <sup>2</sup> (1.3 m <sup>2</sup> )	8 ft <sup>2</sup> (0.7 m <sup>2</sup> )	6 ft <sup>2</sup> (0.5 m <sup>2</sup> )	5 ft <sup>2</sup> (0.4 m <sup>2</sup> )	4 ft <sup>2</sup> (0.4 m <sup>2</sup> )	3 ft <sup>2</sup> (0.3 m <sup>2</sup> )
2" x 2" x 1/4" (5 x 5 x .64 cm)	26 ft <sup>2</sup> (2.4 m <sup>2</sup> )	14 ft <sup>2</sup> (1.3 m <sup>2</sup> )	10 ft <sup>2</sup> (0.9 m <sup>2</sup> )	8 ft <sup>2</sup> (0.7 m <sup>2</sup> )	6 ft <sup>2</sup> (0.5 m <sup>2</sup> )	5 ft <sup>2</sup> (0.4 m <sup>2</sup> )
3" x 3" x 1/4" (7.6 x 7.6 x .64 cm)	38 ft <sup>2</sup> (3.5 m <sup>2</sup> )	20 ft <sup>2</sup> (1.8 m <sup>2</sup> )	13.8 ft <sup>2</sup> (1.3 m <sup>2</sup> )	10.8 ft <sup>2</sup> (1 m <sup>2</sup> )	7.8 ft <sup>2</sup> (0.7 m <sup>2</sup> )	6.3 ft <sup>2</sup> (0.6 m <sup>2</sup> )

4.25" x 4.25" x 1/4" (10.8 x 10.8 x .64 cm)	53 ft <sup>2</sup> (4.9 m <sup>2</sup> )	27 ft <sup>2</sup> (2.5 m <sup>2</sup> )	19 ft <sup>2</sup> (1.7 m <sup>2</sup> )	14 ft <sup>2</sup> (1.3 m <sup>2</sup> )	10 ft <sup>2</sup> (0.9 m <sup>2</sup> )	8 ft <sup>2</sup> (0.7 m <sup>2</sup> )
6" x 6" x 1/4" (15.2 x 15.2 x .64 cm)	74 ft <sup>2</sup> (6.9 m <sup>2</sup> )	38 ft <sup>2</sup> (3.5 m <sup>2</sup> )	26 ft <sup>2</sup> (2.4 m <sup>2</sup> )	20 ft <sup>2</sup> (1.8 m <sup>2</sup> )	14 ft <sup>2</sup> (1.3 m <sup>2</sup> )	11 ft <sup>2</sup> (1 m <sup>2</sup> )
8" x 8" x 3/8" (20.3 x 20.3 x 1 cm)	66 ft <sup>2</sup> (6.1 m <sup>2</sup> )	34 ft <sup>2</sup> (3.1 m <sup>2</sup> )	23 ft <sup>2</sup> (2.1 m <sup>2</sup> )	17 ft <sup>2</sup> (1.6 m <sup>2</sup> )	12 ft <sup>2</sup> (1.1 m <sup>2</sup> )	9 ft <sup>2</sup> (0.9 m <sup>2</sup> )
12" x 12" x 3/8" (30.5 x 30.5 x 1 cm)	98 ft <sup>2</sup> (9.1 m <sup>2</sup> )	50 ft <sup>2</sup> (4.6 m <sup>2</sup> )	33 ft <sup>2</sup> (3.1 m <sup>2</sup> )	25 ft <sup>2</sup> (2.4 m <sup>2</sup> )	17 ft <sup>2</sup> (1.6 m <sup>2</sup> )	13 ft <sup>2</sup> (1.2 m <sup>2</sup> )
16" x 16" x 3/8" (40.6 x 40.6 x 1 cm)	131 ft <sup>2</sup> (12.1 m <sup>2</sup> )	66 ft <sup>2</sup> (6.1 m <sup>2</sup> )	44 ft <sup>2</sup> (4.1 m <sup>2</sup> )	33 ft <sup>2</sup> (3.1 m <sup>2</sup> )	23 ft <sup>2</sup> (8.5 m <sup>2</sup> )	17 ft <sup>2</sup> (1.6 m <sup>2</sup> )
18" x 18" x 3/8" (45.7 x 45.7 x 1 cm)	147 ft <sup>2</sup> (13.7 m <sup>2</sup> )	74 ft <sup>2</sup> (6.9 m <sup>2</sup> )	50 ft <sup>2</sup> (4.6 m <sup>2</sup> )	38 ft <sup>2</sup> (3.5 m <sup>2</sup> )	25 ft <sup>2</sup> (2.4 m <sup>2</sup> )	19 ft <sup>2</sup> (1.8 m <sup>2</sup> )
20" x 20" x 3/8" (50.8 x 50.8 x 1 cm)	163 ft <sup>2</sup> (15 m <sup>2</sup> )	82 ft <sup>2</sup> (7.6 m <sup>2</sup> )	55 ft <sup>2</sup> (5.1 m <sup>2</sup> )	42 ft <sup>2</sup> (3.9 m <sup>2</sup> )	28 ft <sup>2</sup> (2.6 m <sup>2</sup> )	21 ft <sup>2</sup> (2 m <sup>2</sup> )
24" x 24" x 3/8" (61 x 61 x 1 cm)	196 ft <sup>2</sup> (18 m <sup>2</sup> )	98 ft <sup>2</sup> (9.1 m <sup>2</sup> )	66 ft <sup>2</sup> (6.1 m <sup>2</sup> )	50 ft <sup>2</sup> (4.6 m <sup>2</sup> )	34 ft <sup>2</sup> (3.1 m <sup>2</sup> )	25 ft <sup>2</sup> (2.3 m <sup>2</sup> )
6" x 24" x 3/8" (15.2 x 61 x 1 cm)	79 ft <sup>2</sup> (7.3 m <sup>2</sup> )	40 ft <sup>2</sup> (3.7 m <sup>2</sup> )	27 ft <sup>2</sup> (2.5 m <sup>2</sup> )	20 ft <sup>2</sup> (1.9 m <sup>2</sup> )	14 ft <sup>2</sup> (1.3 m <sup>2</sup> )	11 ft <sup>2</sup> (1 m <sup>2</sup> )
12" x 24" x 3/8" (30.5 x 61 x 1 cm)	131 ft <sup>2</sup> (12.1 m <sup>2</sup> )	66 ft <sup>2</sup> (6.1 m <sup>2</sup> )	44 ft <sup>2</sup> (4.1 m <sup>2</sup> )	33 ft <sup>2</sup> (3.1 m <sup>2</sup> )	23 ft <sup>2</sup> (2.1 m <sup>2</sup> )	17 ft <sup>2</sup> (1.6 m <sup>2</sup> )
6" x 36" x 3/8" (15.2 x 91.4 x 1 cm)	85 ft <sup>2</sup> (7.9 m <sup>2</sup> )	43 ft <sup>2</sup> (4 m <sup>2</sup> )	29 ft <sup>2</sup> (2.7 m <sup>2</sup> )	22 ft <sup>2</sup> (2 m <sup>2</sup> )	15 ft <sup>2</sup> (1.4 m <sup>2</sup> )	11.5 ft <sup>2</sup> (1.1 m <sup>2</sup> )
9 x 36" x 3/8" (22.9 x 91.4 x 1 cm)	118 ft <sup>2</sup> (10.9 m <sup>2</sup> )	60 ft <sup>2</sup> (5.5 m <sup>2</sup> )	40 ft <sup>2</sup> (3.7 m <sup>2</sup> )	30 ft <sup>2</sup> (2.8 m <sup>2</sup> )	21 ft <sup>2</sup> (1.9 m <sup>2</sup> )	15.5 ft <sup>2</sup> (1.4 m <sup>2</sup> )
12" x 48" x 3/8" (30.5 x 122 x 1 cm)	157 ft <sup>2</sup> (14.6 m <sup>2</sup> )	79 ft <sup>2</sup> (7.3 m <sup>2</sup> )	53 ft <sup>2</sup> (4.9 m <sup>2</sup> )	40 ft <sup>2</sup> (3.7 m <sup>2</sup> )	27 ft <sup>2</sup> (2.5 m <sup>2</sup> )	20.5 ft <sup>2</sup> (1.9 m <sup>2</sup> )

Chart for estimating purposes. Coverage may vary based on installation practices and jobsite conditions. For more tile and joint sizes, use the [Material Calculator](#) at CustomBuildingProducts.com or contact CUSTOM Technical Services at [800-282-8786](tel:800-282-8786).