

TileLab® Grout & Tile Sealer

1. Product Name

TileLab® Grout & Tile Sealer

2. Product Description

Economical, easy-to-apply, penetrating sealer that resists most common oil-based and water-based stains. Unlike other sealers, it will not leave a difficult-to-remove residue on the surface. Low-odor, water-based formula.

Key Features

- Protects grout and tile against stains

Technical Chart

- Stain resistant to most household contaminants (CTI-072)
- Does not darken most tile and grout
- Complies with all Federal and SCAQMD Standards for VOCs



3. Instructions

Surface should be dry, clean and free of waxes, sealers or finishes. TileLab® Heavy-Duty Stripper & Cleaner or Aqua Mix® Heavy-Duty Tile & Grout Cleaner will clean the surface or strip wax and acrylic finishes. New installations need to be cured 48 - 72 hours before application. Protect painted surfaces. Test product in obscure area to ensure desirable results. Sealer can be applied 48 hours after grout has been installed.

Application of Product

USE CHEMICAL-RESISTANT GLOVES, such as nitrile, when handling product. Apply liberally using a new mop, lambswool applicator, sponge or brush. Allow it to penetrate for up to 5 minutes. Immediately wipe off any excess. If first coat has been absorbed, apply a second coat following the same procedure. Porous surfaces may require additional applications. Conduct a test to see if surface is completely sealed after 2 hours by applying drops of water on the surface. If it penetrates immediately, apply an additional coat. If a residue is visible on the surface after drying, remove it with water and a sponge or white polishing pad 60 minutes after application.

4. Availability & Cost

Location	Item Code	Size	Package
USA	TLPS24Z	24 fl. oz. (709 ml)	Spray Bottle
USA	TLPSRA1-2	1 gal (3.78 L)	Bottle
Canada	CTLPSQT-3	1 qt (.946 L)	Bottle
Canada	CTLPS1-2	1 gal (3.78 L)	Bottle

5. Product Warranty

Custom® Building Products warrants to the original purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom's® sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom's® printed instructions. Custom® makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country or territory to another. For details and complete warranty information, visit [/reference-library/warranties.aspx](#)

6. Technical Services Information

For technical assistance, contact Custom® Building Products.

7. Filing System

Additional product information is available from the manufacturer upon request.

Cleaning of Equipment

Clean tools and hands with soap and water immediately after use.

Health Precautions

MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear skin and eye protection. Contains potassium hydroxide and potassium methyl silicate. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting. Seek medical attention. Keep out of reach of children.

8. Technical Services Information

For technical assistance, contact Custom® Building Products.

9. Filing System

Additional product information is available from the manufacturer upon request.

Coverage Chart

Size	Min Coverage	Max Coverage
On Polished or Dense Surfaces:		
1 Gallon (3.78 L)	800 sq. ft. (74 M ²)	1200 sq. ft. (112 M ²)
24 fl. oz. (709 mL)	150 sq. ft. (14 M ²)	225 sq. ft. (20 M ²)
On Porous Surfaces:		
1 Gallon (3.78 L)(3.78 L)	200 sq. ft. (19 M ²)	400 sq. ft. (37 M ²)
24 fl. oz. (709 mL)	38 sq. ft. (3.5 M ²)	75 sq. ft. (7 M ²)