

TileLab® Grout Sealer

1. Product Name

TileLab® Grout Sealer

2. Product Description

Invisible, low-odor, penetrating grout sealer that protects grout joints from stains and dirt. Easy to apply, it won't leave a hard-to-remove residue on tile surfaces.

Key Features

- Protects grout against stains

Suitable Substrates

For sanded and non-sanded cementitious grout joints.

Technical Chart

- Stain resistant to most household contaminants (CTI-072)
- Does not darken grout
- Complies with all Federal and SCAQMD Standards for VOCs



Application of Product

USE CHEMICAL-RESISTANT GLOVES, such as nitrile, when handling product. Surface should be clean, dry and free of any waxes or finishes. For new installations allow grout to cure 48 - 72 hours. Unscrew cap and remove seal. Apply liberally to grout joints in even coats. Allow to penetrate 5 minutes. Wipe off excess. If absorbed, apply a second coat. Surface is sealed when sealer no longer penetrates. If residue is visible on tile surface, remove with water and sponge or white nylon pad 60 minutes after application.

3. Availability & Cost

Location	Item Code	Size	Package
USA	TLGS6Z	6 fl. oz. (177.5 ml)	Bottle

4. Product Warranty

Custom® Building Products warrants to the original purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom's® sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom's® printed instructions. Custom® makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country or territory to another. For details and complete warranty information, visit </reference-library/warranties.aspx>

5. Product Maintenance

Use an appropriate TileLab® cleaner for routine cleaning.

6. Technical Services Information

For technical assistance contact Custom® Building Products.

7. Filing System

Additional product information is available from the manufacturer upon request.

Cleaning of Equipment

Clean hands with soap and water.

Health Precautions

MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear skin and eye protection. Contains potassium hydroxide and potassium methyl silicate. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting and seek medical attention. Keep out of reach of children.

8. Technical Services Information

For technical assistance contact Custom® Building Products.

9. Filing System

Additional product information is available from the manufacturer upon request.

Coverage Chart

Size	Min Coverage	Max Coverage
6 fl. oz. (177.5 mL)	50 sq. ft. (4.6 M ²)	80 sq. ft. (7.4 M ²)