

StoneSpecific® Polished Granite Sealer

1. Product Name

StoneSpecific® Polished Granite Sealer

2. Product Description

A specially-formulated stone sealer designed to penetrate and protect the surface of a polished, high-density natural stone such as granite. Provides optimum protection against grease, dirt, oil and water-based stains allowing for easy daily maintenance.

StoneSpecific® Low VOC (Volatile Organic Compound) formulas help provide better indoor and outdoor air quality compared to similar traditional products. Complies with EPA and CARB VOC Requirements.

Key Features

- Premium water-based formula
- Low odor and pH neutral
- Interior and Exterior Use
- For commercial or residential applications
- Allows moisture vapor transmission
- Also protects sanded or non-sanded grout



Benefits of Product in the Installation

Protects fabricated granite slabs or tiles in kitchen, bath, floors and walls. When optimum protection is needed in food preparation or high traffic areas.

Technical Chart

- Excellent stain resistance to most household contaminants (CTI-072)
- No darkening of stone

3. Instructions

Surface should be dry, clean and free of waxes, sealers or finishes. TileLab® Heavy-Duty Cleaner & Stripper will clean the surface or strip wax and acrylic finishes. New installations: Allow grout to cure 48 hours before applying sealer.

Application of Product

WEAR IMPERVIOUS GLOVES, such as nitrile, and eye protection when handling product.

Test product in obscure area to ensure desirable results. Apply liberally using a new mop, lambswool applicator or sponge. Maintain a thin, even coat to cover surface, working-in sealer for 5 - 10 minutes. Surface must stay wet letting sealer soak for additional 10 minutes for maximum penetration. Immediately after, wipe off any sealer completely before it dries. If initial coat has been absorbed, apply additional coat 15 minutes after first application.

4. Availability & Cost

| Item Code | Size | Location | Package |
|------------|------------------|----------|---------|
| CSSPGSQT-3 | 1 quart (946 ml) | Canada | Bottle |

5. Product Warranty

Custom® Building Products warrants to the original consumer purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom's sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom's printed instructions. Custom makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country/territory to another.

6. Product Maintenance

Do not use cleaners containing ammonia, acids or bleach; use StoneSpecific Polished Granite Cleaner/Resealer. Tile industry experts recommend testing sealed surfaces every two years. Apply a few drops of water on the surface. If it soaks in, a coat of StoneSpecific Polished Granite Sealer will be necessary to keep protection at peak performance.

7. Technical Services Information

For technical assistance, contact Custom Building Products or visit custombuildingproducts.com.

8. Filing System

Additional product information is available from the manufacturer upon request.

Cleaning of Equipment

Clean tools and hands with soap and water immediately after use.

Health Precautions

CAUTION: MAY IRRITATE EYES. MAY IRRITATE SKIN. MAY CAUSE RESPIRATORY IRRITATION. Do not mix with other chemical products. Do not get on skin or clothing. Do not get in eyes. Do not breathe fumes. Do not swallow. **KEEP OUT OF REACH OF CHILDREN.** Use only in a well-ventilated area. Wear chemical resistant gloves, CSA approved respirator, and eye protection. **FIRST AID TREATMENT:** Contains: Fluoropolymer, quaternary amine compound and d-Limonene. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water. If breathed in, move person into fresh air. In emergency, call (800) 535-5053.

9. Technical Services Information

For technical assistance, contact Custom Building Products or visit custombuildingproducts.com.

10. Filing System

Additional product information is available from the manufacturer upon request.

Coverage Chart

| Size | Min Coverage | Max Coverage |
|---------------|------------------------------------|------------------------------------|
| Quart (946ml) | 200 sq. ft. (18.6 M ²) | 300 sq. ft. (27.9 M ²) |