

StoneSpecific® Stone Enhancer & Sealer

1. Product Name

StoneSpecific® Stone Enhancer & Sealer

2. Product Description

Available in Canada only.

Color enhancer and penetrating sealer for all types of porous natural stone and grout. Rejuvenates the color and appearance of worn, faded stone, tumbled marble and other rustic-look stones. Can also be used to darken the color of grout. Provides long-lasting protection against oil, grease and stains. Its water-based, low odor formula can be used indoors or outdoors.

StoneSpecific® Low VOC (Volatile Organic Compound) formulas help provide better indoor and outdoor air quality compared to similar traditional products. Complies with EPA and CARB VOC Requirements.

For interior and exterior use.



Technical Chart

- Excellent stain resistance to most household contaminants (CTI-072)
- Darkens most stone to a "wet look"

3. Instructions

Surface should be dry, clean and free of waxes, sealers or finishes. TileLab® Heavy-Duty Cleaner & Stripper will clean the surface or strip wax and acrylic finishes. New installations need to be cured 48 hours before application.

Application of Product

USE CHEMICAL-RESISTANT GLOVES, such as nitrile, when handling product. Once the enhancer has been applied to the surface of stone, grout or tile it cannot be reversed. Always test product in hidden area to ensure desired results. Apply liberally using a new mop, lambswool applicator or sponge. Allow to penetrate for up to 5 minutes. Immediately wipe off any sealer completely before it dries. Immediately apply a second coat. Ensure no residue is left to dry on the surface. Do not use outside if inclement weather is expected within 24 hours. Clean off any residue left on the surface with an appropriate StoneSpecific® or TileLab® cleaner. Note: The more porous the stone the deeper the color enhancement.

4. Availability & Cost

Item Code	Size	Location	Package
SSSESQT-3	1 quart (946 ml)	USA	Bottle
CSSSESQT-3	1 quart (946 ml)	Canada	Bottle

5. Product Warranty

Custom® Building Products warrants to the original consumer purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom's sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom's printed instructions. Custom makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country/territory to another.

6. Product Maintenance

Properly installed product requires no special maintenance.

7. Technical Services Information

For technical assistance, contact Custom Building Products or visit custombuildingproducts.com.

8. Filing System

Additional product information is available from the manufacturer upon request.

Cleaning of Equipment

Clean tools and hands with soap and water immediately after use.

Health Precautions

MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear skin and eye protection. Contains Ethylene Glycol, Dibutyl phthalate, Dipropylene glycol methyl ether and acrylic polymer. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting. Seek medical attention. KEEP OUT OF REACH OF CHILDREN.

9. Technical Services Information

For technical assistance, contact Custom Building Products or visit custombuildingproducts.com.

10. Filing System

Additional product information is available from the manufacturer upon request.

Coverage Chart

Size	Min Coverage	Max Coverage
Porous Surfaces: Quart (946 ml)	45 sq. ft. (4.2 M ²)	85 sq. ft. (8.3 M ²)
Polished or Dense Surfaces: Quart (946 ml)	170 sq. ft. (16.6 M ²)	255 sq. ft. (25 M ²)