

SimpleMat® Tile Setting Mat

1. Product Name

SimpleMat® Tile Setting Mat

2. Product Description

The quickest, easiest and cleanest way to install tile on countertops, backsplashes and shower walls. Replaces traditional thinset mortar or mastic adhesive. Install an hour at a time or over several days. Bonds instantly for immediate grouting.



Key Features

- Complete the job in a day - No waiting between setting and grouting
- Raised adhesive delivers instant bond with lasting strength

Suitable Substrates

- Kitchen or bath counters, walls, backsplashes and shower walls.
- Tile over drywall, plywood, WonderBoard® Lite, backerboard, concrete, painted surfaces, laminates and existing tile.

Bonding To Concrete Surfaces

Concrete or plaster must be fully cured and accept water penetration. Test by sprinkling water on various areas of the substrate. If water penetrates, then a good bond can be achieved. If water beads, surface contaminants are present and loss of adhesion may occur. The contaminants should be removed before installation. Concrete must be free of efflorescence and not subject to hydrostatic pressure.

Limitations to the Product

- Not for use on floors, on ceilings, shower floors or in areas constantly exposed to water.
- Tiles should be relatively flat on back to make full contact.
- Limited adjustability.
- Not recommended for outdoor use.
- Not for use with any tile greater than 8" x 8" or heavier than 5 lbs.

3. Instructions

Surfaces must be structurally sound, clean, dry and free from grease, oil, dirt, curing compounds, sealers, adhesives or any other contaminant that would prevent a good bond. All surfaces to be tiled should be flat, even and stable (i.e. no cracks, peeling, or surface movement). SimpleMat™ will follow your wall or counter surface, so patch, flatten or level as needed.

Application of Product

Countertops SimpleMat® Sheet Layout: For efficiency lay SimpleMat® horizontally on counter. Overlap SimpleMat® edges 1/8" to 1/4" (3-6 mm). Installation: Peel off white backing paper. Apply SimpleMat® to counter. Flatten air bubbles and creases. Cover all surfaces to be tiled. Cut SimpleMat® as needed. Cut corner from end of mat to facilitate folding of corner. **SimpleMat® Roll Installation:** Roll and apply SimpleMat® vertically on counter, starting closest to backsplash. Overlap SimpleMat® edges 1/8" to 1/4" (3-6 mm). Flatten air bubbles and creases. Cover entire surface to be tiled. Cut SimpleMat® as needed. **Backsplashes** SimpleMat® Layout: Place SimpleMat® in position and mark cuts if needed. Cut SimpleMat® with scissors or utility knife. SimpleMat® Installation: Apply SimpleMat® and flatten air bubbles and creases. **Shower Walls** SimpleMat® Layout: A single sheet or strip of SimpleMat® must run across a corner with at least 1" (25 mm) of excess material on each wall. Lay SimpleMat® horizontally on shower walls starting from the bottom of your shower wall, working upward. Overlap SimpleMat® edges 1/8" to 1/4" (3 - 6 mm). SimpleMat® Installation: Place SimpleMat® in position and mark cuts if needed. Cut SimpleMat® with scissors or utility knife. Apply SimpleMat® then flatten air bubbles and creases. If additional guidance is needed, call Custom technical services. **Grout Installation** SimpleMat® is designed to be used with grout to lock in tile and stone. Grout your installation within 24 hours with the recommended SimpleGrout® Pre-Mixed Grout or Fusion Pro™ Single Component Grout™. You may also use Polyblend® Grout or CEG-Lite™ Commercial 100% Solids Epoxy Grout.

4. Availability & Cost

Location	Item Code	Size	Package	Case Pack
USA	SM10R2	9" x 18" sheets (23 x 45 cm)	9 sheets/box	6 boxes/case
Canada	CSM10R1	9" x 18" sheets (23 x 45 cm)	9 sheets/box	6 boxes/case
USA	SMCR30	9" x 40' roll (23 cm x 12.2 m)	1 roll/box	1 box/case
Canada	CSMCR30	9" x 40' roll (23 cm x 12.2 m)	1 roll/box	1 box/case

5. Product Warranty

Custom® Building Products warrants to the original consumer purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom's® sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom's® printed instructions. Custom® makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country/territory to another. For details and complete warranty information, visit </reference-library/warranties.aspx>.

6. Product Maintenance

Properly installed product requires no special maintenance.

7. Technical Services Information

For technical assistance, contact Custom® Building Products.

8. Filing System

Additional product information is available from the manufacturer upon request.

Health Precautions

SimpleMat® employs an aggressive adhesive to perform its function. Ensure that SimpleMat® is not placed over the nose or mouth and is kept away from hair.

9. Technical Services Information

For technical assistance, contact Custom® Building Products.

10. Filing System

Additional product information is available from the manufacturer upon request.