

NEW!
Now meets
ANSI A118.11

MULTISET LFT

MultiSet LFT Large Format Tile Mortar

The new, smoother handling, MultiSet LFT is a polymer-modified dry-set cement mortar with a non-slumping formula to help control lippage. Use with large and heavy porcelain, ceramic tile on concrete and exterior grade plywood surfaces. MultiSet LFT can be applied to 3/4" (19 mm) thick on horizontal applications. Large format tile is any tile with one or more sides 15" (38 cm) or larger.

- Specially formulated for large format tiles
- Supports large and heavy tile for flat, even installations
- Bonds to cement and exterior grade plywood surfaces
- Approved for industry-recommended interior and exterior applications

**WE KNOW LARGE FORMAT TILE.
COUNT ON CUSTOM.**



Scan this to
learn more about
MultiSet LFT!



CUSTOM[®]
TILE INSTALLATION SYSTEMS



Suitable Tile Types

- Vitreous, semi-vitreous or non-vitreous tile: ceramic, quarry, pavers
- Impervious porcelain

Suitable Substrates

- Concrete, mortar beds
- WonderBoard® Lite, cement backerboards
- Liquid-applied and fabric waterproofing membranes such as RedGuard® Waterproofing and Crack Prevention Membrane, Custom® 9240 Waterproofing and Anti-Fracture Membrane and RedGuard® SpeedCoat™ Rapid Curing Waterproofing Membrane
- Crack isolation sheet membranes such as Crack Buster® Pro Crack Prevention Mat Underlayment
- Uncoupling mats such as RedGuard® Uncoupling Mat
- Substrates treated with MBP Multi-Surface Bonding Primer
- Existing ceramic tile (scarified)
- Exterior Grade Plywood (interior residential and light commercial dry areas)

Standards

Exceeds ANSI A118.4H and A118.11 standards without the need for additives.

Ordering Information

	ITEM CODE	SIZE	COLOR
USA	MSMLFTG50	50 lb. (22.68 kg) Bag	Gray
USA	MSMLFTW50	50 lb. (22.68 kg) Bag	White
Canada	CMSMLFTG50	50 lb. (22.68 kg) Bag	Gray
Canada	CMSMLFTW50	50 lb. (22.68 kg) Bag	White

Approximate Coverage

TROWEL SIZE	PER 50 LB. (22.68 KG) BAG
Longest side of tile 8" to 15" (20 to 38 cm) use 1/4" x 3/8" x 1/4" (6 x 9.5 x 6 mm) Square-Notch	60 - 67 sq. ft. (5.6 - 6.2 M ²)
Longest side of tile more than 15" (38 cm) use 1/2" x 1/2" x 1/2" (13 x 13 x 13 mm) Square-Notch	42 - 47 sq. ft. (3.9 - 4.4 M ²)
Longest side of tile more than 15" (38 cm) use 3/4" x 9/16" x 3/8" (19 x 14 x 9.5 mm) U-Notch	34 - 38 sq. ft. (3.2 - 3.5 M ²)

Chart for estimating purposes. Coverage may vary based on installation practices and jobsite conditions. Use the material calculator at CustomBuildingProducts.com or contact CUSTOM Technical Services at 800-282-8786.

Recommended minimum coverage: 80% for dry areas and 95% for wet areas and exteriors. Back buttering may be necessary.

CUSTOM also offers an assortment of premium performance medium bed mortars that are ideal for large format tile. See our website for details about MegaLite, ProLite and Complete Contact-LFT.

©2021 Custom Building Products. All rights reserved. The CUSTOM® logo and select product logos are registered trademarks of Custom Building Products, Inc. CUSTOM may make product modifications at any time without notice. Visit custombuildingproducts.com for updated technical data sheets and SDS information.

Custom Building Products
800-272-8786
custombuildingproducts.com

SS182 6/21R