AQUA MIX® POULTICE STAIN REMOVAL GUIDE

When a mixture of Aqua Mix® Poultice Stain Remover and water does not effectively remove a stain, the following products used in conjunction with the mixture have been shown to produce successful results.

Notes:

Aqua Mix brand products are identified by all capital letters. Additives are listed in order from mildest to strongest cleaning compound. Always follow product instructions carefully.

Legend:

a) DO NOT use SEALER & COATING REMOVER on polished, agglomerate or manmade stone as it may etch a polished surface and dissolve the resin binders in the stone.

(b) Do not use acid cleaners on surfaces that are not acid resistant.

IMPORTANT:

Caution should be exercised with water-sensitive marbles such as green and black, follow product instructions carefully. Always test a small inconspicuous area to determine desired results. On some polished marble the entire tile may require treatment to ensure consistent results.

Consult the Custom Building Products website for more information on the prevention and removal of stains. For additional information about any of the products or methods described, contact CUSTOM's Technical Services Department at 800.282.8786.

The information in this bulletin is presented in good faith, but no warranty, express or implied, is given nor is freedom from any patent in as much as any assistance furnished by CUSTOM with reference to the safe use and disposal of its products provided without charge. Custom Building Products assumes no obligation or liability therefore, except to the extent that any such assistance shall be given in good faith.

TB98 3/17R

01 1 0	A AA' B III A I ''''
Stain Source	Aqua Mix Poultice Additive
	1 = Recommended, 2 =
	Alternative
Ink, marker pen and	1. SEALER & COATING
paint	REMOVER (a)
Oil-based	1. HEAVY-DUTY TILE & GROUT
contaminants such	CLEANER
as cooking oil,	2. SEALER & COATING
mayonnaise, grease,	REMOVER (a)
tar, and various food	, ,
stains	
Tea, coffee,	1. SEALER & COATING
tobacco, blood, bird	REMOVER (a)
and animal	2. 35% Hydrogen Peroxide
droppings	, , , , , , , , , , , , , , , , , , , ,
Algae, fungi and	1. HEAVY-DUTY TILE & GROUT
mildew	CLEANER
	2. AQUAKLEEN™
Metallic stains, rust,	1. EX-TREME® (b)
copper, brass and	2. CEMENT GROUT HAZE
other metals as well	REMOVER(b)
as red soil from	, ,
flower pots	
Efflorescence	1. EFF-EX®
Hydrocarbons such	1. EX-TREME® (b)
as soot or fire	2. HEAVY-DUTY TILE & GROUT
damage	CLEANER
Tree sap or timber	1. SEALER AND COATING
stains	REMOVER (b)

