

Consistent bright white color

Accentuates glass tile

High bond strengths with minimal shrinkage

Sag and slip resistant - immediately holds wall tiles in place

WARNING: IRRITANT.
REED COLOR OF BEACH OF CHILDREN

WARNING: RESTANT.
REED COLOR OF BEACH OF CHILDREN

NET WT.
7 LBS | 3.2 kg

Maximize the beauty of your customer's glass tile investment. **CUSTOM** brand Glass Tile Premium Thin-Set Mortar is designed specifically for the unique attributes of glass, spreading smoothly to provide full coverage behind the tile while delivering color consistency and superior bond strength. Work with the leader in performance-driven installation systems and support.

- Consistent White
- Superior Bond Strength
- Minimal Shrinkage
- Exceeds ANSI A118.4TE, A118.15TE, A118.11 and A137.2 when mixed with water



Scan this to learn more about Glass Tile Mortar!









Glass Tile Premium Thin-Set Mortar

Glass Tile Premium Thin-Set Mortar offers the ultimate in bond strength for the most demanding installation requirements for larger format glass tile, mosaics and other difficult to bond tile and stone. Glass Tile Mortar is specifically formulated to provide a consistent bright white backdrop for clear, iridescent and translucent glass tile to accentuate its brilliance and beauty.

FEATURES	BENEFITS	
Consistent White	Color-controlled process provides consistent bright white color for the entire application	
High Bond Strength	Superior bond strength and minimal shrinkage ideal for smooth glass tile	
Sag and Slip Resistant	Superior bond strength keeps the glass tiles in place when applied in vertical installations	
Excellent Handling	Smooth and creamy formula delivers an easy to trowel mortar ensuring proper coverage	
Exceeds ANSI A118.4TE, A118.15TE, A118.11 and A137.2 Requirements	High performance thin-set formulated specifically for glass tile and other impervious materials	

Suitable Tile Types

- Glass
- Natural stone
- Other impervious and hard to bond to tiles; porcelain, metal, synthetic and natural stone
- Vitreous, semi-vitreous or non-vitreous tile: ceramic, mosaic, quarry, cement body tile brick and stone veneer cement-based precast terrazzo

Suitable Substrates

- · Concrete, mortar beds, masonry, Portland cement plaster
- WonderBoard® Lite, cement backerboards
- Liquid applied waterproofing membranes such as RedGard® and Custom 9240®
- Crack prevention sheet membranes such as Crack Buster Pro®
- · Exterior grade plywood
- Gypsum wallboard (dry areas only)
- Existing ceramic tile and fully bonded sheet vinyl flooring
- · Plastic laminates and cutback adhesive

Standards

- Exceeds ANSI A118.4TE, A118.15TE, A118.11 and A137.2 standards without the need for additives
- · ISO 13007-2



Approximate Coverage

TROWEL SIZE	MINIMUM COVERAGE
1/4" x 1/4" x 1/4" (6 x 6 x 6 mm)	14 - 15.4 sq. ft. / 7 lbs.
Square-Notch	(1.3 - 1.4 M²) / 3.18 kg
1/4" x 3/8" x 1/4" (6 x 9.5 x 6 mm)	9.8 - 10.9 sq.ff. / 7 lbs.
Square-Notch	(0.9 - 1 M²) / 3.18 kg

Ordering Information

ITEM CODE	SIZE	COLOR
GTMW7-4	7 lbs. (3.18 kg) Box	White

DOWNLOAD CUSTOM'S MOBILE APP











©2022 Custom Building Products. All rights reserved. The CUSTOM® logo and select product logos are registered trademarks of Custom Building Products, Inc. CUSTOM may make product modifications at any time without notice. Visit custombuildingproducts.com for updated technical data sheets and SDS information.

materials and labor. See website for complete details.

Select a qualifying system of Prep, Set and Grout products and CUSTOM will warranty the tile installation for life, including tile,

Custom Building Products 800-272-8786 custombuildingproducts.com SS117 9/22R



