

AQUA MIX® STANDARD RECOMMENDATION FOR: ALL CEMENT-BASED GROUTS AND CUSTOM'S® PRISM® SURECOLOR® GROUT ONGOING MAINTENANCE

MAINTENANCE - ROUTINE

Purpose: Routine cleaning of Cement-Based Grouts and CUSTOM's® Prism® SureColor® Grout

Product Recommendation: Aqua Mix® Concentrated Stone & Tile Cleaner

Equipment: Sponge or synthetic mop and bucket with wringer

Coverage: Approximately 10,000 - 20,000 sq. ft. per gallon

Procedure:

1. Sweep or vacuum surface.
2. Mix 2 to 4 ounces of Concentrated Stone & Tile Cleaner per gallon of water.
3. Apply solution onto surface.
4. Allow to dwell 3 to 5 minutes on heavy soiled areas.
5. Agitate with sponge mop, synthetic mop or floor scrub machine using a white nylon scrub pad.
6. Remove dirty solution with a mop. A wet/dry vac may be used.
7. Rinse thoroughly with clean water, changing water every 500 sq. ft. or as needed.

MAINTENANCE - PERIODIC HEAVY-DUTY

Purpose: Heavy-duty cleaning of Cement-Based Grouts and CUSTOM's® Prism® SureColor® Grout

Product Recommendation: Aqua Mix® Heavy-Duty Tile & Grout Cleaner

Equipment: Synthetic mop and bucket with wringer and scrub brush or floor scrub machine with white nylon scrub pads

Coverage: Approximately 500 - 600 sq. ft. per gallon

Procedure:

1. Sweep or vacuum surface.
2. Mix 1 part of Heavy-Duty Tile & Grout Cleaner to 5 parts water.
3. Apply solution onto surface.
4. Allow to dwell 3 to 5 minutes on heavy soiled areas.
5. Agitate with scrub brush or floor scrub machine using a white nylon scrub pad.
6. Remove dirty solution with a mop. A wet/dry vac may be used.
7. Rinse thoroughly with clean water, changing water every 100 sq. ft. or as needed.

*These recommendations are intended as general guidelines for the care and maintenance of all above listed grout installations. The actual product dilution ratios and maintenance requirements may vary depending on the use and contaminants common to the area. **READ PRODUCT DIRECTIONS THOROUGHLY PRIOR TO USE. ALWAYS TEST FIRST.***

The information in this bulletin is presented in good faith, but no warranty, express or implied, is given nor is freedom from any patent in as much as any assistance furnished by CUSTOM with reference to the safe use and disposal of its products provided without charge. Custom Building Products assumes no obligation or liability therefore, except to the extent that any such assistance shall be given in good faith.



Technical Bulletin

Technical Services 800-282-8786
custombuildingproducts.com