

Custom**TECH**[®]

FLOORING PREPARATION SYSTEMS



TechPatch[™] RP

Calcium Aluminate Based Rapid-Setting Ramping Patch

- Use as a patch, ramp or screed for interior subfloors
- Install most flooring in just 60 - 90 minutes
- Apply from featheredge to 1.5" (38 mm)



A DIVISION OF
CUSTOM[®]
A QUIKRETE[®] COMPANY

TechPatch™ RP

Calcium Aluminate Based Rapid-Setting Ramping Patch

TechPatch™ RP is a premium quality calcium aluminate, fast setting underlayment product with exceptional handling characteristics, used for ramping, patching or screeding suitable horizontal substrates. TechPatch RP can be installed from featheredge to 1.5" neat under most commercial and residential floor coverings.

Suitable as an Underlayment for:

- Luxury Vinyl Tile (LVT)
- Luxury Vinyl Planks (LVP)
- Carpet flooring
- Vinyl Composition Tile (VCT)
- Sheet vinyl flooring
- Rubber flooring
- Hardwood; laminate and parquet flooring
- Porcelain, ceramic, glass, natural stone and terrazzo

Suitable Substrates*:

- Concrete, masonry and terrazzo
- Gypsum-based underlayment
- Existing resilient flooring
- Cutback adhesive residue
- Approved plywood and OSB
- Moisture mitigation membranes
- Existing ceramic tile & CBU

*Preparation and/or primers may be required to bond to any of these substrates

Benefits of Product in the Installation:

- Quick-setting formula permits most floor covering installation in as little as 60 – 90 minutes
- Exceptional handling properties
- Patches and levels to 1.5" (50 mm) thick

Ordering Information

ITEM CODE	SIZE	PACKAGE
TPRP40T	40 lb. (18.14 kg)	Bag

Coverage

Typical square foot coverage per 40 lb. bag (square meter per 18.14 Kg)

Thickness	Square Feet		Thickness	Square Meter	
	Minimum	Maximum		Minimum	Maximum
1/8"	35.42	37.73	3 mm	3.29	3.51
3/16"	23.6	25	5 mm	2.19	2.34
1/4"	17.71	18.86	6 mm	1.65	1.75
3/8"	11.81	12.58	9.5 mm	1.10	1.17
1/2"	8.86	9.43	13 mm	0.82	0.88
3/4"	5.90	6.29	19 mm	0.55	0.58
1.0"	4.43	4.72	25 mm	0.41	0.44
1.5"	2.95	3.14	38 mm	0.27	0.29

Chart for estimating purposes. Coverage may vary based on installation practices and jobsite conditions. For more sizes, use the material calculator at CustomBuildingProducts.com or contact CUSTOM Technical Services at 800-282-8786.



Warranty: Flooring Installation Systems products are backed by up-to a 25-year warranty. See CustomTechFlooring.com for full warranty information including limitations and exclusions.

©2018 Custom Building Products. All rights reserved. The CUSTOM® and CustomTech® logos, and select product logos are registered trademarks of Custom Building Products, Inc. CUSTOM may make product modifications at any time without notice. Visit customtechflooring.com for updated technical data sheets and SDS information.

Custom Building Products
800-272-8786
CustomTechFlooring.com
SS192 12/18R



A DIVISION OF

CUSTOM®

A QUIKRETE® COMPANY