

TechPatchTW

Calcium Aluminate Based Rapid Curing Tilt Wall Finishing Compound

- Superior mixing and handling
- Excellent for tilt wall patch and finishing
- Featheredge to deep fill
- Mix with water only
- Dries quickly 15-60 minutes





TechPatch™ TW

Calcium Aluminate Based Rapid Curing Tilt Wall Finishing Compound

TechPatch™ TW is a rapid-curing, calcium aluminate cement based compound used to fill and finish exterior and interior concrete and masonry vertical surfaces. Use to hide large and small chips, holes and irregularities on tilt-up concrete; casted concrete and other masonry surfaces before painting or sealing.





Ordering Information

ITEM CODE	SIZE	PACKAGE
TPTW10T	10 lb. (4.5 kg)	Вох

Coverage

Typical square foot coverage per 10 lb. box (square meter per 4.5 Kg)

Square Feet				Square Meter	
Thickness	Minimum	Maximum	Thickness	Minimum	Maximum
SKIM COAT	100	300	SKIM COAT	9	27
1/8"	33.3	35.9	3 mm	3	3.3
1/4"	16.6	17.9	6 mm	1.5	17.9

Chart for estimating purposes. Coverage may vary based on installation practices and jobsite conditions. For more sizes, use the material calculator at CustomBuildingProducts.com or contact CUSTOM Technical Services at 800-282-8786.









MOBILE APP







Warranty: Flooring Installation Systems products are backed by up-to a 25-year warranty. See CustomTechFlooring.com for full warranty information including limitations and exclusions.

©2020 Custom Building Products. All rights reserved. The CUSTOM® and CustomTech® logos, and select product logos are registered trademarks of Custom Building Products, Inc. CUSTOM may make product modifications at any time without notice. Visit customtechflooring.com for updated technical data sheets and SDS information.

