



Select the industry standard in waterproofing and crack isolation membranes.

REDGARD®

Liquid Waterproofing and Crack Prevention Membrane

- Ready to use, roll it on
- Quick dry formula — 30% faster Drying*
- Meets ANSI A118.10, A118.12
- IAPMO rated as a shower pan liner with no fabric

*Faster drying compared to prior formula of RedGard



CUSTOM®

TILE INSTALLATION SYSTEMS



Waterproofing Benefits:

- Creates a continuous waterproof barrier
- Bonds directly to metal drains, PVC, stainless and ABS drain assemblies
- No reinforcing fabric needed
- Flood Test in 24 Hours

Waterproofing Approvals:

- Exceeds ANSI A118.10 requirements
- Meets Uniform Plumbing Code specifications for use as a shower pan liner
- Vaporproof — Meets ASTM E-96 Method E for use in steam showers

Anti-Fracture Benefits:

- Isolates existing cracks to 1/8" (3 mm)
- Rated Extra Heavy-Duty
- Thin application adds no appreciable thickness to floor
- Tile in 60 to 90 minutes

Anti-Fracture Approvals:

- Exceeds ANSI A118.12 requirements

Installations:

- Showers, tubs, steam showers and steam rooms
- Swimming pools and fountains
- Spas and hot tubs
- Terraces and balconies
- Facades

Areas of Use (Substrates):

- Concrete, cement mortar beds, masonry
- WonderBoard® Lite, cement backerboards
- Exterior grade plywood — For crack isolation of interior dry areas only
- Exterior decks — Contact Technical Services for information related to exterior application and the use of pressure treated wood decks
- Lightweight concrete
- Gypsum-based cement toppings

Available Sizes:

- 1 gallon (3.78 L)
- 3.5 gallon (13.2 L)

Coverage:

RedGuard as Crack Prevention Membrane:

SIZE	COVERAGE
1 gallon (3.78 L)	100 sq. ft. (9.3 M ²)
3.5 gallon (13.2 L)	350 sq. ft. (32.5 M ²)

RedGuard as Crack Prevention Membrane Meeting ANSI A118.12:

SIZE	COVERAGE
1 gallon (3.78 L)	25 sq. ft. (2.3 M ²)
3.5 gallon (13.2 L)	88 sq. ft. (8.2 M ²)

RedGuard as Waterproof Membrane:

SIZE	COVERAGE
1 gallon (3.78 L)	55 sq. ft. (5.1 M ²)
3.5 gallon (13.2 L)	192 sq. ft. (17.8 M ²)

RedGuard as IAPMO Pan Liner Meeting ANSI A118.10:

SIZE	COVERAGE
1 gallon (3.78 L)	40 sq. ft. (3.7 M ²)
3.5 gallon (13.2 L)	140 sq. ft. (13 M ²)

Charts are for estimating purposes. Coverage may vary based on installation practices and jobsite conditions. For more tile and joint sizes, use the material calculator at CustomBuildingProducts.com or contact CUSTOM Technical Services at 800-282-8786.



Select a qualifying system of Prep, Set and Grout products and CUSTOM will warranty the tile installation for life, including tile, materials and labor. See website for complete details.

DOWNLOAD CUSTOM'S MOBILE APP



Custom Building Products
800-272-8786
custombuildingproducts.com

SS162 9/19R

©2019 Custom Building Products. All rights reserved. The CUSTOM® logo and select product logos are registered trademarks of Custom Building Products, Inc. CUSTOM may make product modifications at any time without notice. Visit custombuildingproducts.com for updated technical data sheets and SDS information.

