

TileLab® Sulfamic Acid Cleaner

1 Product Name

TileLab® Sulfamic Acid Cleaner

2 Manufacturer

Custom Building Products
 Technical Services
 10400 Pioneer Boulevard, Unit 3
 Santa Fe Springs, CA 90670
 Customer Support: 800-272-8786
 Technical Services: 800-282-8786
 Fax: 800- 200-7765
 Email: contactus@cbpmail.net
custombuildingproducts.com

3 Product Description

Concentrated crystals that mix with water to make a mild, safe to use, acid cleaner. Removes dried Portland cement, grout haze and mortar residue from tile, concrete and masonry. Safe for use on colored grouts. Removes hard water deposits, efflorescence and also etches concrete.

Key Features

- Removes grout haze and residue

Uses

Use on all colors of grout, tile, clay pavers, concrete and masonry.

Limitations to the Product

Do not use on marble or other polished stone. May etch some glazed tile.

Packaging

1 lb (450 gm) tub

4 Technical Data

Technical Properties Chart

- pH of mixed solution is 2-3
- Complies with all Federal and CARB Standards for VOC

5 Instructions

Mixing Procedures

Mix solution in a plastic container using clean, warm water. Don't mix in metal container. Wear rubber gloves and eye protection. For removal of light mineral deposits and Portland cement grout haze or mortar residue on unglazed quarry or glazed tile with colored grout, mix 2 to 3 oz. (57 to 85 gm) with 1 gallon (3.78 L) of water. Mix 6 to 12 oz (170 to 340 gm) to 1 gallon (3.78 L) of water for unglazed tile or masonry that has gray-colored grout joints. For etching concrete or heavy-duty cleaning of old concrete, mix a minimum of 12 oz (340 gm) to 1 gallon (3.78 L) of water.

Note: Do not use on marble or other polished stone. This product may etch some glazed tile. Test solution on a small, inconspicuous area before proceeding. Don't allow product to contact metal fixtures.

Application of Product

WEAR IMPERVIOUS GLOVES, such as nitrile, eye protection and protective clothing when handling product.



Read entire label before using. Concrete and grout should be cured a minimum of 10 days and be clean. Saturate unglazed tile, concrete, masonry or grout with clean water for one hour prior to application. Apply solution to wet surface and scrub with a nylon bristle brush. Work in small areas. Flush with water immediately after brushing. Do not use repeatedly or surface damage could occur. For heavy concrete etching, allow solution to sit for up to 30 minutes prior to flushing with clean water.

Cleaning of equipment

Clean tools and hands with water before material dries.

Storage

- Close container tightly after each use
- Store in original container only
- Store in and use in temperatures between 40°F - 90°F (4°C and 32°C)
- Store in areas inaccessible to small children
- Do not reuse empty container, wrap and discard in trash or recycle

Health Precautions

IMPORTANT: Read carefully before using. WEAR IMPERVIOUS GLOVES, such as nitrile, eye protection, and protective clothing. DANGER: CORROSIVE TO THE SKIN AND EYES. May be harmful if swallowed. Do not mix with other chemical products. Do not get in eyes. Do not get on skin or clothing. Do not breathe in vapors. Do not take internally. Immediately wash contaminated body and clothing thoroughly. Use in well-ventilated areas. Take off contaminated clothing and wash before reuse. If eye or skin contact occurs: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If inhaled: Remove person to fresh air and keep comfortable for breathing. If swallowed: Rinse mouth. Do NOT induce vomiting. Immediately seek medical advice or attention if symptoms are significant or persist. In Emergency: 1-800-535-5053. **Contains: Sulfamic acid.** Before handling read Safety Data Sheet at www.custombuildingproducts.com. **KEEP OUT OF REACH OF CHILDREN.**

For more ingredient information please visit www.custombuildingproducts.com/cleaning



TileLab® Sulfamic Acid Cleaner

6 Availability & Cost

Location	Item Code	Size	Package
USA	TLSACRA1	1 lb (450 gm)	Container
Canada	CTLSAC1	1 lb (450 gm)	Container

7 Product Warranty

Obtain the applicable **LIMITED PRODUCT WARRANTY** at www.custombuildingproducts.com/product-warranty or send a written request to Custom Building Products, Inc., Five Concourse Parkway, Atlanta, GA 30328, USA. Manufactured under the authority of Custom Building Products, Inc. © 2017 Quikrete International, Inc.

8 Product Maintenance

Properly installed product requires no special maintenance.

9 Technical Services Information

For technical assistance, contact Custom® Building Products.

10 Filing System

Additional product information is available from the manufacturer upon request.

VOC Content

Contains no VOC's

TileLab® Sulfamic Acid Cleaner

Coverage

SIZE	Min Coverage	Max Coverage
1 Gallon (3.78 L)	300 sq. ft. (28 M ²)	

