

StoneSpecific® Polished Marble, Travertine & Limestone Sealer

1 Product Name

StoneSpecific® Polished Marble, Travertine & Limestone Sealer

2 Manufacturer

Custom Building Products
 Technical Services
 10400 Pioneer Boulevard, Unit 3
 Santa Fe Springs, CA 90670
 Customer Support: 800-272-8786
 Technical Services: 800-282-8786
 Fax: 800- 200-7765
 Email: contactus@cbpmail.net
custombuildingproducts.com

3 Product Description

Available in Canada only.

Optimum protection on medium-density polished stone - marble, travertine and limestone. Designed to penetrate and seal the polished stone surfaces to provide optimal protection, keeping your natural stone clean, vibrant and new.

A premium water-based formula that is non-combustible. Low odor, pH neutral it can be used indoors or out, in commercial or residential applications. Allows moisture vapor transmission. Protects sanded or non-sanded grouts.

StoneSpecific® Low VOC (Volatile Organic Compound) formulas help provide better indoor and outdoor air quality compared to similar traditional products. Complies with EPA and CARB VOC Requirements.

Suitable Tile Types

Provides optimum protection for all types of polished stone such as marble, travertine and limestone. Specifically formulated to protect polished, medium density porous natural stone.

Benefits of Product in the Installation

When optimum protection is required for polished natural stone. Protects fabricated or tiled stone surfaces covering kitchens, baths, walls or floor surfaces.

Packaging

1 quart (946 ml) bottle

4 Technical Data

Technical Properties Chart

- Excellent stain resistance to most household contaminants (CTI-072)
- No darkening of stone

5 Instructions

General Surface Prep

Surface should be dry, clean and free of waxes, sealers or finishes. TileLab® Heavy-Duty Cleaner & Stripper will clean the surface or strip wax and acrylic finishes. New installations: Allow grout to cure 48 hours before applying sealer.

Application of Product

WEAR IMPERVIOUS GLOVES, such as nitrile, and eye protection when handling product.



Test product in obscure area to ensure desirable results. Apply liberally using a new mop, lambswool applicator or sponge. Maintain a thin, even coat to cover surface, working-in sealer for 5 – 10 minutes. Surface must stay wet letting sealer soak for additional 10 minutes, allowing for maximum penetration. Immediately after, wipe off any sealer completely before it dries. If initial coat has been absorbed, apply additional coat 15 minutes after first application.

Pre-Grout Sealer/Grout Release

Porous tile, such as clay and Saltillo pavers, can be stained by grout during installation. Sealing the tile before grouting will make grout removal much easier. Apply two coats of sealer according to directions after tile has been bonded for a minimum of 24 hours, or apply to front face of tile before installation.

Drying Time

Drying time 2 – 3 hours. Do not clean for 24 hours.

Cleaning of equipment

Clean tools and hands with soap and water immediately after use.

Health Precautions

CAUTION: MAY IRRITATE EYES. MAY IRRITATE SKIN. MAY CAUSE RESPIRATORY IRRITATION. Do not mix with other chemical products. Do not get on skin or clothing. Do not get in eyes. Do not breathe fumes. Do not swallow. **KEEP OUT OF REACH OF CHILDREN.** Use only in a well-ventilated area. Wear chemical resistant gloves, CSA approved respirator, and eye protection. **FIRST AID TREATMENT:** Contains: Fluoropolymer, quarternary amine compound and d-Limonene. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water. If breathed in, move person into fresh air. In emergency, call (800) 535-5053.

6 Availability & Cost

Item Code	Size	Location	Package
CSSPMSQT-3	1 qt (946 ml)	Canada	Bottle



CUSTOM®

StoneSpecific® Polished Marble, Travertine & Limestone Sealer

7 Product Warranty

Obtain the applicable **LIMITED PRODUCT WARRANTY** at www.custombuildingproducts.com/product-warranty or send a written request to Custom Building Products, Inc., Five Concourse Parkway, Atlanta, GA 30328, USA. Manufactured under the authority of Custom Building Products, Inc. © 2021 Quikrete International, Inc.

8 Product Maintenance

Do not use cleaners containing ammonia, acids or bleach. Use an appropriate TileLab® or Aqua Mix® neutral cleaner. Tile industry experts recommend periodic testing of sealed surfaces. Apply a few drops of water on the surface. If it soaks in, a coat of TileLab® or Aqua Mix® sealer will be necessary to keep sealer at peak performance.

9 Technical Services Information

For technical assistance, contact Custom® Building Products.

10 Filing System

Additional product information is available from the manufacturer upon request.

VOC Content

Less than 10 g/L (<0.5% CARB VOC)

Expected Wear

Lasts up to 20 years under normal conditions depending on hardness and texture of surface. Use factors, cleaning routines, harsh cleaning methods, sun exposure and weather conditions will affect wear.

Related Products

StoneSpecific® Marble, Travertine Limestone & Slate Cleaner/Resealer

StoneSpecific® Polished Marble, Travertine & Limestone Sealer

Coverage

Size	Min Coverage	Max Coverage
Quart (946ml)	200 sq. ft. (18.6 M ²)	300 sq. ft. (27.9 M ²)

