

StoneSpecific® Polished Granite Counter Kit (Canada Only)

1 Product Name

StoneSpecific® Polished Granite Counter Kit (Canada Only)

2 Manufacturer

Custom Building Products
 Technical Services
 10400 Pioneer Boulevard, Unit 3
 Santa Fe Springs, CA 90670
 Customer Support: 800-272-8786
 Technical Services: 800-282-8786
 Fax: 800- 200-7765
 Email: contactus@cbpmail.net
custombuildingproducts.com

3 Product Description

The Polished Granite Counter Kit includes everything needed to optimally protect and shine polished stone counters by hand. Perfect for maximum protection and shine on kitchen counters, vanities and vertical stone walls decorative stone fixtures. Hides light etching and restores the lustrous finish.

StoneSpecific® Low VOC (Volatile Organic Compound) formulas help provide better indoor and outdoor air quality compared to similar traditional products. Complies with EPA and CARB VOC Requirements.

Do not use on floors.

Suitable Tile Types

Formulated to best work on polished granite, but can be used on all stones such as, marble, travertine, limestone, onyx, terrazzo.

Packaging

- Kit Containing (1) 16 oz. (473 ml) bottle Polished Granite Sealer, (1) 8 oz. (237 ml) bottle Stone Polish, (2) Cotton buffing cloth

4 Technical Data

Technical Properties Chart

- Stain resistant to most household contaminants (CTI - 072)
- Improves gloss of smooth granite
- Does not darken granite

5 Instructions

General Surface Prep

The surface must be clean, dry and free of wax, coatings or finishes. TileLab® Heavy-Duty Cleaner & Stripper will clean the surface and remove any wax or acrylic finishes.

Application of Product

USE CHEMICAL-RESISTANT GLOVES, such as nitrile, when handling product.

Test in an inconspicuous area of stone prior to application for desired results. Apply sealer (Part 1) liberally using a sponge or brush. Allow it to penetrate for 15 – 30 minutes. Wipe off any excess before it dries on the surface of the stone. If first coat has been absorbed, apply a second coat immediately following the same procedure. Very porous surfaces may require additional applications. Wait 1 hour before applying Polish (Part 2). Shake Granite Polish (Part 2) well and apply a thin, even coat to surface of stone just sealed. Apply sparingly; only a small amount is needed. Use a dry, clean cloth provided to apply polish. Wipe clean once polish has set for 8 – 10 minutes. Buff surface to a shine with the second clean, dry cloth provided. Wipe surface with clean, dry cloth as a final step.

Pre-Grout Sealer/Grout Release

Porous tile, such as clay and Saltillo pavers, can be stained by grout during installation. Sealing the tile before grouting will make grout removal much easier. Apply two coats of sealer according to directions after tile has been bonded for a minimum of 24 hours, or apply to front face of tile before installation.

Drying Time

Drying time 2 – 3 hours. Once satisfied with application, do not clean newly sealed surface until 24 hours after application.

Cleaning of equipment

Clean tools and hands with soap and water immediately after use.

Health Precautions

MAY BE HARMFUL IF SWALLOWED. Do not induce vomiting. Give plenty of water and call a physician immediately. If eye contact occurs, flush immediately with plenty of water for 15 minutes. If contact with sensitive skin occurs, wash with soap and water. Call physician if necessary. Do not mix with other solutions.

6 Availability & Cost

Item Code	Size	Location	Package
SSTHMSQT-3	1 quart (946 ml)	USA	Bottle
CSSTHMSQT-3	1 quart (946 ml)	Canada	Bottle

7 Product Warranty

Obtain the applicable **LIMITED PRODUCT WARRANTY** at www.custombuildingproducts.com/product-warranty or send a written request to Custom Building Products, Inc., Five Concourse Parkway, Atlanta, GA 30328, USA. Manufactured under the authority of Custom Building Products, Inc. © 2017 Quikrete International, Inc.

8 Product Maintenance

Do not use cleaners containing ammonia, acids or bleach. Use an appropriate TileLab® or Aqua Mix® neutral cleaner. Tile industry experts recommend periodic testing of sealed surfaces. Apply a few drops of water on the surface. If it soaks in, a coat of TileLab® or Aqua Mix® sealer will be necessary to keep sealer at peak performance.



StoneSpecific® Polished Granite Counter Kit (Canada Only)

9 Technical Services Information

For technical assistance, contact Custom® Building Products.

10 Filing System

Additional product information is available from the manufacturer upon request.

StoneSpecific® Polished Granite Counter Kit (Canada Only)

Coverage

Size	Min Coverage	Max Coverage
Quart (946ml)	200 sq. ft. (18.6 M ²)	300 sq. ft. (27.9 M ²)



CUSTOM®