

# Waterproofing and Anti-Fracture Membrane Mesh

## 1 Product Name

Waterproofing and Anti-Fracture Membrane Mesh

## 2 Manufacturer

Custom Building Products  
 Technical Services  
 10400 Pioneer Boulevard, Unit 3  
 Santa Fe Springs, CA 90670  
 Customer Support: 800-272-8786  
 Technical Services: 800-282-8786  
 Fax: 800- 200-7765  
 Email: [contactus@cbpmail.net](mailto:contactus@cbpmail.net)  
[custombuildingproducts.com](http://custombuildingproducts.com)

## 3 Product Description

An alkali-resistant fiberglass tape used to reinforce RedGard® when used over cracks in underlayment. It can also be used in corners and wherever there is a change of plane in the installation for additional reinforcement.

### Key Features

- Helps prevent cracks in tile and breaks in waterproofing
- Reinforces liquid-applied membranes when used over cracks or changes of plane in underlayment

### Suitable Substrates

- Concrete, cement mortar, masonry
- Cement Backerboard
- Exterior Plywood and OSB (interior, dry areas only)
- Exterior Decks – Contact Technical Services
- Post-Tension Concrete – Contact Technical Services
- Lightweight Concrete (min. 2000 psi compressive strength)
- Gypsum-Based cement topping (min. 2000 psi compressive strength)
- Existing ceramic tile and resilient flooring

### Composition of Product

Fiberglass mesh with an alkali-resistant coating.

### Benefits of Product in the Installation

Helps prevent cracks occurring in the tile or breaks in the waterproofing and crack isolation treatments in areas with expected higher degree of movement such as changes of plane.

## 4 Technical Data

### Applicable Standards

No industry standards are available for tape alone.

### Approvals

None applicable.

### Technical Properties Chart

- Fiberglass mesh design
- Alkali-resistant coating

### Environmental Consideration

Custom® Building Products is committed to environmental responsibility in both products produced and in manufacturing practices. Use of this product may contribute to LEED® certification.

Published Date: 1/5/2021



## 5 Instructions

### General Surface Prep

Exterior and wet areas must have proper sloping to drains. All surfaces must be structurally sound, clean, dry and free from contaminants that would prevent a good bond. Newly prepared concrete must be troweled smooth and textured to a fine broom finish and cured for 28 days. Existing surfaces must be scarified and leveled, and all defects must be repaired. Cracks exceeding 1/8" (3 mm) should be treated in accordance with TCNA F125 or TCNA F125A.

### Movement Joint Placement

Do not bridge joints designed to experience movement. Carry these types of joints through the tile work. Clean the joint and install an open or closed cell-backer rod to the proper depth, as outlined in the Tile Council Handbook, EJ171. Next compress sealant into the joint, coating the sides and leaving the sealant flush with the surface. When the sealant is dry, place bond-breaker tape over the joint. Apply a minimum 3/64" (1.2 mm) of RedGard® over the joint and the substrate, following the instructions provided previously. Install the tile work onto the membrane, but do not bridge the joint. After the tile work is properly set, follow the architect's and manufacturer's instructions to fill the joint with a specified color sealant.

### Application of Product

Follow installation instructions provided with RedGard® Waterproofing and Anti-Fracture Membrane.

### Cleaning of equipment

Clean tools and hands with water before the material dries.

### Health Precautions

Wear impervious gloves and eye protection while using this product. Avoid contact with eyes or prolonged contact with skin. Wash thoroughly after handling. If eye contact occurs, rinse cautiously with water for several minutes, remove contact lenses if easy to do: continue rinsing. Immediately seek medical advice if symptoms are significant or persist. Do not take internally. KEEP OUT OF REACH OF CHILDREN.

### Conformance to Building Codes

Installation must comply with the requirements of all applicable local, state and federal code jurisdictions.



# CUSTOM®

# Waterproofing and Anti-Fracture Membrane Mesh

---

## 6 Availability & Cost

Item Code	Size	Package
TNSM6	6" x 150'	Roll

## 7 Product Warranty

Obtain the applicable **LIMITED PRODUCT WARRANTY** at [www.custombuildingproducts.com/product-warranty](http://www.custombuildingproducts.com/product-warranty) or send a written request to Custom Building Products, Inc., Five Concourse Parkway, Atlanta, GA 30328, USA. Manufactured under the authority of Custom Building Products, Inc. © 2017 Quikrete International, Inc.

## 8 Product Maintenance

Properly installed product requires no special maintenance. Do not use as a wear surface.

## 9 Technical Services Information

For technical assistance, contact Custom technical services at 800-272-8786 or visit [custombuildingproducts.com](http://custombuildingproducts.com).

## 10 Filing System

Additional product information is available from the manufacturer upon request.

---

### Related Products

RedGard® Waterproofing and Crack Prevention Membrane



# CUSTOM®