

# TileLab® Stone Sealer & Enhancer

## 1 Product Name

TileLab® Stone Sealer & Enhancer

## 2 Manufacturer

Custom Building Products  
 Technical Services  
 10400 Pioneer Boulevard, Unit 3  
 Santa Fe Springs, CA 90670  
 Customer Support: 800-272-8786  
 Technical Services: 800-282-8786  
 Fax: 800- 200-7765  
 Email: [contactus@cbpmail.net](mailto:contactus@cbpmail.net)  
[custombuildingproducts.com](http://custombuildingproducts.com)



## 3 Product Description

Color enhancer and penetrating sealer for all types of porous natural stone and grout. Rejuvenates the color and appearance of worn, faded stone, tumbled-marble and other rustic-look stones. Can also be used to darken the color of grout. Provides long-lasting protection against oil, grease and stains. Its water-based, low-odor formula can be used for interior and exterior use.

### Key Features

- Seals for stain protection and enhances the look

### Uses

- Unsealed natural stone such as marble, granite, slate, limestone, travertine, quartzite, and sandstone
- Effective for interior and exterior applications

### Benefits of Product in the Installation

- Excellent stain resistance to most household contaminants (CTI-072)
- Darkens most stone to a "wet look"
- Complies with all Federal and SCAQMD Standards for VOCs

### Packaging

24 fl. oz. (709 ml) Spray Bottle

## 4 Instructions

### General Surface Prep

Surface should be dry, clean and free of waxes, sealers, or finishes. Do not apply directly over silicone sealers, oil or wax based finishes. TileLab® Heavy-Duty Stripper & Cleaner will clean the surface and remove wax or old acrylic finishes. Place a few drops of water on various tiles. If water doesn't penetrate, additional removal is necessary. Gloss Sealer & Finish can be applied over any TileLab® sealer except Stone Sealer & Enhancer. New installations need to be cured at least 48 hours before application. Clay and Saltillo tile may require extended drying time depending on temperature and humidity. Make sure the tiles are completely dry before application. Test product in obscure area to ensure desirable results.

### Application of Product

**USE CHEMICAL-RESISTANT GLOVES, such as nitrile, when handling product.**

Apply liberally using a new mop, paint pad or sponge. Allow to penetrate for up to 5 minutes. Immediately wipe off any sealer completely before it dries. Immediately apply a second coat. Ensure no residue is left to dry on the surface. Do not use outside if inclement weather is expected within 24 hours. Clean off any residue left on the surface with an appropriate TileLab® cleaner. **Note: The more porous the stone, the deeper the color enhancement.**

### Drying Time

4 – 6 hours.

### Cleaning of equipment

Clean tools and hands with soap and water immediately after use.

### Storage

- Close container tightly after each use
- Store in original container only
- Store and use between temperatures of 45°F - 85°F (7°C - 29°C)
- Dispose of residue or any unused leftover product in accordance with applicable federal, state, and local requirements

### Health Precautions

MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear skin and eye protection. Contains ethylene glycol, dibutyl phthalate, dipropylene glycol methyl ether and acrylic polymer. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting, seek medical attention. KEEP OUT OF REACH OF CHILDREN.

## 5 Availability & Cost

Location	Item Code	Size	Package
USA	TLSES24Z	24 fl. oz. (709 ml)	Spray Bottle
Canada	CSSSESQT-3-3	1 qt (946 ml)	Bottle

## 6 Product Warranty

Obtain the applicable **LIMITED PRODUCT WARRANTY** at [www.custombuildingproducts.com/product-warranty](http://www.custombuildingproducts.com/product-warranty) or send a written request to Custom Building Products, Inc., Five Concourse Parkway, Atlanta, GA 30328, USA. Manufactured under the authority of Custom Building Products, Inc. © 2017 Quikrete International, Inc.



# TileLab® Stone Sealer & Enhancer

---

## 7 Product Maintenance

Use an appropriate TileLab® or Aqua Mix® neutral cleaner for routine cleaning.

## 8 Technical Services Information

For technical assistance, contact Custom® Building Products.

## 9 Filing System

Additional product information is available from the manufacturer upon request.

## 10 VOC Content

No VOCs



**CUSTOM®**

# TileLab® Stone Sealer & Enhancer

---

## Coverage

Size	Min Coverage	Max Coverage
<b>On Porous Surfaces:</b>		
24 fl. oz. (709 mL)	30 sq. ft. (2.8 M <sup>2</sup> )	65 sq. ft. (6 M <sup>2</sup> )
<b>On Polished or Dense Surfaces:</b>		
24 fl. oz. (709 mL)	130 sq. ft. (12 M <sup>2</sup> )	190 sq. ft. (17.6 M <sup>2</sup> )

**CUSTOM®**