

Wood UR Ultimate Adhesive

1 Product Name

Wood UR Ultimate Adhesive

2 Manufacturer

Custom Building Products
7711 Center Avenue
Suite 500
Huntington Beach, CA 92647
Customer Support: 800-272-8786
Technical Services: 800-282-8786
Fax: 800- 200-7765
Email: contactus@cbpmail.net
custombuildingproducts.com

3 Product Description

Wood UR is a professional grade, low solvent, moisture cured urethane adhesive. This classic formulation has been developed to maximize bond strength and elasticity, while minimizing effort needed to trowel. All of this results in a reliable wood adhesive suited for any variety of job.

Suitable as an adhesive

- Solid Wood Plank
- Engineered Wood Plank
- Bamboo (not strand woven)
- Ceramic Tile
- Natural Stone Inlays
- Plywood Panels [for nail down/double bond installations]
- Underlayments [Recycled rubber/cork]

Key Features

Features/Benefits of Product in the Installation

- Easy troweling results in faster installation times
- Excellent green grab for trouble-free installations
- Superior elasticity allows for natural expansion and contraction of wood
- Low odor formulation ideal for occupied environments

Suitable Substrates

- Flooring underlayment and Wood Manufacturer approved substrates
- Cement-based self-leveling underlayment and patching compounds
- Cement/epoxy terrazzo
- Concrete (industry approved) - at least 14 days old with an appropriate moisture vapor barrier properly installed
- Epoxy Coatings
- Existing well bonded floor coverings
- Plywood and other approved wood substrates
- Properly prepared primed/sealed gypsum underlayment per ASTM F2419
- Radiant heated floors (temperature should not exceed 85° F)

* All surfaces / substrates above require proper surface preparation

Acceptable Substrate Conditions



- RH – 80 % / ASTM F2170 Relative Humidity in Concrete Floor Slabs
- pH [Substrate] – up to 12
- Adhesive is suitable for MVER – up to 5 lbs. / per ASTM F1869 Moisture Vapor Emission Rate – See wood flooring manufacture for product limitations and requirements

* Contact Technical Services for test results/readings outside above conditions.

Limitations to the Product

IMPORTANT NOTE: Finished Flooring limitations and requirements will supersede recommendations of WOOD UR adhesive. Consult flooring manufacturer for performance data and recommendations.

- For interior use only
- Do not use when ambient and/or substrate temperature is below 50° F (10 C) or above 95° F (35 C) or when condensation exists
- Do Not install over surfaces with condensation or standing water.
- Not for use in areas subject to hydrostatic moisture conditions
- Concrete substrate temperatures must be above dew point/condensation
- Not for use as a moisture mitigation system under any other flooring types [see CustomTECH™ MVC]
- Existing adhesive must be removed to an embedded residue with no surface trowel ridges [For installation of Bamboo flooring – completely remove all adhesive residues]
- Do not install over treated plywood
- Do not dilute with water, solvents or any chemicals.

4 Technical Data

Applicable Standards

- NWFA / National Wood Flooring Association — Wood Flooring Installation Guidelines
- ASTM F710 Standard Practice for Preparing Concrete Floors to Receive Resilient Flooring
- ASTM E96 Standard Test Methods for Water Vapor Transmission of Materials
- ICRI / International Concrete Institute
- ASTM F2419 Standard Practice of Thick Poured Gypsum Concrete Underlayments and Preparation of the Surface



CUSTOM®

Wood UR Ultimate Adhesive

Technical Chart

Product Data	Composition	100% Moisture Curing Polyurethane
	Appearance	Thick Creamy Paste
	Base color	Dark tan
Product Timing	Open/Working time	60-90 minutes
Service Timing	Installation - Light Traffic	4 hours
	Installation - Moderate/Heavy	24 hours
	Installation - Full Service / Heavy Rolling	48 hours
Moisture Data	RH / Relative Humidity	up to 85%
	MVER/Moisture Vapor Emission Rate	up to 8 lbs.

Storage	Shelf life	1 year — stored in original unopened packaging at 73° F (23° C)
	Storage Conditions required	50° F to 100° F (4° C to 38° C)

Environmental and Sustainability	Solvents	Minimal
	VOCs (Rule #1168 of California's SCAQMD)	<30 g/L
	*LEED Credits / MR5 and IEQ 4.1	Regional and low emitting materials
	Red List Free: https://living-future.org/declare/declare-about/red-list/	LBC / Living Building Challenge: This product has been verified to be free of any chemicals listed per the most current Red List on the LBC's website.

Health and Safety	CAUTION WARNING	Irritant, Sensitizer
	Contains	MDI isocyanate May cause skin and respiratory sensitization.
	Before using product read Safety Data Sheet (SDS).	Intentional misuse by deliberate concentration and inhalation of vapors may be harmful or fatal.

Environmental Consideration

Custom® Building Products is committed to environmental responsibility in both products produced and in manufacturing practices. Use of this product may contribute to LEED® certification.

5 Instructions

Installation

1. Use Proper PPE/Personal Protective Equipment when handling product.
2. Install wood flooring according to the wood-flooring manufacturer's written instructions.
3. Spread the adhesive on the substrate using the recommended trowel. See Trowel table below and always follow finish floor covering manufactures trowel recommendations.
4. Trowel ridge lines should be perpendicular to the wood-flooring installation direction to ensure proper coverage.
5. Do not go beyond the working time of the product to prevent bond failure.
6. Press firmly into the wet adhesive bed to compress all ridges.
7. Occasionally lift up a board and check the subfloor for 100% coverage which is critical for moisture control. If proper transfer is not achieved, reapply using the recommended trowel.
8. Use of adhesive for ceramic tile and stone installations should be limited to insets and complimentary designs to wood installation. For larger areas, it is recommended to use a suitable Custom Building Products tile/stone adhesive.
9. Evaluate suitability with tile and natural stone. In specific, the potential for staining of natural stone or absorptive tiles.
10. Working and drying time of the adhesive is influenced by temperature, humidity of the room, air-flow and substrate temperatures/porosity.
11. Roll flooring's width and length with wood/flooring manufacture's recommended weight roller.
12. Allow for normal wood expansion at wall perimeter and all restraining abutments.
13. PROTECTION – General Contractor, Flooring Contractor and Building owner must provide proper climate controls per flooring manufacturers requirements before, during and after flooring installation.

General Surface Prep

All surfaces must be structurally sound, without excessive deflection, clean, dry and free from contaminants that would prevent or inhibit adhesion bonding. Concrete and cement-based underlayment/patching compounds used to repair flatness deviations must be fully cured and not exhibit signs of moisture or hydrostatic conditions/issues.



CUSTOM®

Wood UR Ultimate Adhesive

Concrete substrates must have porosity/absorption as outlined by ASTM F3191 Field Determination of Substrate Water Absorption, a droplet of water must absorb into concrete within 1 minute. Concrete surfaces must meet a #1-3 CSP/Concrete Surface Profile (not polished/reflective) as defined by ICRI/International Concrete Repair Institute's Guideline No. 03732. Substrates should be free of laitance, contaminants, surface/dissipating curing compounds. To remove curing compounds, construction debris, open up non absorptive concrete substrates, shot-blasting and/or diamond grinding methods are best methods to prepare and clean when and where necessary.

All surfaces must be flat, sound and stable. Floor Flatness requirements of 3/16" allowable variation in 10ft. apply and/or per wood manufacture and NWFA Installation Guidelines.

Any sources of moisture are to be limited to initial concrete placement and not from sources such as water intrusion or from a lack of an effective vapor retarder/barrier under concrete slab. Substrate must be prepared per ASTM F710 standards.

It is the responsibility of the installer to determine the suitability of the substrate and any required preparation work necessary to ensure a successful installation.

Assembly mockups will determine suitability for these conditions on specific projects. Contact CUSTOM Technical Services for product information (800) 282-8786.

Fill all surface cracks, grooves, depressions, control joints and non-moving joints According to ASTM F710. Contaminants or curing compounds should be mechanically removed before installation.

Concrete must be free of efflorescence and hydrostatic pressure conditions. All concrete surfaces must have a minimum tensile strength in excess of 200 psi (1.4 n/mm²). HVAC must be operational between 60-95°F/30-65% relative humidity for ambient conditions a minimum of 72 hours prior to installation enabling the substrate and adhesive to be properly acclimated. Consult the flooring manufacture for site conditioning requirements and acclimation requirements of their materials. Large temperature and relative humidity discrepancy will affect the working time of the adhesive. Disable radiant system 24 hours prior, during and after installation — Follow radiant system manufacture's instruction for start-up procedures.

Cleaning of equipment

Consult the wood manufacture for cleaning wood finish surface instructions. To remove cured adhesive from prefinished flooring, use a citrus cleaner or mineral spirits. Apply the adhesive remover to the affected area with a non-abrasive towel and allow to sit for 5-10 minutes to soften the adhesive. Then buff the adhesive off with the non-abrasive towel. Use personal protective equipment (chemical resistant gloves/ goggles/clothing). Without direct contact, remove spilled or excess product and placed in suitable sealed container. Dispose of excess product and container in accordance with applicable environmental regulations.

Conformance to Building Codes

Installation must comply with the requirements of all applicable local, state and federal code jurisdictions.

6 Availability & Cost

Contact the manufacturer or visit custombuildingproducts.com for information about product cost and availability.

ITEM CODE	SIZE	PACKAGE
UWAT5	5 gal (18.9 L)	Pail

7 Product Warranty

- 2 Years – Product only, unopened and properly stored.
- 15 Year System – CUSTOM Adhesive and CustomTECH Floor Preparation Systems.
- FLOOR-MATCH Warranty – CUSTOM Adhesives & CustomTECH Floor Preparation Products/Systems are warranted equal to the Flooring manufacturer's warranty term up to LIFETIME. *See CUSTOM FLOOR-MATCH Warranty, separate document.

8 Product Maintenance

Follow wood flooring manufacturers written instructions for proper maintenance, chemicals and techniques.

Properly installed product requires no special maintenance, see flooring manufacture for service and maintenance requirements.

9 Technical Services Information

For technical assistance, contact Custom Technical Services at (800) 282-8786 or contact us online at custombuildingproducts.com.

10 Filing System

Additional product information is available from the manufacturer upon request.



CUSTOM®

Wood UR Ultimate Adhesive

Coverage




SQUARE FOOT COVERAGE PER GALLON (SQUARE METER PER 3.8 L)		
Wood Flooring > 5/8" (16 mm) thick	30 - 35 sq. ft. (2.79 - 3.25 M ²)	1/4" x 1/4" x 1/4" (6.4 x 6.4 x 6.4 mm) SQ 
Solid or Engineered Wood 1/2" to 5/8" (12.7 - 16 mm) thick	40 - 50 sq. ft. (3.72 - 4.65 M ²)	1/4" x 1/8" x 1/4" (6.4 x 3.2 x 6.4 mm) SQ 
Engineered Wood up to 1/2" (12.7 mm) thick	45 - 50 sq. ft. (4.18 - 4.65 M ²)	3/16" x 5/32" (4.8 x 4.0 mm) V 

Chart for estimating purposes. Coverage may vary based on installation practices and jobsite conditions. For more sizes, use the material calculator at CustomBuildingProducts.com or contact CUSTOM Technical Services at 800-282-8786.



CUSTOM[®]