CUSTOM® Wood HP4, CUSTOM® Wood UR and CUSTOM® Wood UR4 are recommended for use as a bonding adhesive for the below product:



Centaur Floor Systems "PUZZLETILE", is a vulcanized composition rubber interlocking tile designed for easy and fast installation. This product offers a great surface solution with outstanding durability in a cost-effective system. https://www.centaurfloors.com/

Product thickness:

8mm (0.40-inch) thickness

PUZZLETILE Technical Manual:

https://www.centaurfloors.com/document/ik8qj9kqqd7tjdi7o4v9sjnl7i?filename=CENTAURPuzzleTileTechnicalManual14Jul2021.pdf

Installation:

- Use below adhesive options for PUZZLETILE installation to suitable substrates.
- Install with wet set method only (place into wet adhesive).
- Trowel recommendation 1/4" x 1/8" x 1/4" square notch.
- Install above product per manufacture's technical data sheet instructions.
- Install below adhesives per technical data sheet instructions.

Adhesive Options:

- Wood HP4 4-In-1 Hybrid Polymer Adhesive (4-in-1 product works as an adhesive, concrete moisture barrier, sound reducer and crack suppressant all in one). https://www.custombuildingproducts.com/TDS/TDS-364.pdf
- Wood UR Ultimate Adhesive (is a professional grade, low solvent, moisture cured urethane adhesive).
 https://www.custombuildingproducts.com/TDS/TDS-365.pdf
- Wood UR4 Ultimate Adhesive (4-in-1 product works as a urethane adhesive, concrete moisture control, sound reducer and crack isolation membrane). https://www.custombuildingproducts.com/TDS/TDS-366.pdf

Patching Compound Options:

- Silk™ Patching & Finishing Compound (ASTM C109 / ASTM F710 compressive strength requirements). https://www.custombuildingproducts.com/TDS/TDS244.pdf
- Tech Patch-MP Multipurpose Rapid Setting Skim Coat & Floor Patch (ASTM C109 / ASTM F710 compressive strength requirements). https://www.custombuildingproducts.com/TDS/TDS326.pdf



^{*}Refer to Product Technical Data Sheet for complete installation instructions, requirements and product limitations.